

ZoomSHOT 4K with OneLINK HDMI System **SKU: 999-69350-200W**



A low-cost point-of-view camera with UHD 4K image quality.

Key Features:

- 30x powered zoom with 70.2° horizontal field of view
- Up to 2160p/30 HD image quality
- HDMI output
- Local 12V power supply for camera included or available with optional OneLINK HDMI or OneLINK Bridge Extension Systems
- RS-232 Control
- Manual Pan/Tilt with EZ Set tensioning system
- Compatible with Kensington lock

The ZoomSHOT 4K is a cost-effective, versatile, high-definition point-of-view camera well-suited for small, medium, and large rooms. It is designed to support a wide range of applications, including houses of worship, pro A/V system integration, live events, IMAG systems, UCC applications, videoconferencing, distance learning classrooms and lecture capture. The camera captures with a full HD 1/2.5" Sony Exmor 8.57 megapixel 2160p image sensor, 30x optical zoom, and 70.2° horizontal field of view. It also features a manual pan/tilt, an EZ Set tensioning system, and a presenter-friendly IR remote control. The ZoomSHOT 4K OneLINK HDMI System is easy to install and use.

The ZoomSHOT 4K is a reliable and affordable solution for your video capture needs. Record a lecture, conduct a video conference, or capture live events with outstanding performance and quality. Versatile features, outputs, and ease of use, make this system an excellent choice. Can also be used as a stand alone camera with no extension system if desired.

This Package Includes:

- ZoomSHOT 4K camera (black or white)
- Thin Profile Wall Mount (black or white) with mounting hardware
- Vaddio IR Shot Commander remote with 2x AAA batteries
- OneLINK HDBT EZIM (easy interface module)
- Cables to connect ZoomSHOT 4K to EZIM
- OneLINK HDMI HDBT extension
- 48V power supply for OneLINK Bridge with AC cord set(s)

Total Pixels: 2.14 Megapixel

Specifications

Dimensions &
Measurements

Depth	Camera: 5.8 in (14.73 cm) QMini: 3.58 in (9.1 cm)
Height	Camera: 7 in (17.78 cm) QMini: 1.24 in (3.15 cm)
Max Distance Support	150 ft (45.7 m)
Operating Temperature	32° to 104°F (0° to 40°C)
Product Weight	Camera: 3.5 lbs (1.59 kg) QMini: 1.12 lbs (0.51 kg)
Shipping Weight	1 lbs (0.5 kg)
Width	Camera: 5.5 in (14 cm) QMini: 4.46 in (11.3 cm)

Characteristics &
Features

3rd Party Control	RS232
Camera Type	Fixed
Color	White
Compatible With	Vaddio
Control Method	• IR Remote • RS232
Estimated Room Size	• Large Room • Medium Room

Field of View	70.2 Degrees Wide End
Field of View Wide	Greater than 70
Focus System	• Auto • Manual
Gain	• Auto • Manual
Image Sensor Type	1/2.8 Exmor CMOS
Input Ports	• EZ Power Video • RS232
Manufacturer	Vaddio
Max Resolution	2160p 30
Minimum Illumination	0.3 Lux
OneLINK Compatibility	No
Output Ports	HDMI 1.4b, RS-232
Pan and Tilt Range	• Tilt 30 degrees to negative 30 degrees • Unlimited Pan
Pan and Tilt Speed	Manual
Pixels	2.14 Megapixel
Power Cord	US Cord
Power Supply	• 208A • 24VDC
Power Type	• EZ Power • Local Power
Preset Positions	16
PTZ Motors	No Motors Manual
Quick-Connect Compatibility	QMini

Signal Type	USB 2.0
Solution Type	Camera with Extension
TAA Compliant	Yes
Tri-Sync Motion	No
UPC	840077509095
White Balance	• Auto • Manual
Zoom	30x

Certifications & Warranties

Certifications	• CE • FCC • TAA
Warranty	3 years

Source: https://www.legrandav.com/products/cameras/4k_fixed_camera/zoomshot-4k-hdmi-system/999-69350-200w