

# Product data sheet

Specifications



APC Rack PDU, 9000 switched,  
0U, 30A, 200V and 208V, 21 C13  
and C15, 3 C19 and C21 sockets

APDU9941

## Overview

Lead time Usually in Stock

## Main

Color	Black
Product or Component Type	PDU
PDU Type	Switched
Cord length	10 ft (3.05 m)
Number of cables	1
Provided Equipment	Installation guide Rack Mounting brackets Safety guide

## Complementary

Input Voltage	208 V 200 V
Height	72.008 in (182.9 cm)
Width	2.2 in (5.5 cm)
Output Voltage	200 V 208 V
Depth	1.8 in (4.6 cm)
Net Weight	18.7 lb(US) (8.5 kg)
Mounting Location	Side
Mounting preference	No preference
Input Plug Type	NEMA L6-30P
Mounting Mode	Not rack-mountable
Rack units	0U
USB compatible	No
Mounting position	Vertical
Communication Port Protocol	SNMP Redfish
Line Rated Current	24 A
Max line current	30 A
Input current limits	30 A
Load Capacity	4992 VA

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Input Frequency</b>	50/60 Hz
<b>Outlet type and quantity</b>	21C13/C15 3C19/C21
<b>Communication Network Type</b>	10/100/1000BASE-T

## Environment

<b>Product Certifications</b>	cUL Listed FCC part 15 class A PSE
<b>Standards</b>	ICES-003
<b>Ambient Air Temperature for Operation</b>	23...140 °F (-5...60 °C)
<b>Relative Humidity</b>	5...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient Air Temperature for Storage</b>	-13...149 °F (-25...65 °C)
<b>Storage Relative Humidity</b>	5...95 %
<b>Storage altitude</b>	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

<b>GTIN</b>	731304356264
-------------	--------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	80.3 in (204 cm)
<b>Package 1 Width</b>	4.9 in (12.4 cm)
<b>Package 1 Length</b>	6.5 in (16.5 cm)
<b>Package 1 Weight</b>	22.05 lb(US) (10 kg)

## Contractual warranty

<b>Warranty</b>	3 years repair or replace
-----------------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

**Weee** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)