

# APC KVM 2G, SERVER MODULE, DVI WITH VIRTUAL MEDIA AND CAC

KVM-DVIVMCAC

_			•	
( )	VP	rv/	ıP	۱۸/

Lead time Usually in Stock

#### Main

Product or Component Type USB cable

### **Physical**

•	
Color	Black
Height	0.6 in (1.4 cm)
Width	4.9 in (12.5 cm)
Depth	4.9 in (12.5 cm)
Net Weight	0.29 lb(US) (0.13 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

#### **Conformance**

Product Certifications	C-tick CE TAA compliance VCCI Class A	
Standards	FCC Part 15 class A ICES-003 UI 60950-1	

#### **Environmental**

Ambient Air Temperature for Operation	32122 °F (050 °C)
Operating altitude	010000 ft
Relative Humidity	595 %
Ambient Air Temperature for Storage	14140 °F (-1060 °C)
Storage altitude	050000 ft (0.000000000015240.0000000000 m)
Storage Relative Humidity	595 %

## Ordering and shipping details

GTIN 731304335139

### **Packing Units**

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.7 in (4.2 cm)
Package 1 Width	5.08 in (12.9 cm)
Package 1 Length	4.9 in (12.5 cm)
Package 1 Weight	0.37 lb(US) (0.17 kg)
SCC14	10731304335136

# **Contractual warranty**

Warranty 2 years repair or replace

## Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

## Well-being performance

