



iSeries 3021-18 Case w/Think Tank Designed Liner

SKU: 3i-3021-18LT



Description

The 3i-3021-18LT is watertight and dustproof, and features a deluxe Nylex-wrapped closed cell fitted foam liner and Vexel-covered foam pads with heavy duty hook-and-loop tabs to create the perfect fit for all kinds of gear. Built-in wheels and a pull handle provide convenient transportability.

SKB iSeries Injection Molded Mil-Standard Waterproof Cases are molded of ultra high-strength polypropylene copolymer resin, featuring a gasket-sealed, water and dust tight, submersible design (MIL-STD 810H) that is resistant to corrosion and impact damage. Standard features include a molded-in hinge, padlock loops, Trigger Latch® System, snap-down rubber over-molded cushion grip handle, automatic ambient pressure equalization valve (MIL-STD 810H), and resistance to UV, solvents, corrosion, fungus and impact damage (MIL-STD 810H).

Features

- Think Tank-designed Nylex-wrapped fitted foam liner and (12) repositionable Nylex-covered foam pads with heavy duty hook-and-loop tabs
- Built-in wheels and pull handle
- Reinforced locking loops for customer supplied locks
- Snap-down rubber over-molded cushion grip handle
- Waterproof and dust tight design (MIL-STD 810H)
- Molded-in hinge for added protection
- Trigger Latch® System
- Ambient pressure equalization valve (MIL-STD 810H)

- Resistant to UV, solvents, corrosion, fungus, and impact damage (MIL-STD 810H)

Specifications

Exterior	Hard	
Built In Wheels or Casters	Yes	
Interior Length	30 in	76.20 cm
Interior Width	21 in	53.34 cm
Interior Lid Depth	2 in	5.08 cm
Interior Base Depth	16 in	40.64 cm
Product Weight	34.81 lb	15.79 kg
Exterior Length	32.94 in	83.67 cm
Exterior Width	23.53 in	59.77 cm
Exterior Height	18.87 in	47.93 cm
Carton Length	33.5 in	85.09 cm
Carton Width	24 in	60.96 cm
Carton Height	19.5 in	49.53 cm
Shipping Weight	38.93 lb	17.66 kg
Max Temp	0 °F	-17.8 °C
Min Temp	0 °F	-17.8 °C

AVAILABLE CONFIGURATIONS

3i-3021-18LT	Black / Padded Liner
--------------	----------------------