SPECIFICATION SHEET



VS240 SVGA 3LCD Projector

Basic presentations and graphics SVGA resolution

Business

The affordable portable projector with essential business features.

Far more accurate color with Epson® — 3LCD, 3-chip technology for 3x Higher Color Brightness¹ and up to 3x Wider Color Gamut² than competitive DLP projectors

EPSON

Look for two numbers:

3000 lumens³ Color Brightness for more accurate, vivid color 3000 lumens³ White Brightness for well-lit rooms

SVGA resolution (800 x 600) - for projecting basic presentations and graphics

Fast, easy setup, only from Epson — get up and running in no time with easy image adjustments and convenient control

Compatible with the latest laptops and media players — supports HDMI[®], the standard in connectivity, for digital video and audio with just one cable









VS240 SVGA 3LCD Projector

Specifications

Projection System 3LCD, 3-chip technology Projection Method Front/rear/ceiling mount Driving Method Poly-silicon TFT Active Matrix Pixel Number 480,000 dots (800 x 600) x 3 Color Brightness³ Color Light Output: 3000 lumens White Brightness³ White Light Output: 3000 lumens Aspect Ratio 4:3

Native Resolution 800 x 600 (SVGA)

Resize Support 1024 x 768 (XGA), 1152 x 864 (SXGA), 1280 x 800 (WXGA), 1280 x 960 (SXGA2), 1280 x 1024 (SXGA3), 1440 x 900 (WXGA+), 1400 x 1050 (SXGA+) Lamp Type 200 W UHE

Lamp Life⁵ Up to 5000 hours (Normal Mode) and up to 10,000 hours (ECO Mode)

Throw Ratio Range 1.45 (Zoom:Wide), 1.96 (Zoom:Tele) Size (projected distance) 30" - 350" (0.88 - 10.44 m) Keystone Correction Auto Vertical: ± 30 degrees Keystone Correction Manual Horizontal: ± 30 degrees

(Easy-Slide Horizontal Image Correction) USB Plug 'n Play Projects audio and video, PC and Mac® compatible

Contrast Ratio Up to 15,000:1

Color Reproduction Up to 1.07 billion colors

Projection Lens

Type Digital zoom (Manual)/Focus (Manual) F-number 1.44 Focal Length 16.7 mm

Zoom Ratio Digital zoom 1.0 - 1.35

Other

Display Performance NTSC: 480 lines PAL: 576 lines (Depends on observation of the multi-burst pattern) Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/ SECAM

Speaker 2 W (mono)

Operating Temperature 41 ° to 95 °F (5 ° to 35 °C) Power Supply Voltage 100 - 240 V ±10%, 50/60 Hz **Power Consumption**

291 W (Normal Mode) 214 W (ECO Mode)

Fan Noise

37 dB (Normal Mode) 29 dB (ECO Mode)

Security Kensington®-style lock provision, password protect function

Interfaces

HDMI x 1 Computer/component video: D-sub 15 pin x 1 S-video: Mini DIN x 1 Composite video: RCA (Yellow) x 1 Audio in: RCA x 1 (White/Red) USB connector Type A x 1: PC-free USB and other USB connector Type B x 1: USB Plug 'n Play



Dimensions (W x D x H)

Including Feet: 11.7" x 9.2" x 3.2" Excluding Feet: 11.7" x 9.2" x 3.0" Weight: 5.29 lb

Remote Control

Features Source search selection, power, volume, e-zoom, A/V Mute, freeze, menu, page up and down, help, auto, mouse functions

Operating Angle Right/left: ± 30 degrees Upper/lower: ± 15 degrees Operating Distance 19.7 ft (6 m)

Eco Features

RoHS compliant Recyclable product6 Epson America, Inc. is a SmartWaySM Transport Partner⁷



Epson ConnectionSM

Pre-sales support U.S. and Canada 800-463-7766 Internet website www.epson.com

Service Programs One-year projector limited warranty, Epson Road Service program, PrivateLine® dedicated toll-free support and 90-day limited lamp warranty

What's in the Box

VS240 Projector, Power Cable, Computer Cable (VGA), Projector Remote Control, Batteries, User Manual CD, Quick Setup Sheet

Ordering Information

VS240 Projector	V11H719220
Genuine Epson Lamp (ELPLP88)	V13H010L88
Replacement Air Filter (ELPAF32)	V13H134A32
Soft Carrying Case (ELPKS63)	V12H001K63
Universal Projector Ceiling Mount	ELPMBPJF
Duet [™] Screen	ELPSC80F
ES3000 Screen (ELPSC26H)	V12H002S3Y
ES1000 Screen	V12H002S4Y
Kensington Security Lock	ELPSL01

1 Color brightness (color light output) measured in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. Leading Epson 3LCD business and education projectors compared to leading 1-chip DLP projectors, based on NPD data for June 2013 through May 2014 and PMA Research data for Q1 through Q3 2013. | 2 Gamut volume of leading Epson business and education projectors compared to leading 1-chip DLP projectors, based on NPD data for June 2013 through May 2014. Volume is measured in 3D in the CIE L*a*b* coordinate space. | 3 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 4 Based on TFCinfo: U.S. Projector Brand Customer Perception and Preference Study, Multimedia Projectors 2015. | 5 Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. | 6 For convenient and reasonable recycling options, visit www.epson.com/recycle | 7 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

Better Products for a Better Future eco.epson.com

3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada Limited



185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PrivateLine is a registered trademark, Duet is a trademark and Epson Connection is a service mark of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. SmartWay is a service mark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2015 Epson America, Inc. Com-SS-Oct-13 CPD-43117 6/15

Specification Sheet | Page 2 of 2

Epson America, Inc.