

GCS72DPKIT

2-Port USB VGA Cable KVM with DisplayPort Adapters



2-Port Cable VGA / DisplayPort KVM Switch

- Switch between two computers with the push of a button
- Offers the flexibility to mix and match computer connections: VGA and DisplayPort
- Includes 2 x DisplayPort to VGA adapters
- No external power needed
- Cost effective, Plug-N-Play solution


Flexibility to Choose VGA and/or DisplayPort

You finally have the flexibility to mix and match your video options with this kit, streamlining and developing efficient workstations by eliminating multiple desktop setups. With the included adapters, IOGEAR's VGA and DisplayPort KVM Solution simplifies the method of sharing two computers using one VGA monitor, keyboard and mouse. This bundle is perfect for a home office or small / medium size business, as it offers the flexibility of choosing between VGA and/or DisplayPort connections. Take advantage of your existing DisplayPort computers, and use the included adapters to view your content on a VGA projector, monitor, or display.


- Switch between two computers with the push of a button
- Offers the flexibility to mix and match computer connections: VGA and DisplayPort
- Includes 2 x DisplayPort to VGA adapters
- No external power needed
- Cost effective, Plug-N-Play solution
- One USB keyboard, USB mouse, and VGA monitor control two computers
- Max resolution: 2048 x 1536, DDC2B
- 2.1 Stereo audio and microphone support
- 3' long molded-in cables to simplify setup
- Compatible with PC, MAC and SUN operating platforms
- Supports Windows XP or higher, Mac OS 9.0 or higher, Sun Solaris 9 or higher
- Full Mac keyboard support
- Supports programmable mice
- 2 x DisplayPort to VGA Adapters convert your DisplayPort to VGA:
 - Works with computer systems using DisplayPort
 - Compliant with Displayport Specification 1.1a for both 1.62 Gbps and 2.7 Gbps
 - Support full DisplayPort link tracking
 - Supported resolutions:
 - Full HD 1080p
 - 1920x1200
 - VGA, SVGA, XGA, SXGA and UXGA at 162 MHz pixel rate
 - Support interrupt request output for expansion function
 - Support Deep Sleep Mode (suspend mode)



Solution 1



Solution 2



Requirements

Package Contents

- | | |
|---|---|
| <ul style="list-style-type: none"> • Console: • 1 VGA display • 1 set of USB keyboard and mouse • • Computers: • VGA or DisplayPort port • USB ports • 3.5mm audio port (optional) • • Operating Systems: • Windows Vista®, Windows® 7, Windows® 8.1, Windows® 10 • Mac OS 9 to 10.x • Oracle® Solaris • Linux®, Unix and other USB supported systems* | <ul style="list-style-type: none"> • 1 x 2-Port USB Cable KVM • 2 x DisplayPort to VGA Adapters • 1 x Quick Start Guide • 1 x Warranty Card |
|---|---|

*Additional drivers and support may be needed

Specifications

Function	GCS72DPKIT
Computer Connections	
Direct	2
Console Connectors	
Monitor	VGA
Keyboard	USB
Mouse	USB
CPU Connectors	
Monitor	2 x VGA; 2 x DisplayPort (with adapters)
Keyboard & Mouse	2 x USB
LEDs	
On Line	Green
Video Resolution	2048x1536 (VGA), 1920x1200 (with adapters)
Port Selection	Remote Pushbutton
Cable Length	2 x 3ft each
Cable Type	Bonded USB KVM
Housing	
Case	Plastic

Dimensions	GCS72DPKIT
POP Information	
10" Peg Hook	4
6" Peg Hook	2
Unit Dimensions	
Height	6" (15.24cm)
Depth	7" (17.78cm)
Length	2" (5.08cm)
Unit Package Dimensions	
Width	6.25" (15.87cm)
Height	8.87" (22.54cm)
Depth	2.25" (5.72cm)
Master Carton	
Width	8" (20.32cm)
Height	7" (17.78cm)
Depth	15.25" (38.74cm)
Master Carton Qty.	6
Weight	
Master Carton Wt.	7.52lb (3.42kg)
Unit Pack Wt.	1.14lb (0.52kg)
Unit Wt. w/accessories	0.92lb (0.42kg)
Unit Wt.	0.82lb (0.37kg)