

GCS62HDPKIT

2-Port HD Cable KVM with DisplayPort Adapters




HD and DisplayPort Mix & Match Solution

IOGEAR's HDMI and DisplayPort KVM Solution enables effortless control over two computers using a single USB keyboard, a USB mouse and a monitor with HDMI connection or HDTV. This bundle is perfect for a home office or small / medium size business, as it offers the flexibility of choosing between HDMI and/or DisplayPort connections. Take advantage of your existing computers, and use the included DisplayPort adapters to display your content on a large HDMI display or HDMI projector.

- Connect and control two HD or DisplayPort USB 2.0 interface computers with a single keyboard and mouse
- Full 1080p and up to 1920 x 1200 @ 60Hz
- Port switching via remote switch button, mouse or hotkeys
- Hotkeys allows independent KVM and audio switching between computers
- Includes 2.1 stereo sound and microphone support
- USB 2.0 Peripheral Sharing via mouse port. Connect a powered USB Hub to expand your USB connectivity*
- USB mouse and keyboard emulation for error-free boot-up and instantaneous recognition when switching computers
- Power-On Detection – If one of the computers is powered off, it will automatically switch to the next powered-on computer
- Re-programmable hotkey activation for keyboards without a scroll lock key
- Keyboard emulation can be disabled to support gaming keyboard's special keys
- Mouse emulation can be disabled to support mice with special keys
- Digital Audio support
- HDCP Compliant
- Multi OS platform support
- Works with game consoles
- Mac and Sun keyboard support
- Firmware upgradeable
- Plug-n-play; no software required
- DisplayPort to HD Adapters:
 - Converts your DisplayPort to HDMI so you can connect to your HDMI projector, TV or monitor
 - Works with computer systems using DisplayPort
 - Compliant with Displayport Specification 1.1a for both 1.62 Gbps and 2.7 Gbps
 - Support full DisplayPort link tracking
 - Supported resolutions:
 - Full HD 1080p
 - 1920x1200
 - Compliant with DVI 1.0 up to 1.65Gbps
 - Support interrupt request output for expansion function
 - Support Deep Sleep Mode (suspend mode)

*Mouse emulation must be disabled for this feature to function correctly





Requirements

Package Contents

- | | |
|--|--|
| <ul style="list-style-type: none"> • Console: • 1 HDMI display • 1 set of USB keyboard and mouse • • Computers: • 1 HDMI or DisplayPort • 2 USB ports • • Operating Systems: • Windows Vista®, Windows® 7, Windows® 8, Windows® 8.1, Windows® 10 • Mac OS® X 9 to 10.x • Oracle® Solaris • Linux®, Unix and other USB supported systems* | <ul style="list-style-type: none"> • 1 x GCS62HU • 2 x DisplayPort to HDMI Adapters • 1 x Installation Guide • 1 x Warranty Card |
|--|--|

**Additional drivers and support may be needed*

***IOGEAR's Display Emulation Technology provides the EDID support for Windows® 7*

Specifications

Function	GCS62HDPKIT	Dimensions	GCS62HDPKIT
Computer Connections		POP Information	
Direct	2	10" Peg Hook	5
Console Connectors		6" Peg Hook	3
Monitor	1 x HDMI Female	Unit Dimensions	
Audio	1 x 3.5mm Mini Stereo Jack Female (Green)	Height	2.5" (6.35cm)
Microphone	1 x 3.5mm Mini Stereo Jack Female (Pink)	Depth	1" (2.54cm)
Keyboard	1 x USB Type A Female	Length	3.125" (7.93cm)
Mouse	1 x USB Type A Female	Unit Package Dimensions	
CPU Connectors		Width	6.5" (16.51cm)
Monitor	2 x HDMI Male; 2 x DisplayPort Male (with adapter)	Height	7.5" (19.05cm)
Audio	2 x 3.5mm Mini Stereo Jack Male (Green)	Depth	2.75" (6.99cm)
Microphone	2 x 3.5mm Mini Stereo Jack Male (Pink)	Master Carton	
Keyboard	2 x USB Type A Male (Purple)	Width	16" (40.64cm)
Mouse	2 x USB Type A Male (Black)	Height	7" (17.78cm)
LEDs		Depth	9" (22.86cm)
On Line	2 x Green	Master Carton Qty.	6
Emulation		Weight	
Keyboard	USB	Master Carton Wt.	8.6lb (3.91kg)
Mouse	USB	Unit Pack Wt.	1.3lb (0.59kg)
Scan Interval		Unit Wt.	.94lb (0.43kg)
3, 5, 10, 20 seconds (Default 5 seconds)			
Environment			
Storage Temperature	-20~60°C		
Operation Temperature	0~50°C		
Humidity	0~80%; Non-condensing		
Housing			
Case	Plastic		
Video Resolution			
1080p; 1920x1200			
Port Selection			
Remote Switch, Hotkey, and Mouse			