



20W MagSafe Wireless Charging Stand for iPhone 16 and AirPods, Apple MFI Certified, 3 ft. Cable, White

MODEL NUMBER: U280MS-2N1-WH











Not for sale in the USA.

Wirelessly charges a MagSafe-compatible iPhone and earbuds simultaneously with a combined output of 20W.

Features

2-in-1 Charging Stand Handles 2 Devices at the Same Time

This 20W dual-charging output stand is designed for smartphones (including iPhones), earbuds (including AirPods) and other devices compatible with magnetic wireless charging. The top charging pad for smartphones extends toward you, so you can scroll, text or watch videos in landscape or portrait mode while the phone is charging. The bottom pad is for AirPods and other wireless charging-compatible earbuds, which can be charged in their case. Both charging pads can be used simultaneously.

Supports Apple MagSafe Technology for a Secure Charge Every Time

Built-in MagSafe technology helps ensure your iPhone and the U280MS-2N1-WH work together for a complete charge whenever you need it. Magnets inside both your phone and the charging pad prevent the iPhone from falling off the charger and being disconnected while charging. The U280MS-2N1-WH delivers up to 15W of power to smartphones and 5W to wireless headphones or earbuds that support Qi wireless charging.

Compact Charging Stand Fits Comfortably on Any Counter, Table or Workspace

The portable U280MS-2N1-WH takes up hardly any space, making it ideal for your bedside table or desktop. The included three-foot (0.9-meter) USB-C charging cable connects the charging stand to a user-provided USB wall charger or power adapter, such as the 9V 2.2A U280-W01-20C1-G (sold separately). Over-current, over-voltage and short circuit protections defend your devices against damage.

Specifications

OVERVIEW		
UPC Code	037332279309	
Product Type	Wireless Charging Stand	
Charging Form Factor	Pad/Stand	

Highlights

- MagSafe wireless charging pad charges iPhone 12 and above with up to 15W of power
- Wireless charging pad charges compatible earbuds with up to 5W of power
- Both charging pads can be used simultaneously for a combined charging output of 20W
- Features over-current, overvoltage and short circuit protections to ensure safe charging
- Developed and tested to Apple's MFi standards

System Requirements

- Works with all MagSafecompatible smartphones, including iPhone 12 and above
- Charging pad only works with devices compatible with wireless charging

Package Includes

- U280MS-2N1-WH 20W Wireless Charging Stand
- USB-C charging cable (M/M), 3 ft. (0.9 m)
- Quick Start Guide





	Wireless	
Country/Region (,	
, ,	Global	
Host Connector	USB C (FEMALE)	
INPUT		
	5V DC; 9V DC	
	USB Type-C	
,	30+24	
	USB-C (FEMALE)	
	USB-A to USB-C Cable Included	
	5V/3A, 9V/3A 	
Bus Powered 1	No .	
OUTPUT		
Output Capacity (Watts)	20	
Overload Protection	Yes	
POWER		
	USB	
Power Consumption (Watts)	20.00	
CONNECTIONS		
Side A - Connector 1	USB C (FEMALE)	
Side B - Connector 1	WIRELESS CHARGING COIL	
Side B - Connector 2	Magnetic Charger	
Connector Style	Straight	
CHARGING		
Number of Charging Ports 2	2	
	4	
	20	
	Magnetic Charger; USB; Wireless	
	(2) WIRELESS CHARGING COIL	
Charging Ports Details	MagSafe wireless charging pad provides up to 15W to MagSafe compatible smartphones, such as Apple iPhone 12 or aboveWireless charging pad provides up to 5W to wireless charging compatible earbuds	
Magnetic Charging	Yes	





Overcharge Protection	Yes	
Compatible Devices	Chromebook; Laptop; Smartphone; Tablet	
PHYSICAL	MIL: i.e.	
Color	White	
Material of Construction	ABS	
Cable Jacket Color	White	
Connector Color	White	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	3.5mm	
Wire Gauge (AWG)	30+24	
Charging Station Form Factor	Pad/Stand	
Cable Length (ft.)	3	
Cable Length (m)	0.91	
Cable Length (in.)	36	
Cable Length (cm)	90	
Unit Dimensions (hwd / in.)	5.490 x 3.560 x 4.950	
Unit Dimensions (hwd / cm)	13.9 x 9.04 x 12.58	
Unit Dimensions (hwd / mm)	139.4 x 90.4 x 125.8	
Unit Packaging Type	Вох	
Unit Weight (lbs.)	1	
Unit Weight (kg)	0.45	
ENVIRONMENTAL		
Operating Temperature Range	32° to 104°F (0° to 40°C)	
Storage Temperature Range	23° to 113°F (-5° to 45°C)	
Operating Humidity Range	20% to 90% RH	
Storage Humidity Range	45% to 85% RH	
FEATURES & SPECIFICATIONS		
GaN Technology	No	
Overcurrent Protection	Yes	
Overvoltage Protection	Yes	
Over Current Protection	Yes	
Driver Required	No	
Qi Compliant	Yes	





STANDARDS & COMPLIANCE			
Product Certifications	ICES (Canada); MFi		
Product Compliance	CE (Europe); FCC Part 15 Class B (USA); REACH; RoHS3; UKCA		
Product Compliance	CE (Europe), FCC Part 15 Class B (USA), REACH, ROHSS, UNCA		
WARRANTY & SUPPORT			
Product Warranty Period (Worldwide)	1-year limited warranty		

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.