

HP Fortis G2m 14 inch Chromebook Enterprise



Front

- | | | | |
|---|---------------------|---|------------|
| 1 | Internal Microphone | 4 | Webcam LED |
| 2 | Webcam | 5 | Touchpad |
| 3 | Camera Shutter | | |





Sides

- | | | | |
|---|---|---|---|
| 1 | HDMI 1.4b | 4 | Nano SIM card slot (optional) |
| 2 | USB Type-A 5Gbps signaling rate | 5 | Headphone/mic combo jack |
| 3 | USB Type-C® 5Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4) | 6 | USB Type-C® 5Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4) |
| | | 7 | Nano Security Slot |

PRODUCT NAME

HP Fortis G2m 14 inch Chromebook Enterprise



OPERATING SYSTEM

Preinstalled

ChromeOS

ChromeOS with ChromeOS Enterprise Upgrade



PROCESSORS

Processor ^{1,2}	Cores	Threads	Base Frequency	L3 Cache	Integrated Graphic
Mediatek Kompanio processor 540	8 cores	8	2.00 GHz	1MB	ARM® Mali™ G57 MC2

1. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. MediaTek’s numbering, branding and/or naming is not a measurement of higher performance.

2. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

GRAPHICS

Integrated

ARM® Mali™ G57 MC2

Supported Protocols

Support HDMI 1.4b

Display supported (including internal display; dock may be required) up to 2



DISPLAY

Availability may vary by country.
Actual brightness will be lower with touchscreen or HP Sure View.

Non-Touch

35.6 cm (14") diagonal, FHD (1920 x 1080), LCD, UWVA, Anti-Glare, WLED, 300 nits, Low power, NTSC 45%
35.6 cm (14") diagonal, HD (1366x768), LCD, SVA, Anti-Glare, WLED, 250 nits, NTSC 45%

Touch

35.6 cm (14") diagonal, FHD (1920 x 1080), LCD, Touch on Panel, UWVA, Anti-Glare, WLED, 250 nits, NTSC 45%
35.6 cm (14") diagonal, HD (1366x768), LCD, Touch on Panel, Anti-Glare, WLED, 250 nits, NTSC 45%

Display Size (Diagonal)

35.6 cm (14")

Aspect Ratio

16:9

Screen to Body Ratio

Up to 81.54%

Max Hinge Open Angle

180°



DOCKING (SOLD SEPARATELY)

Docking station model name

HP USB-C™ 100W G6 Dock

Total number of supported displays (incl.the notebook)

3

Max. resolutions supported

(1) 4K @120hz*

(2) 4K @120hz*

(3) 4K @60hz*

Dock Connectors

1 x HDMI 2.1, 2 x DisplayPort 1.4

Technical limitations

*Requires DisplayPort 1.4 support with Display Stream Compression (DSC).

Bluetooth required for HP Quick Connect. HP Quick Connect available on select HP notebooks.

Maximum resolution and display support is dependent on the maximum capability of the notebook.

Highest resolution with dual displays is two 8K@ 30Hz host in High Resolution mode.

Three maximum displays supported are two 5K@ 30 Hz on DP ports plus one 4K UHD@ 30 Hz on HDMI in Multi-function mode.

The highest resolution for a non-Thunderbolt host in multi-function mode is a single 5K dual cable (using both DP ports) + (1) 4K on HDMI port.



STORAGE AND DRIVES

Storage

64 GB eMMC 5.0 ³

128 GB UFS ³

3. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 32 GB is reserved for system recovery software. Storage performance may vary by configuration and usage.



MEMORY

Memory Slot	Onboard memory, no memory slots
Memory Type	LPDDR5X
Maximum supported memory	16 GB LPDDR5X-8533 MT/s
Available memory configuration	16 GB LPDDR5X-8533 MT/s, single-channel 8 GB LPDDR5X-8533 MT/s, single-channel 4 GB LPDDR5X-8533 MT/s, single-channel
Notes	System runs at 6400 MT/s Memory is non-accessible / non-upgradeable.



NETWORKING / COMMUNICATIONS

Items below may be optional.

WLAN

Mediatek MT7925 Wi-Fi 7 Bluetooth® 6.0 WW WLAN ⁴

Mediatek RZ616 Wi-Fi 6E Bluetooth® 5.3 AIM-T WLAN ^{5, 6}

WWAN

Qualcomm® SDX35 5G RedCap WWAN ⁷

Chromecast

Chromecast Support ⁸

4. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 7 (802.11be) functionality requires compatible Chrome OS, select processor, and a Wi-Fi 7 router, sold separately. Wi-Fi 7 is backwards compatible with prior 802.11 specs. Available in countries where Wi-Fi 7 is supported.

5. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. Available in countries where Wi-Fi 6E is supported.

6. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.

7. 5G module is optional. WWAN-ready configuration must be selected at purchase to add WWAN module at a later date (WWAN After Market Option Kit). Module designed for 5G RedCap (Reduced Capability), 5G NR SA (Standalone) and 4G LTE Public and Private networks with both 20MHz of 5G NR and LTE channel bandwidth, using 256QAM 2x2 as defined by 3GPP. Module includes embedded eSIM. Module requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Data connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. Backwards compatible to 4G LTE technologies. 5G module planned to be available in select platforms and select countries, where carrier and frequency bands supported.

8. Chromecast must be purchased separately.



AUDIO/MULTIMEDIA

Audio

- 2 Integrated stereo speakers
- 2 Integrated dual array microphone

Speaker Power

2W / 4 ohm per speaker

Camera

FHD HDR camera

Sensors

Hall Effect Sensor



KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

Full-size island-style Chrome keyboard, top mount design, Pick Resistant, spill resistant with HP Full-Skirted Anchored Key⁹

Pointing Device

Clickpad

Multi-touch gesture support

Taps enabled as default

Function Keys

ESC - Escape

F1 - Back

F2 - Refresh

F3 - Full screen

F4 - Overview

F5 - Screenshot

F6 - Display Brightness Down

F7 - Display Brightness Up

F8 - Dictation

F9 - Play or pause media

F10 - Turn on/off microphone

F11 - Audio Mute

F12 - Volume Down

F13- Volume Up

9. Keyboard is replaceable by an authorized HP service provider or trained IT personnel.

SOFTWARE AND SECURITY

Application Software

HP Support Assistant

Manageability Features

ChromeOS Education Upgrade ^{10,11,12}

ChromeOS Enterprise Upgrade ¹²

Security Management

NuvoTitan Security Chip

Security lock slot (Lock sold separately) ¹⁰

Zero-touch enrollment ¹³

Security - TPM

Model

NuvoTitan

FIPS 201 Compliant

No

IPv6 Support

Yes

FirstNet Certified

No

Does the BIOS implement the ISO/IEC 19678:2015 (formerly NIST 800-147) guidelines?

Yes

UEFI version

No



Class

No

10. Sold separately

11. ChromeOS Education Upgrade requires one-time setup, subscription, Google Admin Console, and your organization's domain.

Please see <https://support.google.com/a/answer/60216>.

12. The ChromeOS Upgrade must be bundled at the time of configuration during purchase and cannot be added after manufacturing. Please verify that the correct Upgrade is selected prior to order placement, as Upgrades cannot be exchanged or substituted after purchase. The ChromeOS Education Upgrade may not be available for sale through Channel Partners in certain countries; availability is subject to local sales terms and Google licensing requirements.

13. Zero-touch enrollment is sold separately and requires separately purchased HP Get More Service. HP Services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product



POWER

Power supply availability may vary by country.

Battery is internal and replaceable by customer.

Higher wattage adapter is recommended for best performance and fastest charging.

Using lower-capacity third-party USB Type-C® power cables may reduce power delivery.

Power Supply

HP 45W Standard USB Type-C® GaN AC power adapter

HP 45W Wall Mount USB Type-C® GaN Halogen Free AC power adapter

Battery

HP Long Life 3 cell, 41Wh Polymer

Battery Recharge Time

Supports battery HP Fast Charge: approximately 90% in 90 minutes ¹⁴

Power Cord

3-wired plug- 1.0m for standard type adapter

USB-C Power Cable- 2.0m for wall mount adapter

Battery life

Up to 14 hours 30 minutes with 41Whr battery (Mediatek Kompanio 540, UMA graphic, brightness set to 150nits on a 14-inch FHD 300nits LP LCD display, 4GB LPDDR5X memory, 64 GB eMMC) ¹⁵

14. Recharges up to 90% within 90 minutes when the system is off or in standby mode when used with the power adapter provided with the notebook. After charging has reached 90% capacity, charging speed will return to normal. Charging time may vary +/-10% due to System tolerance.

15. Testing conducted by HP using Google Chrome OS Power Qualification Test v2. Battery life will vary and the maximum capacity of the battery will naturally decrease with time and usage and battery optimization activation. See <http://www.chromium.org/chromium-os/testing/power-testing> for test details. Battery configuration and charge capacity is optimized to improve battery health over time based upon charging patterns and temperature.



WEIGHT & DIMENSIONS

Weight will vary by configuration. Does not include power adapter.

Front height measurement is near the front edge where the mechanical chassis taper begins. Back height measurement is near the rear edge where the mechanical chassis taper ends.

Product Weight

Starting at 1.479 kg (3.26 lb) with 41.00 Wh battery

Product Dimensions (w x d x h)¹⁶

Width: 328.97 mm (12.95 in)

Depth: 225.00 mm (8.86 in)

Height Front: 14.12 mm (0.56 in)

Height Rear: 19.31 mm (0.76 in)

Maximum Height: 21.5 mm (0.85 in)

Packaging and Pallet Dimensions

Product packaging size varies based on options chosen. Please contact your HP representative for your packaging size details. For detailed packaging information, access the [HP Commercial Notebooks Packaging Guide](#).

16. Typical dimension. Actual dimension may vary +/- 0.5mm. Height may vary based on configuration. Maximum Height does not include Rubber feet.



PORTS/SLOTS

The actual throughput of ports may vary and depending on many factors, such as the processing speed of the host device and other factors related to system configuration and the operating environment, will be slower than theoretical speed.

Left side

- 1 x USB Type-C® 5Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)
- 1 x USB Type-A 5Gbps signaling rate
- 1 x HDMI 1.4b

Right side

- 1 x USB Type-C® 5Gbps signaling rate (USB Power Delivery, DisplayPort™ 1.4)
 - 1 x headphone/mic combo jack
 - 1 x Nano SIM card slot (optional)
 - 1 x Nano Security Slot
-



SERVICE AND SUPPORT

Warranty

1-year warranty and 90 day software limited warranty options depending on country. HP Worldwide Limited Warranty for the battery is aligned with the warranty period of the HP Hardware Product. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.



SYSTEM UNIT

Stand - Alone Power Requirements

(AC Power)

Nominal Operating Voltage	20.0 V
Max Operating Power	UMA < 15 W

Temperature

Operating	5° to 35° C (41° to 95° F) No sustained direct exposure to sunlight, System performance may be reduced above 32°C (89.6°F)
Non - operating	-20° to 60° C (-4° to 140° F) No sustained direct exposure to sunlight, System performance may be reduced above 32°C (89.6°F)

Relative Humidity

Operating	10% to 90% (non-condensing)
Non - operating	5% to 95%, 38.7° C (101.6° F) maximum wet bulb temperature

Shock

Operating	40 G, 2 ms, half-sine
Non - operating	240 G, 2 ms, half-sine

Random Vibration

Operating	1.043 grms
Non - operating	3.500 grms

Altitude(unpressurized)

Operating	3,048 m (10,000 ft)
Non - operating	12,192 m (40,000 ft)

Industry Standard Certifications

Regulatory Model Number	TPN-C184
UL 62368-1	Yes
ENERGY STAR® 17	Yes
FCC/ICES/CISPR/VCCI	Yes
CE MARKING	Yes
GS Mark	No
China CCC/SRRC/CEL	No
Taiwan BSMI/NCC	Yes
Korea KCC/KC/KES	Yes



Ukraine NSoC/TEC	Yes
EAEU Compliance	Yes
Saudi Arabian Compliance	Yes
TCO	Yes
EPEAT Gold ¹⁸	Yes
Low Blue Light	No
WW RoHS	Yes
CECP	No
Medical EMC: IEC 60601-1-2:2014 EN60601-1-2: 2015	No
SEPA	No
MIL - STD Testing ¹⁹	MIL-STD 810H

17. Configurations that are ENERGY STAR® qualified are identified as ENERGY STAR on HP websites and on <http://www.energystar.gov>

18. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit <http://www.epeat.net> for more information.

19. MIL STD testing is not intended to demonstrate fitness for U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

DISPLAYS

Actual brightness will be lower with touchscreen or HP Sure View.
Availability may vary by country

35.6 cm (14") diagonal, FHD (1920 x 1080), LCD, UWVA, Anti-Glare, WLED, 300 nits, Low power, NTSC 45%	Active Area	309.31 x 173.99 mm (typ)
	Dimensions (W x H)	315.37 x 185.17 mm (max)
	Weight	290 g (max)
	Diagonal Size	14 inch
	Surface Treatment	Anti-Glare
	Touch Enabled	No
	Contrast Ratio	1000:1 (typical)
	Refresh Rate	60Hz/ 40Hz
	Brightness	300 nits (typ)
	Pixel Resolution	RGB
	Pixel Resolution - Format	1920x1080 (FHD)
	Aspect Ratio	16:9
	Backlight	WLED
	Color Gamut Coverage	NTSC 45%
	Color Depth	8 bits
	Viewing Angle	UWVA 89/89/89/89
	Low Blue Light	No
	Power Consumption	EBL @ 150 nits: 1.5 W(max) EBL @ 200 nits: 1.83 W(max) EBL @ 250 nits: 2.19 W(max)

35.6 cm (14") diagonal, FHD (1920 x 1080), LCD, Touch on Panel, UWVA, Anti-Glare, WLED, 250 nits, NTSC 45%	Active Area	309.312 x 173.988 mm (typ.)
	Dimensions (W x H)	316.17 x 186.4 mm (max)
	Weight	295 g (max)
	Diagonal Size	14 inch
	Surface Treatment	Anti-Glare
	Touch Enabled	Yes
	Contrast Ratio	600:1 (typ)
	Refresh Rate	60Hz/ 40Hz

Brightness	250 nits (typ)
Pixel Resolution	RGB
Pixel Resolution - Format	1920x1080 (FHD)
Aspect Ratio	16:9
Backlight	WLED
Color Gamut Coverage	NTSC 45%
Color Depth	6 bits
Viewing Angle	UWVA 85/85/85/85
Low Blue Light	No
Power Consumption	EBL @ 150 nits: 2.24 W(max) EBL @ 200 nits: 2.72 W(max) EBL @ 250 nits: 3.2 W(max)

35.6 cm (14") diagonal, HD
(1366x768), LCD, SVA, Anti-
Glare, WLED, 250 nits, NTSC
45%

Active Area	309.4 x 173.95 mm (typ.)
Dimensions (W x H)	316.110 x 186.370 mm (max)
Weight	285 g (max)
Diagonal Size	14 inch
Surface Treatment	Anti-Glare
Touch Enabled	No
Contrast Ratio	300:1 (typical)
Refresh Rate	60Hz/ 40Hz
Brightness	250 nits (typ)
Pixel Resolution	RGB
Pixel Resolution - Format	1366x768 (HD)
Aspect Ratio	16:9
Backlight	WLED
Color Gamut Coverage	NTSC 45%
Color Depth	6 bits
Viewing Angle	SVA 45/45/15/35
Low Blue Light	No
Power Consumption	EBL @ 150 nits: 2.52 W(max) EBL @ 200 nits: 2.86 W(max) EBL @ 250 nits: 3.4 W(max)



35.6 cm (14") diagonal, HD (1366x768), LCD, Touch on Panel, Anti-Glare, WLED, 250 nits, NTSC 45%	Active Area	309.400 x 173.950 mm (typ)
	Dimensions (W x H)	316.200 x 186.53 mm (max)
	Weight	300g (max)
	Diagonal Size	14 inch
	Surface Treatment	Anti-Glare
	Touch Enabled	Yes
	Contrast Ratio	300:1 (Typ)
	Refresh Rate	60Hz/ 40Hz
	Brightness	250 nits (typ)
	Pixel Resolution	RGB
	Pixel Resolution - Format	1366x768 (HD)
	Aspect Ratio	16:9
	Backlight	LED
	Color Gamut Coverage	NTSC 45%
	Color Depth	6 bits
	Viewing Angle	SVA 45/45/15/ 35
	Low Blue Light	No
	Power Consumption	EBL @ 150 nits: 2.34 W(max) EBL @ 200 nits: 2.92 W(max) EBL @ 250 nits: 3.5 W(max)



STORAGE

64 GB eMMC 5.0 ¹	Form Factor	153 FBGA
	Capacity	64GB
	NAND Type	TLC
	Weight	11.5 x 13mm
	Interface	eMMC 5.x
	Sequential Read	Up to 300 MB/s
	Sequential Write	Up to 200 MB/s
	Logical Blocks	32GB (31,268,536,320 Bytes)/64GB (62,537,072,640 Bytes)
	Features	32° to 158°F (0° to 70°C) [ambient temp]
128 GB UFS ¹	Form Factor	UFS 3.1
	Capacity	128GB
	NAND Type	TLC
	Interface	SCSI
	Sequential Read	1000MB/s (ADL-N support UFS 2.1 only)
	Sequential Write	200MB/s
	Logical Blocks	128GB (127,984,992,256 Bytes)
	Features	HS400

1. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 32 GB is reserved for system recovery software. Storage performance may vary by configuration and usage.

NETWORKING / COMMUNICATION

Mediatek MT7925 Wi-Fi 7	Wireless LAN Standards	IEEE 802.11a
Bluetooth® 6.0 WW WLAN ¹		IEEE 802.11ac
		IEEE 802.11ax
		IEEE 802.11b
		IEEE 802.11be
		IEEE 802.11d
		IEEE 802.11e
		IEEE 802.11g
		IEEE 802.11h
		IEEE 802.11i
		IEEE 802.11j
		IEEE 802.11k
		IEEE 802.11mc
		IEEE 802.11n
		IEEE 802.11r
		IEEE 802.11v
		IEEE 802.11w
	Interoperability	Wi-Fi certified
	Frequency Band	802.11b/g/n/ax/be(Wifi7)
		2.402 - 2.482 GHz
		802.11a/n/ac/ax/be(Wifi7)
		4.9 - 4.95 GHz (Japan)
		5.15 - 5.25 GHz
		5.25 - 5.35 GHz
		5.47 - 5.725 GHz
		5.825 - 5.850 GHz
		5.925 - 7.125 GHz
		5.955 - 6.415 GHz
		6.435 - 6.515 GHz
		6.535 - 6.875 GHz
		6.895 - 7.115 GHz

	802.11b/g/n/ax(Wifi6/Wifi6E) 2.402 - 2.482 GHz
	802.11a/n/ac/ax(Wifi6/Wifi6E) 4.9 - 4.95 GHz (Japan) 5.15 - 5.25 GHz 5.25 - 5.35 GHz 5.47 - 5.725 GHz 5.825 - 5.850 GHz 5.925 - 7.125 GHz 5.955 - 6.415 GHz 6.435 - 6.515 GHz 6.535 - 6.875 GHz 6.895 - 7.115 GHz
Data Rates	802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11ac : MCS0 ~ MCS9, (20MHz, 40MHz, 80MHz, 160MHz) 802.11ax : MCS0 ~ MCS11, (20MHz, 40MHz, 80MHz, 160MHz) 802.11b: 1, 2, 5.5, 11 Mbps 802.11be : MCS0~13, (20MHz, 40MHz, ,80MHz, 160MHz, 320MHz) 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: MCS 0 ~ MCS 15, (20MHz, 40MHz)
Modulation	Direct Sequence Spread Spectrum 338, 335, 337, 339, 336, 332, 334, 331, 333
Security	802.1x authentication AES-CCMP: 128 bit in hardware IEEE 802.11i IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only WAPI WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification



	WPA3 certification
Network Architecture	Ad-hoc (Peer to Peer)
Models	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power	802.11b, 1Mbps : +17dBm minimum 802.11g, 6Mbps : +16dBm minimum 802.11a, 6Mbps : +17dBm minimum 802.11n, MCS7(HT20) : +14dBm minimum 802.11n, MCS7(HT40) : +13.5dBm minimum 802.11ac MCS9(VHT20) : 13.5dBm minimum 802.11ac MCS9(VHT40) : +13.5dBm minimum 802.11ac MCS9(VHT80) : +12.5dBm minimum 802.11ac MCS9(VHT160) : +10.5dBm minimum 802.11ax MCS11(HE20)(6GHz) : +11.5dBm minimum 802.11ax MCS11(HE40)(6GHz) : +7.5dBm minimum 802.11ax MCS11(HE80)(6GHz) : +7.5dBm minimum 802.11ax MCS11(HE160)(6GHz) : +7.5dBm minimum 802.11be MCS13(EHT20)(6GHz) : +11.5dBm 802.11be MCS13(EHT40)(6GHz) : +7.5dBm 802.11be MCS13(EHT80)(6GHz) : +7.5dBm 802.11be MCS13(EHT160)(6GHz) : +6.5dBm
Power Consumption	Transmit mode : 2.7 W Receive mode : 1.8 W Idle mode (PSP) : 180 mW (WLAN Associated) Idle mode: 50 mW (WLAN unassociated) Connected Standby/Modern Standby : 10 mW Radio disabled : 8 mW
Power Management	ACPI and PCI Express® compliant power management; 802.11 compliant power saving mode
Receiver Sensitivity ⁴	802.11b, 1Mbps : -93.5dBm maximum 802.11b, 11Mbps : -85dBm maximum 802.11a/g, 6Mbps : -90.5dBm maximum 802.11a/g, 54Mbps : -72.5dBm maximum



	802.11n, MCS0(HT20) : -90dBm maximum
	802.11n, MCS7(HT20) : -71.5dBm maximum
	802.11n, MCS0(HT40) : -88.5dBm maximum
	802.11n, MCS7(HT40) : -68.5dBm maximum
	802.11ac, MCS9(VHT20) : -88.5dBm maximum
	802.11ac, MCS9(VHT40) : -65.5dBm maximum
	802.11ac, MCS9(VHT80) : -60.5dBm maximum
	802.11ac, MCS9(VHT160) : -58.5dBm maximum
	802.11ax, MCS11(HE20)(6GHz) : -59.5dBm maximum
	802.11ax, MCS11(HE40)(6GHz) : -56.5dBm maximum
	802.11ax, MCS11(HE80)(6GHz) : -53.5dBm maximum
	802.11ax, MCS11(HE160)(6GHz) : -51.5dBm maximum
	802.11be, MCS13(EHT20)(6GHz) : -55.5dBm maximum
	802.11be, MCS13(EHT40)(6GHz) : -53.5dBm maximum
	802.11be, MCS13(EHT80)(6GHz) : -51.5dBm maximum
	802.11be, MCS13(EHT160)(6GHz) : -48.5dBm maximum
Antenna Type	High efficiency antenna with spatial diversity, mounted in the display enclosure
	Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI Express® M.2 MiniCard
Dimensions	2.30 x 22.00 x 30.00 mm (0.09 x 0.87 x 1.18 inch)
Weight	Type 2230: 2.8 g(0.099 oz)
Operating Voltage	3.3 v +/- 9 %
	Integrated Bluetooth® specifications
Bluetooth® Specification	4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4/6.0 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps



	Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels
	Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class I Bluetooth device with a maximum transmit power of +15.5 dBm for BR and +13dBm for EDR.
Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
Bluetooth® Software	Microsoft Windows Bluetooth® Software
Supported Link Topology	Linux/Chrome OS Bluetooth® Software
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407 ETSI 300 328, ETSI 301 893, ETSI 303 687
FIPS 140-3 compliant	No
Bluetooth® Profiles Supported	Advanced Audio Distribution Profile (A2DP) Basic Imaging Profile (BIP) Bluetooth® 4.1 -ESR 5/6/7 Compliance Bluetooth® 4.2 ESR08 Compliance Bluetooth® 5.2 Bluetooth® 5.3 Bluetooth® 5.4 Bluetooth® 6.0 Channel Selection Algo Compliance to the latest Errata Section 12.3 of Bluetooth® 5.3 specification Encryption key size control enhancements ESR 9/10 Compliance FAX Profile (FAX) Hands Free Profile (HFP) Headset Profile (HSP)



		Host to Controller Encryption Key Control Enhancements
		LE 2Mbps
		LE Advertisement Extensions
		LE Data Packet Length Extension
		LE Dual Mode
		LE L2CAP Connection Oriented Channels
		LE Link Layer
		LE Link Layer Ping
		LE Long Range
		LE Low Duty Cycle Directed Advertising
		LE Privacy 1.2 -Extended Scanner Filter Policies
		LE Privacy 1.2 -Link Layer Privacy
		LE Secure Connection- Basic/Full
		Limited High Duty Cycle Non-Connectable Advertising
		Periodic Advertisement interval
		Train Nudging & Interlaced Scan
		Windows Bluetooth® profiles support
Mediatek RZ616 Wi-Fi 6E	Wireless LAN Standards	IEEE 802.11a
Bluetooth® 5.3 AIM-T WLAN ^{2,3}		IEEE 802.11ac
		IEEE 802.11ax
		IEEE 802.11b
		IEEE 802.11d
		IEEE 802.11e
		IEEE 802.11g
		IEEE 802.11h
		IEEE 802.11i
		IEEE 802.11j
		IEEE 802.11k
		IEEE 802.11mc
		IEEE 802.11n
		IEEE 802.11r
		IEEE 802.11v

	IEEE 802.11w
Interoperability	Wi-Fi certified
Frequency Band	802.11b/g/n/ax/be(Wifi7) 2.402 - 2.482 GHz
	802.11a/n/ac/ax/be(Wifi7) 5.15 - 5.25 GHz 5.25 - 5.35 GHz 5.47 - 5.725 GHz 5.825 - 5.850 GHz 5.925 - 7.125 GHz
Data Rates	802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11ac : MCS0 ~ MCS9, (20MHz, 40MHz, 80MHz, 160MHz) 802.11ax : MCS0 ~ MCS11, (20MHz, 40MHz, 80MHz, 160MHz) 802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: MCS 0 ~ MCS 15, (20MHz, 40MHz)
Modulation	Direct Sequence Spread Spectrum 338, 335, 337, 336, 332, 334, 331, 333
Security	802.1x authentication AES-CCMP: 128 bit in hardware IEEE 802.11i IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only WAPI WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification WPA3 certification
Network Architecture	Ad-hoc (Peer to Peer)
Models	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power	2.4GHz (MIMO, typical): 802.11b : +18dBm



	802.11g : +16.5dBm
	802.11n/ac/ax (HT20/VHT20/HE20) : +16dBm
	802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm
	5GHz (MIMO, typical):
	802.11a : +13dBm
	802.11n/ac/ax (HT20/VHT20/HE20) : +13.5dBm
	802.11n/ac/ax (HT40/VHT40/HE40) : +12.5dBm
	802.11ac/ax (VHT80/HE80) : +11.5dBm
	802.11ax HE160 : +11.5dBm
	6GHz LPI mode (MIMO, typical):
	802.11a : 0dBm
	802.11ax HE20 : +1dBm
	802.11ax HE40 : +4dBm
	802.11ax HE80 : +7dBm
	802.11ax HE160 : +7.5dBm
Power Consumption	Transmit mode : 2.5 W
	Receive mode : 2.0 W
	Idle mode (PSP) : 180 mW (WLAN Associated)
	Idle mode: 50 mW (WLAN unassociated)
	Connected Standby/Modern Standby : 10 mW
	Radio disabled : 8 mW
Power Management	ACPI and PCI Express® compliant power management; 802.11 compliant power saving mode
Receiver Sensitivity ⁴	2.4GHz (SISO):
	802.11b, 11Mbps : -82dBm maximum
	802.11g, 54Mbps : -71dBm maximum
	802.11n, MCS7 : -64dBm maximum
	802.11ac, MCS9 : -52dBm maximum
	802.11ax, MCS11(HT40): -49dBm maximum
	5GHz (SISO):
	802.11a, 54Mbps : -71dBm maximum
	802.11n, MCS07 : -64dBm maximum



	802.11ac, MCS9 : -52dBm maximum
	802.11ax, MCS11(HE80/HE160): -46dBm maximum
	6GHz (SISO):
	802.11a, 54Mbps : -71dBm maximum
	802.11n, MCS7 : -64dBm maximum
	802.11ac, MCS9 : -52dBm maximum
	802.11ax, MCS11(HE160): -46dBm maximum
Antenna Type	High efficiency antenna with spatial diversity, mounted in the display enclosure
	Two embedded dual band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI Express® M.2 MiniCard
Dimensions	30.00 x 22.00 x 2.30 mm (1.18 x 0.87 x 0.09 inch)
Weight	Type 2230: 2.8 g(0.099 oz)
Operating Voltage	3.3 v +/- 9 %
	Integrated Bluetooth® specifications
Bluetooth® Specification	4.0/4.1/4.2/5.0/5.1/5.2/5.3 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class 1.5 Bluetooth device with a maximum transmit power of + 14 dBm and 10 dBm for BR and EDR, respectively.
Power Consumption	Peak (Tx): 330 mW Peak (Rx): 230 mW



	Selective Suspend: 17 mW
Bluetooth® Software	Microsoft Windows Bluetooth® Software
Supported Link Topology	
Power Management	Microsoft Windows ACPI, and USB Bus Support
Certifications	FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407 ETSI 300 328, ETSI 301 893, ETSI 303 687
FIPS 140-3 compliant	No
Bluetooth® Profiles	Advanced Audio Distribution Profile (A2DP)
Supported	Basic Imaging Profile (BIP) Bluetooth® 4.1 -ESR 5/6/7 Compliance Bluetooth® 4.2 ESR08 Compliance Bluetooth® 5.2 Channel Selection Algo Encryption key size control enhancements FAX Profile (FAX) Hands Free Profile (HFP) Headset Profile (HSP) LE 2Mbps LE Advertisement Extensions LE Data Packet Length Extension LE Dual Mode LE L2CAP Connection Oriented Channels LE Link Layer LE Link Layer Ping LE Long Range LE Low Duty Cycle Directed Advertising LE Privacy 1.2 -Extended Scanner Filter Policies LE Privacy 1.2 -Link Layer Privacy LE Secure Connection- Basic/Full Limited High Duty Cycle Non-Connectable Advertising Periodic Advertisement interval Train Nudging & Interlaced Scan Windows Bluetooth® profiles support



- 1. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 7 (802.11be) functionality requires compatible Chrome OS, select processor, and a Wi-Fi 7 router, sold separately. Wi-Fi 7 is backwards compatible with prior 802.11 specs. Available in countries where Wi-Fi 7 is supported.
- 2. Wi-Fi 6E requires a Wi-Fi 6E router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 6E is backwards compatible with prior 802.11 specs. Available in countries where Wi-Fi 6E is supported.
- 3. Wi-Fi 6E is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
- 4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Qualcomm® SDX35 5G RedCap WWAN ⁵	Technology Operating Bands	LTE FDD/TDD operating bands:
		Band 01: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL) Band 02: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL) Band 03: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL) Band 04: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL) Band 05: 824 to 849 MHz (UL), 869 to 894 MHz (DL) Band 07: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL) Band 08: 880 to 915 MHz (UL), 925 to 960 MHz (DL) Band 12: 699 to 716 MHz (UL), 729 to 746 MHz (DL) Band 13: 777 to 787 MHz (UL), 746 to 756 MHz (DL) Band 14: 788 to 798 MHz (UL), 758 to 768 MHz (DL) Band 17: 704 to 716 MHz (UL), 734 to 746 MHz (DL) Band 18: 815 to 830 MHz (UL), 860 to 875 MHz (DL) Band 19: 830 to 845 MHz (UL), 875 to 890 MHz (DL) Band 20: 832 to 862 MHz (UL), 791 to 821 MHz (DL) Band 25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL) Band 26: 814 to 849 MHz (UL), 859 to 894 MHz (DL) Band 28: 703 to 748 MHz (UL), 758 to 803 MHz (DL) Band 29: 717 to 728 MHz (DL) Band 30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL) Band 66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL) Band 71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)

	5GNR Sub 6GHZ:
	n1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)
	n12: 699 to 716 MHz (UL), 729 - 746 MHz (DL)
	n13: 777 to 787 MHz (UL), 746 - 756 MHz (DL)
	n14: 788 to 798MHz (UL), 758- 768 MHz (DL)
	n18: 815 to 830 MHz (UL), 860- 875 MHz (DL)
	n2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)
	n20: 832 to 862 MHz (UL), 791 to 821 MHz (DL)
	n25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL)
	n26: 814 to 839 MHz (UL), 860- 875 MHz (DL)
	n28: 703 to 748 MHz (UL), 758 to 803 MHz (DL)
	n3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL)
	n30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL)
	n38: 2570 to 2620 MHz (UL/DL)
	n40: 2300 to 2400 MHz (UL/DL)
	n41: 2496 to 2690 MHz (UL/DL)
	n48: 3550 to 3700 MHz (UL/DL)
	n5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)
	n66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL)
	n7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL)
	n70: 1695 to 1710 MHz (UL), 1995 to 2020 MHz (DL)
	n71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)
	n77: 3300 to 4200 MHz (UL/DL)
	n78: 3300 to 3800 MHz (UL/DL)
	n79: 4400 to 5000 MHz (UL/DL)
	n8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)
Maximum Data Rates	5G SA sub-6 Peak: 226.00 Mbps(Download), 121.00 Mbps (Upload)
	(0.20 Gbps Download), (105.00 Mbps Upload)
Maximum Output Power	NR n41, n77, n78, n79 HPUE: 26.0 dBm Support HPUE
	LTE all band (except B30= 22dBm & B48= 21.5dBm); 23.0 dBm
	Not support HPUE



Maximum Power	5G Sub 6: 2,500 mA (peak); 900 mA (average)
Consumption	LTE: 2,500 mA (peak); 900 mA (average)
Form Factor	M.2
Weight	5.9 g (0.208 oz)
Dimensions (Length x Width x Thickness)	30.00 x 42.00 x 2.30 mm (1.18 x 1.65 x 0.09 inch)
Embedded eSIM	Yes

5. 5G module is optional. WWAN-ready configuration must be selected at purchase to add WWAN module at a later date (WWAN After Market Option Kit). Module designed for 5G RedCap (Reduced Capability), 5G NR SA (Standalone) and 4G LTE Public and Private networks with both 20MHz of 5G NR and LTE channel bandwidth, using 256QAM 2x2 as defined by 3GPP. Module includes embedded eSIM. Module requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Data connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. Backwards compatible to 4G LTE technologies. 5G module planned to be available in select platforms and select countries, where carrier and frequency bands supported.



POWER

Power supply availability may vary by country.

Battery is internal and replaceable by customer.

Higher wattage adapter is recommended for best performance and fastest charging.

Using lower-capacity third-party USB Type-C® power cables may reduce power delivery.

HP 45W Standard USB Type-C® GaN AC power adapter	Weight (DC Cable Included)	185 g ± 10 g
	Input	100 Vac ~ 240 Vac
	Input Efficiency	USB-C 88.85 % min at 115 Vac/ 230 Vac @ 20.00 V/ 2.25 A
	Input frequency range	47 Hz ~ 63 Hz
	Input AC current	Max 1.40 A at 90 Vac input
	Output	
	Output power	20.00 V / 45.00 W
	DC output	+ 20.00 V
	Hold - up time	5 ms at 115 Vac input
	Output Over Current	5.00 A (max)
	Protection	
	AC Inlet Type	C6
	DC Cable Connector	USB Type-C
	DC Cable Material	PVC
	Connector	
	Connector	C6
	Environmental Design	
	Operating temperature	0°C to 35°C (32°F to 95°F)
	Non - operating(storage) temperature	-20°C to 85°C (-4°F to 185°F)
	Altitude	0 m to 5000 m (0 ft to 16404.2 ft)
	Humidity	20 % to 95 %
	Storage Humidity	10 % to 95 %
	EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1 and IEC62368-1 :

		2018, EN62368-1:2014+A11, UL62368-1
		Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC, USB-IF, Ukraine(CoC+DoC+RoHS+ECO)
HP 45W Wall Mount USB Type-C® GaN Halogen Free AC power adapter	Weight (DC Cable Included)	130 g ± 10 g
	Input	100 Vac ~ 240 Vac
	Input Efficiency	USB-C
		8.85 % min at 115 Vac/ 230 Vac @ 20.00 V/ 2.25 A
	Input frequency range	47 Hz ~ 63 Hz
	Input AC current	Max 1.40 A at 90 Vac input
	Output	
	Output power	20.00 V / 45.00 W
	DC output	20.00 V
	Hold - up time	5 ms at 115 Vac input
	Output Over Current Protection	3.75 A (max)
	AC Inlet Type	Foldable for 2 prong
	DC Cable Connector	USB Type-C
	DC Cable Material	Halogen Free
	Connector	
	Connector	Foldable for 2 prong
	Environmental Design	
	Operating temperature	0°C to 35°C (32°F to 95°F)
	Non - operating(storage) temperature	-20°C to 85°C (-4°F to 185°F)
	Altitude	0 m to 5000 m (0 ft to 16404.2 ft)
	Humidity	20 % to 95 %
	Storage Humidity	10 % to 95 %
	EMI and Safety Certifications	Worldwide safety standards - IEC60950-1 and IEC62368-1:

HP 45W Wall Mount USB
Type-C® GaN Halogen Free
AC power adapter

	2018, EN62368-1:2014+A11, UL62368-1	
	Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC	
Weight (DC Cable Included)	185 g ± 10 g	
Input	100 Vac ~ 240 Vac	
Input Efficiency	USB-C	
	88.85 % min at 115 Vac/ 230 Vac @ 20.00 V/ 2.25 A	
Input frequency range	47 Hz ~ 63 Hz	
Input AC current	Max 1.40 A at 90 Vac input	
Output		
Output power	20.00 V / 45.00 W	
DC output	+ 20.00 V	
Hold - up time	5 ms at 115 Vac input	
Output Over Current	5.00 A (max)	
Protection		
AC Inlet Type	Fixed 2 Prong	
DC Cable Connector	USB Type-C	
DC Cable Material	PVC	
Connector		
Connector	Fixed 2 Prong	
Environmental Design		
Operating temperature	0°C to 35°C (32°F to 95°F)	
Non - operating(storage) temperature	-20°C to 85°C (-4°F to 185°F)	
Altitude	0 m to 5000 m (0 ft to 16404.2 ft)	
Humidity	20 % to 95 %	
Storage Humidity	10 % to 95 %	
EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives	
	Worldwide safety standards - IEC60950-1 and IEC62368-1 :	



2018, EN62368-1:2014+A11, UL62368-1
Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC, USB-IF, Ukraine(CoC+DoC+RoHS+ECO)

Battery

HP Long Life 3 cell, 41Wh
Polymer

Weight	175 g ± 10 g (0.39 lb)
Cells / Type	3 cell Lithium-Ion Polymer /
Energy	
Voltage	11.25 V
Amp - hour capacity	3.750 Ah
Watt - hour capacity	41.0.00
Temperature	
Operating (Charging)	0°C to 45°C (32°F to 113°F)
Operating (Discharging)	0°C to 50°C (32°F to 122°F)
Optional Travel Battery Available	No



AUDIO

Codec	Realtek ALC5650
Audio I/O Ports	Combo audio jack with CTIA
Internal Speaker Amplifier	Codec Integrated (Realtek ALC5650)
Multi-streaming Capable	
Sampling	DAC: Supports resolutions from 16-bit to 24-bit;44.1 kHz to 48.0 kHz ADC: Supports resolutions from 16-bit to 24-bit;44.1 kHz to 48.0 kHz
Wavetable Syntheses	Yes - Uses OS soft wavetable
# of Channels on Line-Out	Stereo (Left & Right channels)
Internal Speaker	Yes

OPTIONS

Container Name	Description	Part Number
Adapters	HP HDMI to VGA Adapter	H4F02AA#ABA,H4F02AA#AC3, H4F02AA#UUF
	HP USB 3.0 to Gigabit RJ45 Adapter G2	4Z7Z7AA
	HP USB-C to DisplayPort Adapter G2	8Y8Y1AA
	HP USB-C to HDMI 2.0 Adapter	1WC36AA
	HP USB-C to RJ45 Adapter G2	4Z527AA
	HP USB-C to USB 3.0 Adapter	N2Z63AA#ABA,N2Z63AA#AC3
Audio - Earbuds	HP USB-C to VGA Adapter	N9K76AA#ABA,N9K76AA#AC3
	Poly Voyager Free 60/60+ Black Earbuds (2 Pieces)	8L5A6AA
	Poly Voyager Free 60/60+ Microsoft Teams Certified Black Earbuds (2 Pieces)	8L5A8AA
	Poly Voyager Free 60+ UC Carbon Black Earbuds +BT700 USB-C Adapter +Touchscreen Charge Case	7Y8G4AA
Audio - Headset	HP Poly Focus 625 Fold Headset + Wireless Charge Stand	C56XZAA#AC3,C56XZAA#B13
	HP Poly Focus 625 Fold Stereo Bluetooth Headset	C56XSAA#AC3,C56XSAA#B13
	HP Poly Focus 625 Headset + Wireless Charge Stand	C56XXAA#AC3,C56XXAA#B13
	HP Poly Focus 625 Stereo Bluetooth Headset	C56XPAA#AC3,C56XPAA#B13
	HP Poly Mission 415 Monaural USB Wired Headset Classic	C01A9AA#AC3
	HP Poly Mission 425 Stereo USB Wired Headset Classic	C01B3AA#AC3
	HP Poly Mission 615 Monaural	C01F4AA#AC3
	HP Poly Mission 615 Monaural USB Wired Headset	C01C3AA#AC3
	HP Poly Mission 625 Stereo	C01F6AA#AC3
	HP Poly Mission 625 Stereo USB Wired Headset	C01C6AA#AC3
	HP Poly Mission 815 Monaural USB Wired Headset	C01F8AA#AC3,C01F8AA#B13
	HP Poly Mission 825 Stereo USB Wired Headset	C01FCAA#AC3,C01FCAA#B13
	Poly Blackwire 8225 Stereo USB-C Headset	8X223AA
	Poly Blackwire 8225 Stereo USB-C Headset	8X225AA
	Poly Savi 7310 DECT 1880-1900 MHz Single Ear Headset	8D3G3AA#ABB,8D3G3AA#AB G,8D3G3AA#UUF
	Poly Savi 7310 Monaural DECT 1880-1900 MHz Headset	8L561AA#ABB,8L561AA#ABG
	Poly Savi 7310 Monaural DECT 1880-1900 MHz Headset	8L575AA#ABB,8L575AA#ABG
	Poly Savi 7310 Monaural DECT 1880-1900 MHz Top	8Y9B6AA#ABB,8Y9B6AA#ABG, 8Y9B6AA#UUF
	Poly Savi 7310 Monaural DECT 1880-1900 MHz Top	8Y9B8AA#ABB,8Y9B8AA#ABG, 8Y9B8AA#UUF
	Poly Savi 7310 Monaural DECT 1893-1906 MHz Top	9V8Z7AA#ABJ



Poly Savi 7310 Monaural DECT 1920-1930 MHz Headset	7S430AA#ABA
Poly Savi 7310 Monaural DECT 1920-1930 MHz Headset	8L570AA#ABA
Poly Savi 7310 Monaural DECT 1920-1930 MHz Headset	8L585AA#ABA
Poly Savi 7310 Monaural DECT 1920-1930 MHz Top	783N0AA#ABA
Poly Savi 7310 Monaural DECT 1920-1930 MHz Top	783N2AA#ABA
Poly Savi 7310-M DECT 1880-1900 MHz Single Ear Headset	8D3K7AA#ABB,8D3K7AA#ABG, 8D3K7AA#UUF
Poly Savi 7310-M DECT 1920-1930 MHz Single Ear Headset	7S439AA#ABA
Poly Savi 7320 Stereo DECT 1880-1900 MHz Headset	8D3F7AA#ABB,8D3F7AA#ABG, 8D3F7AA#UUF
Poly Savi 7320 Stereo DECT 1880-1900 MHz Headset	8L545AA#ABB,8L545AA#ABG, 8L545AA#UUF
Poly Savi 7320 Stereo DECT 1880-1900 MHz Headset	8L553AA#ABB,8L553AA#ABG, 8L553AA#UUF
Poly Savi 7320 Stereo DECT 1880-1900 MHz Top	8Y9B7AA#ABB,8Y9B7AA#ABG, 8Y9B7AA#UUF
Poly Savi 7320 Stereo DECT 1880-1900 MHz Top	8Y9B9AA#ABB,8Y9B9AA#ABG, 8Y9B9AA#UUF
Poly Savi 7320 Stereo DECT 1893-1906 MHz Headset	8D3F8AA#ABJ
Poly Savi 7320 Stereo DECT 1893-1906 MHz Headset	8L546AA#ABJ
Poly Savi 7320 Stereo DECT 1893-1906 MHz Headset	8L555AA#ABJ
Poly Savi 7320 Stereo DECT 1893-1906 MHz Top	9V8Z6AA#ABJ
Poly Savi 7320 Stereo DECT 1893-1906 MHz Top	9V8Z8AA#ABJ
Poly Savi 7320 Stereo DECT 1920-1930 MHz Headset	7S429AA#ABA
Poly Savi 7320 Stereo DECT 1920-1930 MHz Headset	8L549AA#ABA
Poly Savi 7320 Stereo DECT 1920-1930 MHz Headset	8L559AA#ABA
Poly Savi 7320 Stereo DECT 1920-1930 MHz Top	783N1AA#ABA
Poly Savi 7320 Stereo DECT 1920-1930 MHz Top	783N3AA#ABA
Poly Savi 7320-M Stereo DECT 1880-1900 MHz Headset	8D3J6AA#ABB,8D3J6AA#ABG, 8D3J6AA#UUF
Poly Savi 7320-M Stereo DECT 1893-1906 MHz Headset	8D3K2AA#ABJ
Poly Savi 7320-M Stereo DECT 1920-1930 MHz Headset	7S435AA#ABA
Poly Savi 8210 DECT 1880-1900 MHz USB-A Headset	8D3E9AA#ABB,8D3E9AA#ABG, 8D3E9AA#UUF
Poly Savi 8210 DECT 1880-1900 MHz USB-A Headset	8D3F1AA#ABB,8D3F1AA#ABG, 8D3F1AA#UUF
Poly Savi 8210 DECT 1920-1930 MHz USB-A Headset	77T29AA#ABA
Poly Savi 8210 DECT 1920-1930 MHz USB-A Headset	77T31AA#ABA



Poly Savi 8220 DECT 1880-1900 MHz USB-A Headset	8D3F2AA#ABB,8D3F2AA#ABG, 8D3F2AA#UUF
Poly Savi 8220 DECT 1880-1900 MHz USB-A Headset	8D3F5AA#ABB,8D3F5AA#ABG, 8D3F5AA#UUF
Poly Savi 8220 DECT 1920-1930 MHz USB-A Headset	77T33AA#ABA
Poly Savi 8220 DECT 1920-1930 MHz USB-A Headset	77Y82AA#ABA
Poly Savi 8410 Monaural DECT 1880-1900 MHz Headset	8L5A7AA#ABB,8L5A7AA#ABG, 8L5A7AA#UUF
Poly Savi 8410 Monaural DECT 1880-1900 MHz Headset	8L5A9AA#ABB,8L5A9AA#ABG, 8L5A9AA#UUF
Poly Savi 8410 Monaural DECT 1920-1930 MHz Headset	8L7E6AA#ABA
Poly Savi 8410 Monaural DECT 1920-1930 MHz Headset	8L7E9AA#ABA
Poly Savi 8420 Stereo DECT 1880-1900 MHz Headset	8L5B2AA#ABB,8L5B2AA#ABG, 8L5B2AA#UUF
Poly Savi 8420 Stereo DECT 1880-1900 MHz Headset	8L5B3AA#ABB,8L5B3AA#ABG, 8L5B3AA#UUF
Poly Savi 8420 Stereo DECT 1920-1930 MHz Headset	8L7F2AA#ABA
Poly Savi 8420 Stereo DECT 1920-1930 MHz Headset	8L7F5AA#ABA
Poly Savi 8445 DECT 1880-1900 MHz Convertible Headset	8L5B4AA#ABG,8L5B4AA#UUF
Poly Savi 8445 DECT 1880-1900 MHz Convertible Headset	8L5B6AA#ABG,8L5B6AA#UUF
Poly Savi 8445 DECT 1920-1930 MHz Convertible Headset	8L7F1AA#ABA
Poly Savi 8445 DECT 1920-1930 MHz Convertible Headset	8L7F7AA#ABA
Poly Savi 8445 DECT 1920-1930 MHz Convertible Headset	8L7F8AA#ABA
Poly Voyager 4310 Headset	77Y93AA
Poly Voyager 4310 Monaural Headset	77Y92AA
Poly Voyager 4310 USB-A Headset	76U48AA
Poly Voyager 4310 USB-A Headset	77Y91AA
Poly Voyager 4310 USB-C Headset	77Y94AA
Poly Voyager 4310 USB-C Headset	77Y95AA
Poly Voyager 4310 USB-C Headset	77Y96AA
Poly Voyager 4310-M USB-C Headset	77Y97AA
Poly Voyager 4320 Headset	77Z00AA
Poly Voyager 4320 Stereo USB-A Headset	77Y99AA
Poly Voyager 4320 USB-A Headset	76U49AA
Poly Voyager 4320 USB-A Headset	77Y98AA
Poly Voyager 4320 USB-C Headset	76U50AA
Poly Voyager 4320 USB-C Headset	77Z30AA
Poly Voyager 4320 USB-C Headset	77Z31AA



Audio - Speaker phone	Poly Voyager 4320-M Headset	77Z32AA
	Poly Voyager Surround 80 USB-C Headset	8G7T9AA
	Poly Voyager Surround 80 USB-C Headset	8G7U0AA
	Poly Voyager Surround 85 USB-C Headset	8G7T7AA
	Poly Voyager Surround 85 USB-C Headset	8G7T8AA
	Poly Sync 10 Speakerphone	77P34AA
	Poly Sync 60 Speakerphone	772C2AA
	Poly Sync 60 Speakerphone	77P41AA
Camera	Poly Sync USB-A USB-C 10 Speakerphone	772C3AA
	HP 435 FHD Webcam	77B10AA#ABA,77B10AA#ABB, 77B10AA#UUF
	HP 625 FHD Webcam	6Y7L1AA#ABB,6Y7L1AA#ABL,6 Y7L1AA#UUF
Cases	HP 325 FHD USB-A Webcam	53X27AA
	HP 14 Convertible Laptop Backpack Tote	9C2H1AA
	HP 215 15.6 Laptop Backpack	35L98UT#ACJ,AP4Y9UT#ACJ
	HP 225 15.6 Laptop Backpack	2P7U6AA#ACJ,2P7U6UT#ACJ, AP4Z0UT#ACJ
	HP Campus blue Backpack	7K0E5AA
	HP Campus XL Tie Dye Backpack	7K0E3AA
	HP Convertible Laptop Stand	9C2H2AA
	HP Everyday 14 odyssey gray Laptop Bag	A08KJAA
	HP Everyday 14 odyssey gray Laptop Briefcase	A08KGAA,A08KGUT
	HP Everyday 16 odyssey gray Laptop Backpack	A08KLAA,A08KLUT
	HP Everyday 16 odyssey gray Laptop Bag	A08KKAA
	HP Everyday 16 odyssey gray Laptop Briefcase	A08KHAA,A08KHUT
	HP Modern 14-inch moonless Night Laptop Briefcase	CJ8D0AA#ABB,CJ8D0AA#UUF
	HP Modern 14-inch navy blazer Laptop Briefcase	CJ8F8AA#ABA
	HP Modern 16-inch moonless Night Laptop Briefcase	CJ8D2AA#ABB
	HP Modern 16-inch navy blazer Laptop Briefcase	CJ8F9AA#ABA
	HP Prelude 15.6 Backpack	1E7D6UT,50P32AA
	HP Prelude 15.6 Top Load	1E7D7AA
	HP Protective 13-14 atmospheric blue Laptop Sleeve	C3TR3UT#ABA,C3TR3UT#ABB, C3TR3UT#UUF
	HP Protective 13-14 meteor silver Laptop Sleeve	C3TR2UT#ABB
	HP Protective 15-16 atmospheric blue Laptop Sleeve	C40BPUT#ABA,C40BPUT#ABB, C40BPUT#UUF
	HP Protective 15-16 meteor silver Laptop Sleeve	C40BQUT#ABB



Commodity	HP Renew Business 14.1 Laptop Bag	3E5F9AA
	HP Renew Business 14.1 Laptop Sleeve	3E2U7AA
	HP Renew Business 15.6 Laptop Bag	3E5F8AA
	HP Renew Business 17.3 Laptop Backpack	3E2U5UT
	HP Renew Business 17.3 Laptop Bag	3E2U6AA
	HP Renew Executive 14.1 Laptop Sleeve	6B8Y3AA
	HP Renew Executive 16 Laptop Backpack	6B8Y1UT
	HP Renew Executive 16 Laptop Bag	6B8Y2AA
	HP Travel 18 Liter 15.6 iron gray Laptop Backpack	6H2D9AA
	HP Travel 25 Liter 15.6 iron gray Laptop Backpack	6H2D8AA
	HP Travel Plus 15 Liter 14 Laptop Bag	A2CE2AA
	HP Travel Plus 22 Liter 16 Laptop Bag	A2CE1AA
	HP Travel Plus 30 Liter 17 Laptop Backpack	A2CE0AA
	HP USB DVD-Writer External ODD	F2B56AA
	HP 14-inch Widescreen Laptop Privacy Filter	BH0M6AA
Hub	HP Portable USB-C 4K HDMI Hub	BR1U0UT
	HP Portable USB-C Hub	B8SU8UT
	HP Universal USB-C Multiport Hub	50H55UT
	HP USB-C to USB-A Hub	Z6A00AA
Keyboard	HP USB-C Travel Hub G3	86S97UT
	HP 125 G2 Wired Keyboard	AY2Y7AA#A2M,AY2Y7AA#A2Q, AY2Y7AA#AB0,AY2Y7AA#AB1, AY2Y7AA#AB2,AY2Y7AA#AB4, AY2Y7AA#AB6,AY2Y7AA#AB7, AY2Y7AA#AB8,AY2Y7AA#AB9, AY2Y7AA#ABA,AY2Y7AA#ABB, AY2Y7AA#ABC,AY2Y7AA#ABD, AY2Y7AA#ABE,AY2Y7AA#ABF, AY2Y7AA#ABJ,AY2Y7AA#ABM, AY2Y7AA#ABT,AY2Y7AA#ABU, AY2Y7AA#ABV,AY2Y7AA#ABZ, AY2Y7AA#AC0,AY2Y7AA#AC3, AY2Y7AA#AC4,AY2Y7AA#ACB, AY2Y7AA#ACJ,AY2Y7AA#AK4, AY2Y7AA#AKC,AY2Y7AA#AKE, AY2Y7AA#AKL,AY2Y7AA#AKS, AY2Y7AA#AR4,AY2Y7AA#ARK, AY2Y7AA#B15,AY2Y7AA#BCM,

HP 175K Wired Keyboard

AY2Y7AA#BED,AY2Y7AA#UUF,
AY2Y7AA#UUW,AY2Y7AA#UUZ
D54CRAA#A2M,D54CRAA#A2
Q,D54CRAA#AB0,D54CRAA#A
B1,D54CRAA#AB2,D54CRAA#
AB4,D54CRAA#AB6,D54CRAA
#AB7,D54CRAA#AB8,D54CRA
A#AB9,D54CRAA#ABA,D54CR
AA#ABB,D54CRAA#ABC,D54C
RAA#ABD,D54CRAA#ABE,D54
CRAA#ABF,D54CRAA#ABJ,D54
CRAA#ABM,D54CRAA#ABT,D5
4CRAA#ABU,D54CRAA#ABV,D
54CRAA#ABZ,D54CRAA#AC0,
D54CRAA#AC3,D54CRAA#AC4
,D54CRAA#ACB,D54CRAA#AK
C,D54CRAA#AKE,D54CRAA#AK
L,D54CRAA#AKS,D54CRAA#AR
4,D54CRAA#ARK,D54CRAA#B1
5,D54CRAA#BCM,D54CRAA#B
ED,D54CRAA#UUF,D54CRAA#U
UW,D54CRAA#UUZ

HP 275K Wireless Keyboard

D4YK9AA#A2M,D4YK9AA#A2Q,
D4YK9AA#AB0,D4YK9AA#AB1,
D4YK9AA#AB2,D4YK9AA#AB4,
D4YK9AA#AB6,D4YK9AA#AB7,
D4YK9AA#AB8,D4YK9AA#AB9,
D4YK9AA#ABA,D4YK9AA#ABB,
D4YK9AA#ABC,D4YK9AA#ABD,
D4YK9AA#ABE,D4YK9AA#ABF,
D4YK9AA#ABJ,D4YK9AA#ABM,
D4YK9AA#ABT,D4YK9AA#ABU,
D4YK9AA#ABV,D4YK9AA#ABZ,
D4YK9AA#AC0,D4YK9AA#AC3,
D4YK9AA#AC4,D4YK9AA#ACB,
D4YK9AA#AKC,D4YK9AA#AKE,
D4YK9AA#AKL,D4YK9AA#AKS,
D4YK9AA#AR4,D4YK9AA#ARK,



HP 320K G2 Wired Keyboard

D4YK9AA#B15,D4YK9AA#BCM,
D4YK9AA#BED,D4YK9AA#UUF,
D4YK9AA#UUW,D4YK9AA#UUZ
9SR37UT#A2M,9SR37UT#A2Q,
9SR37UT#AB0,9SR37UT#AB1,
9SR37UT#AB2,9SR37UT#AB4,
9SR37UT#AB6,9SR37UT#AB7,
9SR37UT#AB8,9SR37UT#AB9,
9SR37UT#ABA,9SR37UT#ABB,
9SR37UT#ABC,9SR37UT#ABD,
9SR37UT#ABE,9SR37UT#ABF,9
SR37UT#ABJ,9SR37UT#ABM,9
SR37UT#ABT,9SR37UT#ABU,9
SR37UT#ABV,9SR37UT#ABZ,9
SR37UT#AC0,9SR37UT#AC3,9
SR37UT#AC4,9SR37UT#ACB,9
SR37UT#ACH,9SR37UT#ACJ,9
SR37UT#AK4,9SR37UT#AKC,9
SR37UT#AKE,9SR37UT#AKL,9S
R37UT#AKS,9SR37UT#AR4,9S
R37UT#ARK,9SR37UT#B15,9S
R37UT#BCM,9SR37UT#BED,9S
R37UT#UUF,9SR37UT#UUW,9S
R37UT#UUZ

HP 405 Backlit Wired Keyboard

7N7C1AA#A2M,7N7C1AA#A2
Q,7N7C1AA#AB6,7N7C1AA#A
B7,7N7C1AA#AB8,7N7C1AA#A
B9,7N7C1AA#ABA,7N7C1AA#
ABB,7N7C1AA#ABD,7N7C1AA
#ABE,7N7C1AA#ABF,7N7C1AA
#ABJ,7N7C1AA#ABM,7N7C1A
A#ABT,7N7C1AA#ABU,7N7C1A
A#ABV,7N7C1AA#ABY,7N7C1A
A#ABZ,7N7C1AA#AC0,7N7C1
AA#ACB,7N7C1AA#ACQ,7N7C
1AA#AKC,7N7C1AA#AKE,7N7C
1AA#AKQ,7N7C1AA#AKS,7N7
C1AA#AR4,7N7C1AA#ARK,7N7



HP 485 Comfort Wired Keyboard

C1AA#B15,7N7C1AA#BCM,7N
7C1AA#BED,7N7C1AA#UUF,7N
7C1AA#UUW,7N7C1AA#UUZ,7
N7C1UTABA
8T6M2AA#A2M,8T6M2AA#A2
Q,8T6M2AA#AB6,8T6M2AA#A
B7,8T6M2AA#AB8,8T6M2AA#A
B9,8T6M2AA#ABA,8T6M2AA#A
BB,8T6M2AA#ABD,8T6M2AA#
ABE,8T6M2AA#ABF,8T6M2AA#
ABM,8T6M2AA#ABT,8T6M2AA
#ABU,8T6M2AA#ABV,8T6M2AA
#ABZ,8T6M2AA#AC0,8T6M2AA
#AC3,8T6M2AA#AC4,8T6M2A
A#ACB,8T6M2AA#AKC,8T6M2
AA#AKE,8T6M2AA#AKS,8T6M2
AA#AR4,8T6M2AA#ARK,8T6M2
AA#B15,8T6M2AA#BCM,8T6M
2AA#BED,8T6M2AA#UUF,8T6M
2AA#UUW,8T6M2AA#UUZ
BD5F5UT#A2M,BD5F5UT#A2Q,
BD5F5UT#AB6,BD5F5UT#AB7,
BD5F5UT#AB8,BD5F5UT#AB9,
BD5F5UT#ABB,BD5F5UT#ABD,
BD5F5UT#ABE,BD5F5UT#ABF,B
D5F5UT#ABJ,BD5F5UT#ABT,BD
5F5UT#ABU,BD5F5UT#ABV,BD
5F5UT#ABZ,BD5F5UT#AC0,BD
5F5UT#AC3,BD5F5UT#ACB,BD
5F5UT#AKC,BD5F5UT#AKE,BD
5F5UT#AKS,BD5F5UT#AR4,BD
5F5UT#ARK,BD5F5UT#B15,BD5
F5UT#BCM,BD5F5UT#BED,BD5
F5UT#UUF,BD5F5UT#UUW,BD5
F5UT#UUZ
BD5F7AA#A2M,BD5F7AA#A2Q,
BD5F7AA#AB6,BD5F7AA#AB7,
BD5F7AA#AB8,BD5F7AA#AB9,

HP Multi-Device Dual-Mode Keyboard 495KHP 495K Multi-
Device Keyboard

HP Multi-Device Dual-Mode Keyboard with Palm Rest 585K



HP 685 Comfort Dual-Mode Keyboard

BD5F7AA#ABB,BD5F7AA#ABD,
BD5F7AA#ABE,BD5F7AA#ABF,
BD5F7AA#ABT,BD5F7AA#ABU,
BD5F7AA#ABV,BD5F7AA#ABZ,
BD5F7AA#AC0,BD5F7AA#AC3,
BD5F7AA#ACB,BD5F7AA#AKC,
BD5F7AA#AKE,BD5F7AA#AKS,
BD5F7AA#AR4,BD5F7AA#ARK,
BD5F7AA#B15,BD5F7AA#BCM,
BD5F7AA#BED,BD5F7AA#UUW,
BD5F7AA#UUZ
8T6L9UT#A2M,8T6L9UT#A2Q,8
T6L9UT#AB6,8T6L9UT#AB7,8T
6L9UT#AB8,8T6L9UT#AB9,8T6
L9UT#ABA,8T6L9UT#ABB,8T6L
9UT#ABD,8T6L9UT#ABE,8T6L9
UT#ABF,8T6L9UT#ABM,8T6L9U
T#ABT,8T6L9UT#ABU,8T6L9UT
#ABV,8T6L9UT#ABZ,8T6L9UT#
AC0,8T6L9UT#AC3,8T6L9UT#A
CB,8T6L9UT#AKC,8T6L9UT#AK
E,8T6L9UT#AKS,8T6L9UT#AR4,
8T6L9UT#ARK,8T6L9UT#B15,8
T6L9UT#BCM,8T6L9UT#BED,8T
6L9UT#UUF,8T6L9UT#UUW,8T6
L9UT#UUZ

HP 725 Multi-Device Rechargeable Wireless Keyboard

9T5B2AA#A2M,9T5B2AA#A2Q,
9T5B2AA#AB0,9T5B2AA#AB1,
9T5B2AA#AB2,9T5B2AA#AB4,
9T5B2AA#AB6,9T5B2AA#AB7,
9T5B2AA#AB8,9T5B2AA#AB9,
9T5B2AA#ABA,9T5B2AA#ABB,
9T5B2AA#ABC,9T5B2AA#ABD,
9T5B2AA#ABE,9T5B2AA#ABF,
9T5B2AA#ABJ,9T5B2AA#ABM,
9T5B2AA#ABT,9T5B2AA#ABU,
9T5B2AA#ABV,9T5B2AA#ABZ,
9T5B2AA#AC0,9T5B2AA#AC3,



Keyboard & Mouse Combo

HP 225 Wired Mouse and Keyboard Combo Cashmere White

9T5B2AA#ACB,9T5B2AA#ACJ,
9T5B2AA#AKC,9T5B2AA#AKE,
9T5B2AA#AKL,9T5B2AA#AKS,9
T5B2AA#AR4,9T5B2AA#ARK,9
T5B2AA#B15,9T5B2AA#BCM,9
T5B2AA#BED,9T5B2AA#UUF,9T
5B2AA#UUW,9T5B2AA#UUZ
AW5S6AA#A2M,AW5S6AA#A2
Q,AW5S6AA#AB6,AW5S6AA#A
B7,AW5S6AA#AB8,AW5S6AA#
AB9,AW5S6AA#ABB,AW5S6AA
#ABD,AW5S6AA#ABE,AW5S6A
A#ABF,AW5S6AA#ABT,AW5S6
AA#ABU,AW5S6AA#ABV,AW5S
6AA#ABZ,AW5S6AA#AC0,AW5
S6AA#AC3,AW5S6AA#ACB,AW
5S6AA#AKC,AW5S6AA#AKE,A
W5S6AA#AKS,AW5S6AA#AR4,
AW5S6AA#ARK,AW5S6AA#B1
5,AW5S6AA#BCM,AW5S6AA#B
ED,AW5S6AA#UUW,AW5S6AA#
UUZ
1Y4D0UT#A2M,1Y4D0UT#A2Q,
1Y4D0UT#AB1,1Y4D0UT#AB6,
1Y4D0UT#AB7,1Y4D0UT#AB8,
1Y4D0UT#AB9,1Y4D0UT#ABA,
1Y4D0UT#ABB,1Y4D0UT#ABC,
1Y4D0UT#ABD,1Y4D0UT#ABE,
1Y4D0UT#ABF,1Y4D0UT#ABH,
1Y4D0UT#ABM,1Y4D0UT#ABN,
1Y4D0UT#ABS,1Y4D0UT#ABT,
1Y4D0UT#ABU,1Y4D0UT#ABV,
1Y4D0UT#ABX,1Y4D0UT#ABY,
1Y4D0UT#ABZ,1Y4D0UT#AC0,
1Y4D0UT#AC3,1Y4D0UT#AC4,
1Y4D0UT#ACB,1Y4D0UT#ACQ,
1Y4D0UT#AKB,1Y4D0UT#AKC,
1Y4D0UT#AKD,1Y4D0UT#AKE,

HP 235 Wireless Mouse and Keyboard Combo



HP 275C Mouse and Keyboard Combo

1Y4D0UT#AKQ,1Y4D0UT#AKR,
1Y4D0UT#AKS,1Y4D0UT#ARK,
1Y4D0UT#B13,1Y4D0UT#B15,
1Y4D0UT#B1T,1Y4D0UT#BCM,
1Y4D0UT#BED,1Y4D0UT#UUF,
1Y4D0UT#UUW,1Y4D0UT#UUZ
D4YK6AA#A2M,D4YK6AA#A2Q,
D4YK6AA#AB0,D4YK6AA#AB1,
D4YK6AA#AB2,D4YK6AA#AB4,
D4YK6AA#AB6,D4YK6AA#AB7,
D4YK6AA#AB8,D4YK6AA#AB9,
D4YK6AA#ABA,D4YK6AA#ABB,
D4YK6AA#ABC,D4YK6AA#ABD,
D4YK6AA#ABE,D4YK6AA#ABF,
D4YK6AA#ABJ,D4YK6AA#ABM,
D4YK6AA#ABT,D4YK6AA#ABU,
D4YK6AA#ABV,D4YK6AA#ABZ,
D4YK6AA#AC0,D4YK6AA#AC3,
D4YK6AA#AC4,D4YK6AA#ACB,
D4YK6AA#AKC,D4YK6AA#AKE,
D4YK6AA#AKL,D4YK6AA#AKS,
D4YK6AA#AR4,D4YK6AA#ARK,
D4YK6AA#B15,D4YK6AA#BCM,
D4YK6AA#BED,D4YK6AA#UUF,
D4YK6AA#UUW,D4YK6AA#UUZ
D54DLAA#A2M,D54DLAA#A2Q
,D54DLAA#AB0,D54DLAA#AB1,
D54DLAA#AB2,D54DLAA#AB4,
D54DLAA#AB6,D54DLAA#AB7,
D54DLAA#AB8,D54DLAA#AB9,
D54DLAA#ABA,D54DLAA#ABB,
D54DLAA#ABC,D54DLAA#ABD,
D54DLAA#ABE,D54DLAA#ABF,
D54DLAA#ABJ,D54DLAA#ABM,
D54DLAA#ABT,D54DLAA#ABU,
D54DLAA#ABV,D54DLAA#ABZ,
D54DLAA#AC0,D54DLAA#AC3,
D54DLAA#AC4,D54DLAA#ACB,

HP 175C Wired Mouse and Keyboard Combo



HP 685 Comfort Dual-Mode Keyboard and Mouse Combo

D54DLAA#AKC,D54DLAA#AKE,
D54DLAA#AKL,D54DLAA#AKS,
D54DLAA#AR4,D54DLAA#ARK,
D54DLAA#B15,D54DLAA#BCM,
D54DLAA#BED,D54DLAA#UUF,
D54DLAA#UUW,D54DLAA#UUZ
8T6L7UT#A2M,8T6L7UT#A2Q,8
T6L7UT#AB6,8T6L7UT#AB7,8T
6L7UT#AB8,8T6L7UT#AB9,8T6
L7UT#ABA,8T6L7UT#ABB,8T6L
7UT#ABD,8T6L7UT#ABE,8T6L7
UT#ABF,8T6L7UT#ABT,8T6L7U
T#ABU,8T6L7UT#ABV,8T6L7UT
#ABZ,8T6L7UT#AC0,8T6L7UT#
AC3,8T6L7UT#ACB,8T6L7UT#A
KC,8T6L7UT#AKE,8T6L7UT#AK
S,8T6L7UT#AR4,8T6L7UT#ARK,
8T6L7UT#B15,8T6L7UT#BCM,8
T6L7UT#BED,8T6L7UT#BH5,8T
6L7UT#UUF,8T6L7UT#UUW,8T6
L7UT#UUZ

HP Multi-Device Dual-Mode Mouse and Keyboard Combo
495C

BE1Q0UT#A2M,BE1Q0UT#A2Q,
BE1Q0UT#AB6,BE1Q0UT#AB7,
BE1Q0UT#AB8,BE1Q0UT#AB9,
BE1Q0UT#ABA,BE1Q0UT#ABB,
BE1Q0UT#ABC,BE1Q0UT#ABD,
BE1Q0UT#ABE,BE1Q0UT#ABF,
BE1Q0UT#ABJ,BE1Q0UT#ABM,
BE1Q0UT#ABT,BE1Q0UT#ABU,
BE1Q0UT#ABV,BE1Q0UT#ABZ,
BE1Q0UT#AC0,BE1Q0UT#AC3,
BE1Q0UT#AC4,BE1Q0UT#ACB,
BE1Q0UT#AKC,BE1Q0UT#AKE,
BE1Q0UT#AKS,BE1Q0UT#AR4,
BE1Q0UT#ARK,BE1Q0UT#B15,
BE1Q0UT#BCM,BE1Q0UT#BED,
BE1Q0UT#UUF,BE1Q0UT#UUW,
BE1Q0UT#UUZ



HP Multi-Device Dual-Mode Mouse and Keyboard Combo
495C White

BE1M6AA#A2M, BE1M6AA#A2Q, BE1M6AA#AB6, BE1M6AA#AB7, BE1M6AA#AB8, BE1M6AA#AB9, BE1M6AA#ABB, BE1M6AA#ABD, BE1M6AA#ABE, BE1M6AA#ABF, BE1M6AA#ABT, BE1M6AA#ABU, BE1M6AA#ABV, BE1M6AA#ABZ, BE1M6AA#AC0, BE1M6AA#AC3, BE1M6AA#ACB, BE1M6AA#AKC, BE1M6AA#AKE, BE1M6AA#AKS, BE1M6AA#AR4, BE1M6AA#ARK, BE1M6AA#B15, BE1M6AA#BCM, BE1M6AA#BED, BE1M6AA#UUG, BE1M6AA#UJW, BE1M6AA#UJZ

HP Multi-Device Dual-Mode Mouse and Keyboard Combo with
Palm Rest 585C

BD5F3AA#A2M, BD5F3AA#A2Q, BD5F3AA#AB6, BD5F3AA#AB7, BD5F3AA#AB8, BD5F3AA#AB9, BD5F3AA#ABB, BD5F3AA#ABD, BD5F3AA#ABE, BD5F3AA#ABF, BD5F3AA#ABJ, BD5F3AA#ABT, BD5F3AA#ABU, BD5F3AA#ABV, BD5F3AA#ABZ, BD5F3AA#AC0, BD5F3AA#AC3, BD5F3AA#ACB, BD5F3AA#AKC, BD5F3AA#AKE, BD5F3AA#AKS, BD5F3AA#AR4, BD5F3AA#ARK, BD5F3AA#B15, BD5F3AA#BCM, BD5F3AA#BED, BD5F3AA#UUF, BD5F3AA#UJW, BD5F3AA#UJZ

HP Wired Desktop 320MK Mouse and Keyboard

9SR36UT#A2M, 9SR36UT#A2Q, 9SR36UT#AB0, 9SR36UT#AB1, 9SR36UT#AB2, 9SR36UT#AB4, 9SR36UT#AB6, 9SR36UT#AB7, 9SR36UT#AB8, 9SR36UT#AB9, 9SR36UT#ABA, 9SR36UT#ABB, 9SR36UT#ABC, 9SR36UT#ABD, 9SR36UT#ABE, 9SR36UT#ABF, 9



Mouse

- HP 105 Black Wired Mouse
- HP 105 Sanitizable Mouse Pad
- HP 125 Wired Mouse
- HP 128 Laser Wired Mouse
- HP 175M Wired Mouse
- HP 205 Sanitizable Desk Mat
- HP 245 Black Bluetooth Mouse
- HP 285 Silent Wireless Mouse
- HP 320M Wired Mouse
- HP 405 Quiet Black Wireless Mouse
- HP 515 Ultra-Fast Rechargeable Wireless Mouse
- HP 685 Comfort Dual-Mode Mouse

Power

- HP 65W Gallium Nitride USB-C LC Power Adapter

SR36UT#ABJ,9SR36UT#ABM,9
SR36UT#ABT,9SR36UT#ABU,9
SR36UT#ABV,9SR36UT#ABZ,9
SR36UT#AC0,9SR36UT#AC3,9
SR36UT#AC4,9SR36UT#ACB,9
SR36UT#ACH,9SR36UT#ACJ,9
SR36UT#AK4,9SR36UT#AKC,9
SR36UT#AKE,9SR36UT#AKL,9S
R36UT#AKS,9SR36UT#AR4,9S
R36UT#ARK,9SR36UT#B15,9S
R36UT#BCM,9SR36UT#BED,9S
R36UT#UUF,9SR36UT#U UW,9S
R36UT#UUZ
822M9UT#ABA,822M9UT#ABB,
822M9UT#UUF
8X595AA
265A9UT
265D9AA
D54CFAA#ABA,D54CFAA#ABB,
D54CFAA#UUF
8X597AA
81S67AA#ABB
6G4E6AA#ABB,6G4E6AA#ABL,
6G4E6AA#UUF
9VA80AA#ABA,9VA80AA#AC3,
9VA80AA#AK4,9VA80AA#UUF
AZ7B3AA#ABA,AZ7B3AA#ABB,
AZ7B3AA#UUF
9C2F7AA#ABA,9C2F7AA#ABB,
9C2F7AA#UUF
8T6M0AA#ABA,8T6M0AA#ABB,
8T6M0AA#UUF,8T6M0UT#ABA,
8T6M0UT#ABB,8T6M0UT#UUF
D36ZXAA#AB0,D36ZXAA#AB1,
D36ZXAA#AB2,D36ZXAA#ABA,
D36ZXAA#ABB,D36ZXAA#ABG,
D36ZXAA#ABJ,D36ZXAA#ABM,
D36ZXAA#ABT,D36ZXAA#ABU,



D36ZXAA#ABY,D36ZXAA#ABZ,
D36ZXAA#AC4,D36ZXAA#ACJ,
D36ZXAA#ACQ,D36ZXAA#AKL,
D36ZXAA#AR6,D36ZXAA#UUF,
D36ZXAA#UUZ



CHANGELOG

Date of change	Version History		Description of change
	V1		

© Copyright 2026 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core, Thunderbolt and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency.

© 2026 Google LLC All rights reserved. Google and the Google Logo are registered trademarks of Google LLC.