

**PowerLite**<sup>®</sup>  
**825**  
Multimedia Projector




Remarkable brightness and audio. Enhanced connectivity and optional wireless performance.

- **Ultra bright, brilliant presentations** — 3000 lumens color light output, 3000 lumens white light output\*
- **Razor-sharp detail** — native XGA resolution
- **Convenient network accessibility** — display images and presentations over the IP network from any networked location
- **Powerful sound and communication features, no added cost** — built-in 10 W speaker, closed captioning decoder
- **Convenient microphone input** — saves both money and the presenter's voice by using the projector's speaker
- **Energy-efficient E-TORL<sup>®</sup> lamp** — up to 6000-hour lamp life\*\*
- **Plug 'n Play, no-hassle setup** — instantly projects images from a PC via the USB connection
- **Message broadcasting** — broadcasts customized images/alerts over the network for announcements or instructions†
- **Easy network monitoring and control** — RJ-45 connectivity and included software
- **Easy picture adjustments and greater positioning flexibility** — automatic keystone correction, 1.6x optical zoom
- **Quick, convenient control** — direct power on/off, AV Mute/Sleep Mode, Instant Off<sup>®</sup>/On
- **Wireless capabilities** — via the optional wireless module and included software or optional Quick Wireless Connection USB key
- **PC-free JPEG slideshows** — via the USB thumb drive port
- **Rich, vibrant color and reliable performance** — 3LCD, 3-chip optical engine
- **Filters to protect your investment** — with easy side access for hassle-free maintenance
- **Added security in any environment** — convenient metal anchor bar
- **Carrying case included** — for easy portability and protection when stored



# PowerLite 825

## Multimedia Projector



### ORDERING INFORMATION

Product Name	Product Code	UPC
PowerLite 825	V11H297020	010343 87306 3
Replacement Lamp	V13H010L50	010343 87322 3
Replacement Air Filter Set	V13H134A22	010343 87323 0

### SPECIFICATIONS

#### Projection System

Epson 3LCD, 3-chip optical engine

#### Projection Method

Front/rear/ceiling mount

#### Driving Method

Epson Poly-silicon TFT Active Matrix

#### Pixel Number

786,432 dots (1024 x 768) x 3

#### White Light Output\*

3000 lumens (ISO 21118 Standard)

#### Color Light Output\*

3000 lumens

#### Aspect Ratio

4:3

#### Native Resolution

1024 x 768 (XGA)

#### Resize

640 x 480 (VGA), 800 x 600 (SVGA),  
1152 x 864 (SXGA), 1280 x 800 (WXGA),  
1440 x 900 (WSXGA), 1400 x 1050 (SXGA+),  
1600 x 1200 (UXGA)

#### Lamp Type

E-TORL 200 W UHE

#### Lamp Life\*\*

Up to 6000 hours (Low Light Output Mode)  
Up to 5000 hours (High Light Output Mode)

#### Throw Ratio Range

1.39 – 2.26 (4:3)

#### Size (projected distance)

30" – 300" (2.7' – 45.5')

#### Keystone Correction Automatic

Vertical: ± 30 degrees

#### Plug 'n Play

Projector is Mac<sup>®</sup> compatible via DVI to VGA  
adapter (not included)

#### Contrast Ratio

Up to 2000:1

#### Color Reproduction

16.77 million colors

### PROJECTION LENS

#### Type

Manual focus/(optical) zoom

#### F-number

1.49 – 1.94

#### Focal Length

18.2 mm – 29.2 mm

#### Zoom Ratio

Optical zoom 1.0 – 1.6

### OTHER

#### Display Performance

NTSC: 480 lines  
PAL: 560 lines  
(Depends on observation of the multi-burst  
pattern)

#### Input Signal

NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/  
SECAM

#### Interfaces

Computer/component video: D-sub 15 pin x 2  
S-video: Mini DIN x 1  
Composite video: RCA x 1  
Audio in x 3 (RCA (L&R) x 1, mini stereo x 2)  
Variable Audio Out: mini stereo x 1  
USB connector: Type B x 1 (USB display and  
mouse/keyboard control), Type A x 1 (for USB  
memory device)  
Serial: RS-232c x 1  
LAN Networking: RJ-45 x 1  
Monitor Out: Mini D-sub 15 pin x1  
Microphone: stereo mini jack x 1  
Wireless LAN port: 802.11 a/b/g (optional —  
module sold separately)

#### Speaker

10 W (mono)

#### Operating Temperature

41 ° to 95 °F (5 ° to 35 °C)

#### Power Supply Voltage

100 – 240 V ±10%, 50/60 Hz

#### Power Consumption

289 W  
Communication on: 7.9 W standby  
Communication off: 1.9 W standby

### Fan Noise

35 dB (High Light Output Mode)  
28 dB (Low Light Output Mode)

### Security

Kensington<sup>®</sup>-style lock provision, security  
anchor bar

### DIMENSIONS (W x D x H)

Including feet: 12.9" x 9.8" x 4.3"  
Excluding feet: 12.9" x 9.8" x 3.7"  
Weight: 7.0 lb/3.1 kg

### REMOTE CONTROL

#### Features

Search, Comp, Video, USB, LAN, power,  
aspect, color mode, volume, e-zoom, A/V mute,  
freeze, menu, page up and down, help, auto,  
mouse functions, user, num, pointer, esc, enter

#### Operating Angle

Right/left: ± 30 degrees  
Upper/lower: ± 30 degrees

#### Operating Distance

19' (6 m)

### SUPPORT — THE EPSON CONNECTION™

#### Pre-sales Support

U.S. and Canada 800-463-7766  
Internet website www.epson.com

#### Service Programs

Two-year projector limited warranty, Epson  
Road Service program, Epson PrivateLine<sup>®</sup>  
dedicated toll-free support and 90-day lamp  
limited warranty

#### What's In The Box

Power cord, computer cable (VGA), USB  
cable, soft carrying case, projector remote  
control, batteries, user manual CD, Projector  
Software CD, Quick Setup Sheet, PrivateLine  
support card, registration card and password  
protection sticker

### ACCESSORY PART NUMBERS

Wireless LAN module (ELPAP03) V12H306P11  
Quick Wireless Connection  
USB Key (ELPAP05) V12H005M05  
Universal projector ceiling mount ELPMBPJF  
Advanced projector ceiling mount ELPMBPRG

High Security projector ceiling mount	ELPMBATA
Adjustable suspended ceiling channel kit	ELPMBP01
False ceiling plate kit	ELPMBP02
Structural Round ceiling plate	ELPMBP03
Adjustable Extension Column (pipe) 8" – 11"	ELPMBBC01
Component to VGA video cable	ELPKC19
S-video cable	ELPSV01
SwissGear <sup>®</sup> backpack	ELPKS63
Wheeled soft case	ELPKS62
Soft shoulder case for projector and laptop	ELPKS61
Molded hardshell case	ELPKS58
50" portable screen	ELPSC06
60" portable pop-up screen	ELPSC07
80" portable pop-up screen	ELPSC08
Duet™ screen	ELPSC80
Epson DC-10s document camera	ELPDC10S
Epson DC-06 document camera (ELPDC06)	V12H321001
Kensington security lock	ELPSL01
Distribution amplifier	ELPDA01
Image presentation camera (ELPDC05)	V12H162020

### PACKAGING SPECIFICATIONS

#### PowerLite 825

Dimensions 16.3" x 14.6" x 7.2" (W x D x H)  
Weight 12.8 lb

#### Replacement Lamp

Dimensions 6.3" x 5.6" x 5.6" (W x D x H)  
Weight 0.7 lb  
Master Carton  
Dimensions 28.4" x 13.1" x 6.8" (W x D x H)  
Weight 8.6 lb  
Units Per Master Carton 10

#### Replacement Air Filter Set

Dimensions 4.9" x 3.9" x 1.2" (W x D x H)  
Weight 0.02 lb  
Master Carton  
Dimensions 12.8" x 5.3" x 4.7" (W x D x H)  
Weight 0.2 lb  
Units Per Master Carton 10

\* Light output varies depending on modes (color and white light output).

\*\* Lamp life results will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time.

† Plug-in available at www.epson.com

**Better Products for a Better Future™**  
www.epson.com/environment

**Epson America, Inc.**  
3840 Kilroy Airport Way, Long Beach, CA 90806

**Epson Canada, Ltd.**  
3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5