# Product data sheet

Specifications

Green Premium™

## APC Surge Module for Analog Phone Line, Replaceable, 1U, use with PRM4 or PRM24 Rackmount Chassis

PTEL2R

**To be discontinued**

⚠ Discontinued on: Feb 14, 2024

⚠ To be end-of-service on: Sep 30, 2024

## Overview

| | |
|---|---|
| Lead time | Usually in Stock |

## Main

| | |
|---|---|
| number of rack unit | 0U |
| Provided equipment | User Manual |

## Physical

| | |
|---|---|
| Color | Black |
| Height | 1.7 in (4.4 cm) |
| Width | 0.7 in (1.9 cm) |
| Depth | 2.7 in (6.9 cm) |
| Net Weight | 0.04 lb(US) (0.02 kg) |
| Mounting preference | No preference |
| Mounting Mode | Not rack-mountable |

## Output

| | |
|---|---|
| Number of power socket outlets | 1 |

## Conformance

| | |
|---|---|
| Product Certifications | cUL Recognized<br>CE |
| Standards | UL 497A |

## Environmental

| | |
|---|---|
| Ambient Air Temperature for Operation | 5…113 °F (-15…45 °C) |
| Relative Humidity | 0…95 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | 5…113 °F (-15…45 °C) |
| Storage Relative Humidity | 0…95 % |
| Storage altitude | 0…10000 ft (0.0000000000…3048.0000000000 m) |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Surge Protection and Filtering

| | |
|---|---|
| **Data Lines Protected<br />(multi-line only)** | Dual analog line (4 wire) |
| **NM Surge Response Time (ns)** | 1 ns common mode |
| **Peak current** | 0.25 kAcommon mode<br />0.2 kAnormal mode |

## Ordering and shipping details

| | |
|---|---|
| **GTIN** | 731304202851 |
| **Country of origin** | PH |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 3.900 in (9.906 cm) |
| **Package 1 Width** | 1.300 in (3.302 cm) |
| **Package 1 Length** | 3.750 in (9.525 cm) |
| **Package 1 Weight** | 1.6 oz (45 g) |
| **SCC14** | 30731304202852 |

## Contractual warranty

| | |
|---|---|
| **Warranty** | Limited Lifetime |

# Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-$CO_2$ products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Take-back    Transparency    RoHS/REACh

## Resource performance

✓  Take-Back Program Available

## Well-being performance

✓  Reach Free Of Svhc

✓  Lead Free

## Certifications & Standards

| | |
|---|---|
| **Reach Regulation** | REACh Declaration |
| **Eu Rohs Directive** | Compliant<br>EU RoHS Declaration |
| **Environmental Disclosure** | Product Environmental Profile |
| **Weee** | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| **Circularity Profile** | End of Life Information |