

Product data sheet

Specifications



APC Smart-UPS Modular Ultra External Battery Frame, Rackmount

SRYLFXBPRM4

Overview

Lead time Usually in Stock

Main

product or component type Battery
Battery type Li-Ion (Lithium-Ion)

Batteries & Runtime

Battery location External frame
Number of battery free slots 4
Number of battery filled slots 0
device mounting Built-in

Physical

Height 5.1 in (130 mm)
Width 17.3 in (440 mm)
Depth 29.1 in (740 mm)
net weight 43.2 lb(US) (19.6 kg)

Environmental

Ambient air temperature for operation 32.0000000000...122.0000000000 °F (0...50 °C)
Operating altitude 0...3000 m
Ambient air temperature for storage -4.0000000000...140.0000000000 °F (-20...60 °C)
Storage altitude 0.0000000000...49212.6 ft (0...15000 m)

Packing Units

Unit Type of Package 1 PCE
Number of Units in Package 1 1
Package 1 Height 11.4 in (29 cm)
Package 1 Width 23.03 in (58.5 cm)
Package 1 Length 39.0 in (99 cm)
Package 1 Weight 59.5 lb(US) (27 kg)

Contractual warranty

Warranty

5 YR

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 **Rohs Exemption Information** [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information
