

## Safe-IT 6-Outlet Clamp Surge Protector, 5-15R Outlets, 3 USB Charging Ports, 8 ft. (2.4 m) Cord, Antimicrobial Protection

MODEL NUMBER: TLP648UCBAM



Safely charges and powers up to 9 devices, including laptops and tablets, during important work-from-anywhere meetings and conferences.

### Features

#### 6-Outlet Surge Protector Clamp Safeguards Your Sensitive Electronics

Ideal for your home or office workstation or travel use, this Safe-IT™ surge protector features a surge protection rating of 1080 joules to defend your sensitive electronic components against even the strongest power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP648UCBAM protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

#### Spring-Loaded Desk Clamp Protects Equipment at Any Workstation

This portable surge protector features a spring-loaded clamp that attaches to any flat, smooth surface up to 2.5 inches (6.4 centimeters) thick, so you can take it with you to the office, dorm, conference room, hotel or anywhere else you need to plug in your electronic devices. The eight-foot power cord with NEMA 5-15P plug pivots 90 degrees to accommodate installation to a horizontal or vertical surface.

#### NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your computer, printer, wireless router, desk lamp or other home/office electronics into six NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise.

#### USB Ports for Charging Mobile Devices

This surge protector with three USB ports is ideal for keeping your devices at full capacity. Two USB-A ports share 2.4A for charging your smartphone, tablet and other USB mobile devices, which are also protected from the damaging effects of surges, spikes and line interference. In addition to the dual USB-A ports, a 3.0A USB-C port charges devices quickly and safely.

#### Filtering EMI/RFI Line Noise Helps Your Equipment Perform Better

This surge protector filters out disruptive electromagnetic and radio frequency interference that can inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

#### Antimicrobial Protection Helps Provide a Safer, Cleaner and Healthier Work Environment

The Safe-IT TLP648UCBAM features antimicrobial protection that helps resist the growth of bacteria,

### Highlights

- 6 NEMA 5-15R outlets distribute AC power to connected home/office equipment
- 1080 joules protect your valuable electronics against dangerous surges and spikes
- 2 USB-A/1 USB-C ports for fast charging of phones, tablets and other mobile devices
- Spring-loaded clamp attaches to flat surface up to 2.5 in. thick for use anywhere
- Antimicrobial protection helps resist the growth of bacteria, viruses, fungi, mold and mildew

### Package Includes

- TLP648UCBAM 6-Outlet Clamp Surge Protector
- Owner's manual



viruses, fungi, mold and mildew.

#### Premium Safety Features Protect Your Valuable Equipment

The on/off switch provides one-touch control over connected equipment. Automatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is required. A green LED confirms your connected equipment is protected.

## Specifications

| OVERVIEW                           |                              |
|------------------------------------|------------------------------|
| UPC Code                           | 037332265807                 |
| Product Type                       | Surge Protector              |
| Charging Form Factor               | Strip                        |
| Device Compatibility               | Phone; Tablet; Amazon Kindle |
| INPUT                              |                              |
| Nominal Input Voltage(s) Supported | 120V AC                      |
| Input Cord Gauge Type              | 14 gauge                     |
| Input Cord Length Details          | 8 ft cord                    |
| Voltage Compatibility (VAC)        | 120                          |
| Input Plug Type                    | NEMA 5-15P                   |
| Input Cord Length (ft.)            | 8                            |
| Right-Angle Plug                   | No                           |
| Input Cord Length (m)              | 2.44                         |
| Integrated Cord Clip               | No                           |
| OUTPUT                             |                              |
| Frequency Compatibility            | 60 Hz                        |
| Output (Watts)                     | 1800                         |
| Output Receptacles                 | (6) 5-15R                    |
| Circuit Breaker (amps)             | 15                           |
| Transformer Accommodation          | (2) Yes                      |
| Right-Angle Outlets                | No                           |
| USER INTERFACE, ALERTS & CONTROLS  |                              |
| Diagnostic LED(s)                  | Yes                          |
| Switches                           | Manual On/Off Switch         |
| CHARGING                           |                              |



|                                   |  |
|-----------------------------------|--|
| Number of Charging Ports          | 3  |
| Total Charging Watts              | 27   |
| Charging Method                   | USB  |
| Charging Port Type                | (2) USB A (FEMALE); (1) USB C (FEMALE)                                       |
| Charging Ports / Amps             | (1) 3A; (2) 2.4A   |
| Overcharge Protection             | No   |
| <b>SURGE / NOISE SUPPRESSION</b>  |  |
| AC Suppression Joule Rating       | 1080   |
| AC Suppression Response Time      | < 1ns  |
| Protection Modes                  | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression |
| UL1449 Let Through Rating         | 500, 500, 600  |
| EMI / RFI Filtering               | Yes  |
| Immunity                          | Conforms to IEE 587/ANSI C62.41  |
| Automatic Shut-Off                | Yes  |
| <b>DATALINE SURGE SUPPRESSION</b> |  |
| Cable (Coax) Protection           | No   |
| Network (Ethernet) Protection     | No   |
| Telephone/DSL Protection          | No   |
| <b>PHYSICAL</b>                   |  |
| Material of Construction          | Plastic  |
| Antimicrobial                     | Yes  |
| Power Cord Color                  | Black  |
| Housing Color                     | Black; Gray  |
| Mounting Holes or Slots           | No   |
| Receptacle Color                  | Black  |
| Shipping Dimensions (hwd / cm)    | 13.79 x 11.99 x 17.09  |
| Shipping Dimensions (hwd / in.)   | 5.43 x 4.72 x 6.73   |
| Shipping Weight (kg)              | 0.88   |
| Shipping Weight (lbs.)            | 1.94   |
| Unit Dimensions (hwd / in.)       | 5.2 x 2.7 x 5.3  |
| Unit Dimensions (hwd / cm)        | 13.21 x 6.86 x 13.46   |
| Unit Weight (lbs.)                | 1.72   |
| Unit Weight (kg)                  | 0.78   |



|  |   |
|--|---|
| Input Cord Color   | Black   |
| <b>FEATURES &amp; SPECIFICATIONS</b>                       |   |
| Rotatable Outlets  | No  |
| GaN Technology   | No  |
| <b>STANDARDS &amp; COMPLIANCE</b>                          |   |
| Canada   | CAN/CSA-C22.2 No. 369.3; 2017 (2ND Ed.); CAN/CSA-C22.2 No. 308-14   |
| Approvals  | RoHS  |
| UL1449 3rd Edition (AC Suppression)                        | UL1449 : 2014 (4th Ed)  |
| UL1363 (Power Tap)   | UL1363: 2014 (4th Ed.0  |
| <b>WARRANTY</b>  |   |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty   |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$50,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>