Data sheet

HP Thunderbolt G4 Dock





The Dock That Does It All

Boost your security, productivity, and connectivity with this Thunderbolt™ 4 dock. It protects your network and devices from the moment you log in, supports multi-OS compatibility¹, and can support up to four 4K displays². Ideal for ITDMs and hybrid workers, this dock also makes home or office device management easy.

The World's Most Secure Dock³

Feel safe and secure from the moment you log in. The HP Thunderbolt G4 Dock with HP Sure Start⁴ prevents hackers from using the dock to attack the network and the attached notebook. Everything connected to this dock is protected and meets full NIST 800-193 requirements.

Expanded Compatability. Easy Connectivity

Focus on your work and not your compatibility¹ with a dock that works seamlessly with most notebooks and operating systems. Whether you use Windows, Mac, or Chrome OS—rigorous testing and certifications ensure that one USB-C® cable⁵ connects your device and peripherals without issue.

The Power To Be Productive

Multitask, create, and collaborate faster with a dock that supports up to four 4K displays through superfast Thunderbolt™ 4 technology² and has double the ethernet speed for faster downloads⁶. This dock also delivers up to 100W/230W of power—enough to charge most notebooks.

Device Management Made Easy

Manage your mixed fleet more efficiently with wired Intel® vPro® support that allows authorized administrators to remotely access and manage vPro® enabled notebooks using wired connections to make updates. IT Managers can also plan dock firmware updates anytime, even after the user disconnects through HP's One Click Installer⁷.

- 1. Backward compatible with USB-C® Alt mode, ports will work at USB-C® Alt mode speeds which are dependent on host specifications.
 2. For USB-C® Alt mode, host PC must support
- 2. For USB-C[®] Alt mode, host PC must support Thunderbolt™ 3 or Thunderbolt™ 4 running a DP 1.4 DSC host.
- 3. Based on HP's internal analysis of docking stations that are Thunderbolt™ 4, have auto validating & self healing firmware, Meet NIST 800-173 requirements, have Port control, the ability to disable the RJ-45 and a BIOS MAPT authorized list.
- 4. HP Sure Start on HP Thunderbolt G4 dock supports firmware integrity verification and recovery it does not include real-time and runtime protections or Microsoft SCCM integration typically found on HP Sure Start in HP notebooks.
- 5. For USB-C® alt mode functionality, host PC must support the DisplayPort™ Alt mode protocol through its USB-C® port. Charging and port replication is supported on notebooks that have implemented USB-C® Alt Mode industry specifications. Power button to turn on or wake the system, Wake-on LAN from warm and cold dock, Wake-on LAN from S4/S5, and MAC Address Pass-Through S0, S3, S4, S5 warm and cold dock features only function on HP or HP supported notebooks. HP does not provide ethernet and audio drivers on Mac PCs
- 6. Requires infrastructue to support 2.5Gb ethernet speeds.
- 7. Windows Management Instrumentation installation required. Requires Windows 10 or higher.

Features

Modern Device Manageability

With Intel® vPro® Active Management Technology, authorized administrators can remotely access notebooks using wired connections, even if turned off, to make updates.

Electronic Asset Management for Your Docks

Empower your IT to manage and track your docks by product name, serial number, and MAC Address from anywhere with the time-saving, easy-to-use Electronic Tag (eTag) asset management tool.¹

Thoughtful Product Packaging

HP is committed to reducing plastic in landfills by using recyclable, fiber-based, and sustainably sourced packaging² that meets recycling requirements, so it can stay out of the landfill³ when customers are finished with it.

One Cable. Two Power Options

With two power options (120W/280W) from one cable, you can power mainstream and high performance PCs alike with just one cable/dock.

We Test So You Can Rest

Rigorous testing⁴ helps assure dock compatibility across HP notebooks and Apple®, Dell, and Lenovo notebooks with USB-C® power ports.

More Ports. More Flexibility

More ports means more capabilities. With a TB4™, HDMI, two USB-C®, two DisplayPorts™, four USB-A 3.2 ports and an RJ45 port, you can connect multiple devices like a keyboard and mouse⁵.

1-year Limited Warranty

Get added peace of mind with a 1-year limitied warranty that includes technical support, diagnostic services, and hardware replacement.



- 1. Windows Management Instrumentation installation required. Requires Windows 10 or higher.
- 2.100% outer box/corrugate cushion packaging made from sustainably sourced certified and recycled fibers. Fiber cushions made from 100% recycled wood fiber and organic material. Any plastic cushions are made from >90% recycled plastic. Excludes plastic bags and plastic foam sheeting.
- 3. Recycling facilities not available in all locations.
- 4. Based on HP internal testing on select non-HP notebook models compatible with USB-C® industry standards. Certain Alt mode features are not supported, such as power button, MAC Address Pass-Through, Wake-on LAN, and OOB Wake on LAN. Visit the HP Support page to determine your HP notebook's wattage and port specifications. Visit the support page of your non-HP notebook to determine its wattage and port specifications.
- 5. Comes with Power Cord.



Specifications







HP Thunderbolt G4 Dock

Part number	HP Thunderbolt 120W G4 Dock - 4J0A2AA HP Thunderbolt 280W G4 Dock w/Combo Cable - 4J0G4AA		
Dimensions (H x W x D)	3.9 x 3.9 x 2.7 in (98 x 98 x 68 mm)		
Weight	120W: 1.68 lbs (760 g) 280W: 1.76 lbs (800 g)		
Security	HP Sure Start ¹		
Operating systems ²	Windows 10, Windows 11; MacOS		
Systems management	Wired vPRO Management		
Top components	LED and power button to power or wake host system ³		
Front components	(1) USB Type-C® 3.2 Gen 2 (10 Gbps) port with data and power out (15W)		
Side components	Right side: (1) Kensington Standard Lock Slot (2) USB 3.2 Gen 1 ports - 1 on each side (5 Gbps each)		
Back components	(2) USB 3.2 Gen 1 (5 Gbps each) Charging ports, power output: 7.5W (1) HDMI 2.0 port (2) DisplayPort 1.4 ports (1) Power barrel port (120W or 280W) (1) Ethernet port: 2 internal NIC cards to support 1 Gb and 2.5 Gb Ethernet⁴ (1) USB-C® 3.2 Gen 1 DisplayPort (1) Thunderbolt™ 4 port		
Network manageability features	vPRO (wired or wireless) ⁴ eTag Disconnected Firmware updates PXE Boot Wake on LAN (from the Off, Sleep or Hibernation States ⁵) MAC address pass-through (from the On, Off, Sleep or Hibernation States ⁶) WLAN-LAN Switching		
Networking	Supports 1 Gb and 2.5G Ethernet		
Power to host (USB-C PD)	Up to 100W via USB-C / 230W to host using 280W power supply via combo cable		
External monitor support	Up to 4		
Power delivery (PD) profiles	PD 3.0: 5V/5A, 9V/5A, 12V/5A, 15V/5A, 20V/5A		
Power to system	Up to 100W/230W via USB-C		
Operating voltage and current	120W: Input 100 to 240V 1.7A 50 to 60Hz. Output is 19.5V at 6.15A 280W: Input 100 to 240V 1.7A 50 to 60Hz. Output is 19.5V at 14.35A		
Temperature (operating)	0° C to 35° C (32° F to 95° F)		
Relative humidity noncondensing (operating)	10 % to 90 %		
Maximum altitude unpressurized (operating)	15 m to 3,048 m (- 50 ft to 10,000 ft)		
Cable length	0.8 M		
Security slot type	Standard Kensington lock slot		
Warranty	1-0-0		
What's in the box	Dock, power supply, power cord, warranty		

- 1. HP Sure Start on HP Thunderbolt G4 dock supports firmware integrity verification and recovery it does not include real-time and runtime protections or Microsoft SCCM integration typically found on HP Sure Start in HP notebooks.
- 2. Operating systems supported: Windows 10 19H1 and up, Win 10 IoT Enterprise LTSC 2021, Windows 11 21H2 and up, Chrome OS v92.0.4515.157 and up, Ubuntu Linux 20.04 LTS with 5.14 kernel, ThinPro OS 8.0 and MacOS Big Sur 11.5.2. Not all features work with all operating systems, ask your sales representative about compatibility with your PC. Linux testing currently underway and expected to be completed after launch.
- $3. \ The \ dock \ power \ button \ is \ not \ functional \ when \ connected \ to \ non-supported \ HP \ notebooks \ or \ non-HP \ notebooks.$
- 4. Requires infrastructure that supports 2.5 GB Ethernet speeds.
- 5. Your computer might support Wake on LAN from the Off, Sleep or Hibernate States, or only when the computer is On or in Sleep.
- 6. Your computer might support MAC address pass-through the On, Off, Sleep or Hibernate States, or only when the computer is On or in Sleep.

Thunderbolt[™] host systems require Thunderbolt[™] software (minimum SW17.x).

 $Ether net\ drivers\ need\ to\ be\ installed\ separately\ on\ non-HP\ Windows\ systems\ for\ headset\ auto\ switching\ functionality.\ Drivers\ available\ on\ HP\ website.$

For MAC PCs, HP does not provide ethernet and audio drivers.

Firmware updates on Window-based host systems only.

Certain features are not functional on non-HP supported nor non-HP notebooks:

- \bullet Power button to turn on or wake the system.
- Wake on LAN from warm and cold dock.
- Wake on LAN from S4/S5.
- MAC Address pass-through S0, S3, S4, S5 warm and cold dock.



Specifications

HP Thunderbolt G4 Dock video resolution specifications


(All Thunderbolt resolutions assume at least dual DP streams. All high resolution mode resolutions assume 4 DP streams)		
Host specification		
DP 1.2 Thunderbolt™ host:		Dual 4K @30Hz or dual 4K UHD @ 60Hz or (1) 6k TBT running multple tiles Triple displays: (3) 2.5k @30Hz
		Quad displays: (3) 2.5k @30Hz + (1) FHD @ 30Hz
	Multi-function mode	Single display: (1) 4K DCI @ 30Hz
		Dual display: (1) 4K DCI @ 30Hz + (1) FHD @ 30Hz
		Triple displays: (3) FHD @30Hz
	High resolution mode	Single display: (1) 4K DCI @60Hz
		Dual displays: (2) 4K DCI @ 30Hz
		Triple displays: (3) 2.5k @30
DP 1.3/1.4 Thunderbolt host		Single display: (1) 4K DCI @60Hz
		Dual displays: (2) 4K UHD @60Hz
		Triple displays: (2) 5K single cable@30Hz + (1) 2.5K@30Hz or (3) 4K DCI @ 30Hz
DP 1.3/1.4 USB-C host:	Multi-function mode	Single display: (1) 5k Ultra Wide @60Hz or (1) 4K DCI @ 60Hz
	-	Dual displays: (2) 4K UHD @60Hz
		Triple displays: (3) 2.5K@ 30Hz
	High resolution mode	Single display: (1) 5k Ultra Wide (5120X1440) @ 60Hz or (1) 8k single cable @ 30Hz
		Dual displays: (2) 4K UHD @60Hz or (2) 4K DCI @ 30Hz
		Triple displays: (3) 4K DCI @ 30Hz
DP 1.4 with DSC Thunderbolt host:		Single display: up to (1) 8K Thunderbolt with multiple tiles @ 60Hz
		Dual displays: (2)4K DCI @ 60Hz or
		Triple displays: (3) 4K@ 60Hz up to (2) 5K single cable @30Hz + (1) 4K UHD @30Hz
		Quad displays: (4) 4K DCI @ 60Hz
DP 1.4 with DSC USB-C host:	Multi-function mode	Single display: (1) 4K DCI @ 60Hz up to (1) 8K single cable @ 30Hz
	-	Dual displays: (2) 4K DCI @ 60 Hz up to (1) 5K dual cable + (1) 4K
		Triple displays: (3) 4K DCI @ 30Hz or (3) 4K UHZ @ 60Hz up to (2) 5K single cable@30Hz + (1) 4K
		UHD @30Hz
	High resolution mode	Single display: upto (1) 8K dual @ 60Hz
		Dual displays: (2) 4K DCI @ 60Hz or up to (2) 5K single cable + (1) 4K UHD@ 60 Hz
		Triple displays: (3) 4K DCI @ 60Hz up to (2) 5K single cable + (1) 4K UHD

Sign up for updates hp.com/go/getupdated





Rate this document



 $Display Port ^{\intercal} is a trademark owned by the Video Electronics Standards Association (VESA ^{@}) in the United States and other countries.$

 ${\it USB\,Type-C@}\ and\ {\it USB-C@}\ are\ registered\ trademarks\ of\ {\it USB\,Implementers\,Forum}.$

 $Microsoft, Encarta, MSN, and\ Windows\ are\ either\ registered\ trademarks\ or\ trademarks\ of\ Microsoft\ Corporation\ in\ the\ United\ States\ and/or\ other\ countries.$

