LX-1350

DATASHEET / BROCHURE





With paper handling up to A3 size, the Epson LX-1350 is the ideal printer to deal with lighter duties on a larger scale.

With paper handling up to A3 size, the Epson LX-1350 is the ideal printer to deal with lighter duties on a larger scale.

This wide-carriage 9-pin printer fits perfectly into a range of environments including data reporting, listings and point-of-sale. It is 337 cps fast, very reliable and cost efficient and has a range of options so you can create the perfect high quality printer to match your changing business requirements.

Flexible working

Handle light duties in style with printing up to A3 size, 5-part forms (1 original + 4 copies) and 337 cps (12cpi) speed.

Get connected

Enjoy no-fuss support for a range of office equipment with auto switching between USB, parallel and serial sources.

Optional extras

Choose from a wide range of options to match changing needs, including a 50 cut-sheet feeder, and roll paper holder.

KEY FEATURES

- Wider format
 Fast, reliable 9-pin printing up to A3
- High productivity
 Print up to 337 characters per second (12 cpi)
- Multi-part flexibility
 Print up to 5-part forms (1 original 4 copies)
- Paper handling
 Top, bottom, front and rear paper paths
- Easy connectivity
 Auto switch between USB, parallel, serial sources



PRODUCT SPECIFICATIONS

TECHNOLOGY

Number of Pins 9 pins Number of columns 136 columns

PRINT

Printing Speed HighSpeed-Draft: 10 cpi: 347 chars/s, 12 cpi: 357 chars/s, Draft: 10 cpi: 260 chars/s, 12 cpi:

312 chars/s, NLQ: 10 cpi: 65 chars/s, 12 cpi: 78 chars/s

Barcodes Coda bar (NW-7), Code 128, Code 39, EAN-13, EAN-8, Industrial 2 of 5, Interleaved 2 of 5,

Matrix 2 of 5, POSTNET, UPC-A, UPC-E

Carbon Copies 4 plus one original Printing Resolution 240 x 144 DPI

CONNECTIVITY

Interfaces USB 2.0 Type A, Bidirectional parallel, RS-232

PAPER / MEDIA HANDLING

Document Feed Single sheet rear, Continuous media rear, Paper output rear

Paper Formats Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels

(single- and multi-layer), Roll Paper, Envelopes

Paper Thickness Continuous 0.065 mm - 0.39 mm

Paper Thickness Multi Part 0.14 mm - 0.39 mm Paper Thickness Single Sheet 0.065 mm - 0.14 mm

GENERAL

Power consumption 33 Watt, 1.1 Watt (standby)

AC 220 V - 240 V Supply Voltage

Product dimensions 546 x 275 x 164 mm (Width x Depth x Height)

Product weight 6.6 ka

Supported Temperature Operation 5° C - 35° C, Storage 5° C - 35° C

Compatible Operating Windows 2000, Windows 7, Windows 8, Windows 98, Windows Server 2008 R2, Windows XP

Systems

Included Software

Mean Time Between Failures 10,000 hours

Print Head Life 400 Million Strokes/Wire Operation: 53 dB (A) Noise Memory 128 kB Included

Ribbon Yield 4000000 characters Black Draft

OTHER FEATURES

ESC/P, IBM PPDS **Emulations**

Input Data Buffer 128 kB

OTHER

Warranty 24 months Carry in

Optional warranty extension available

LOGISTICS INFORMATION

SKU	C11CD24301A0
EAN code	8715946540573
Country of Origin	Indonesia
Layer	3 Units
Layer Block	3 Units

LX-1350

WHAT'S IN THE BOX

- Main unit
- Setup guide
- User manual (CD)
- Driver and utilities (CD)
- Software (CD)
- Warranty document
- Power cable
- Ribbon

SUPPLIES

• SIDM Black Ribbon Cartridge (C13S015642)

OPTIONAL ACCESSORIES

• Epson SIDM Paper Roll Holder for LX-300+II/1170II, FX-890/A, FX-2190, LQ-690/300+II series C12C811141

For more information please contact:

Home users: 0343 90 37766 Business users*: 0871 42 37766 Republic of Ireland: 01 436 7742

Or visit us at https://www.epson.co.uk/contactus * 10p per minute plus network extras.

www.epson.co.uk www.epson.ie

