

QuickSpecs

HP 640 Redundant External Power Supply

Overview

Models

HP 640 Redundant/External Power Supply Shelf

J9805A

Key features

- Provides redundant or external power for HP 2920 Switch Series products
- Uses same modular power supplies as the HP 2920 Switches
- Unit has three power supply slots for maximum configurability options
- In RPS mode can provide protection for 8 switches, with up to 3 internal supply failures
- In EPS mode can provide up to an additional 2,100 watts of shared PoE+ power for up to 3 switches

Product overview

The HP 640 Redundant/External Power Supply Shelf is used with the HP 2920 Switch Series to provide redundant power to back up internal power supplies in the switches, as well as provide external power for applications where additional power is required, as in PoE+ applications. Unit ships ready to be populated with at least one optional power supply and power cable, purchased separately.

Features and benefits

Scalability

- **Three modular power supply slots**
 - **Supports redundant power for up to eight HP 2920 Switches**
protects against internal switch power supply failures
 - **Supports external power allowing up to three HP 2920 48 Port PoE+ Switches to support 1440W of PoE+ power**
allows all 48 ports of a PoE+ switch to offer 30W of PoE+ power at the same time

Resiliency and high availability

- **External redundant power supply**
provides high reliability

Configuration

- **Easy configuration**
provides full management features, available through connected HP 2920 Switches

Product architecture

- **Three power supply module slots**
allows failure of a power supply in one bay to not affect the other two power supplies

Warranty and support

- **Lifetime warranty**
advance hardware replacement for as long as you own the product with next-business-day delivery (available in most countries)†

†HP warranty includes repair or replacement of hardware for as long as you own the product, with next business day advance



QuickSpecs

HP 640 Redundant External Power Supply

Overview

replacement (available in most countries). The disk drive included with HP AllianceOne Advanced Services and Services zL Modules, HP Threat Management Services zL Module, HP AllianceOne Extended zL Module with Riverbed Steelhead, HP MSM765 zL Mobility Controller and HP Survivable Branch Communication zL Module powered by Microsoft® Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at www.hp.com/networking/warranty.

QuickSpecs

HP 640 Redundant External Power Supply

Technical Specifications

HP 640 Redundant/External Power Supply Shelf (J9805A)

Ports	8 redundant power supply ports	
	Restrictions: Has 3 Zones, Zone 1 has 4 RPS/EPS power ports, Zone 2 and Zone 3 have 2 each RPS/EPS power ports	
Physical characteristics	Dimensions	17.4(w) x 12.7(d) x 1.73(h) in (44.2 x 32.26 x 4.4 cm) (1U height)
Environment	Operating temperature	32°F to 131°F (0°C to 55°C)
	Operating relative humidity	15% to 95%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	15% to 95%, noncondensing
	Altitude	up to 9,842 ft (3 km)
	Acoustic	Power: 69.1 dB, Pressure: 53.1 dB Acoustic ratings are absolute max sound levels with 3 modular power supplies and max output power
Electrical characteristics	Description	No power connected directly to the RPS 640. All power inlets come from optional power supplies.
	DC voltage	Depending on which power supplies are installed, can supply 12VDC or 54VDC
	Maximum power rating	3150 W
	PoE power	2100 W
	RPS	12VDC or 54VDC V
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. Unit has 3 empty power supply slots. 1 to 3 optional power supplies and RPS cables for each connected switch required but not included. J9739A can only be used with non-PoE Switches. Must use J9737A to support 1440W PoE+. Bay #1 has 4 Switch connectors and power is split evenly among each enabled connector. Bays 2 and 3 have 2 Switch connectors, and split power evenly among each enabled connector. Switch power port connectors are all enabled by default, and may be disabled through CLI commands on a connected HP 2920 Switch.
Safety	GOST R MEK60950; EN62479:2010; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition; EN 60950-1:2006+A11:2009+A1:2010+A12:2011; IEC 60950-1:2005, Amd 1: 2009	
Emissions	FCC Rules Part 15, Subpart B Class A; VCCI Class A; BSMI CNS 13438; AS/NZS CISPR 22 Class A; KCC Class A; EN 55022:2010; EN 61000-3-3:2008; EN 6100-3-2:2006+A1:2009 + A2:2009; GOST R 51318.22	
Immunity	Generic	EN55024:2010
	ESD	IEC 61000-4-2:2008
	Radiated	IEC 61000-4-3:2010
	EFT/Burst	IEC 61000-4-4:2012



QuickSpecs

HP 640 Redundant External Power Supply

Technical Specifications

Surge	IEC 61000-4-5:2005
Conducted	IEC 61000-4-6:2008
Power frequency magnetic field	IEC 61000-4-8:2009
Voltage dips and interruptions	IEC 61000-4-11:2004

- Notes**

No power cords, or power supplies are included with this product. Order modular power supplies to meet your needs.
- Services**

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.



QuickSpecs

HP 640 Redundant External Power Supply

Accessories

HP 640 Redundant/External Power Supply Shelf accessories

Cables

NEW HP 640 External/Redundant Power Supply 1m Cable	J9806A
--	--------

Power Supply

NEW HP X332 1050W 110-240VAC to 54VDC Power Supply	J9737A
---	--------

NEW HP X332 575W 100-240VAC to 54VDC Modular Power Supply	J9738A
--	--------

NEW HP X331 165W 100-240VAC to 12VDC Modular Power Supply	J9739A
--	--------

To learn more, visit www.hp.com/networking

© Copyright 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.