

Data sheet

HP 65W USB-C Laptop Charger



Charge your World

Charge most USB-C® devices with just one compact charger. The HP 65W USB-C Laptop Charger provides up to 65W of power, enough for almost any USB-C® device. Designed with travel and hybrid work in mind, this lightweight charger is the essential universal charger.

Charges Big or Small

Now with smart power that adapts to your charging needs, this laptop charger delivers 15W, 27W, 60W, or 65W of power¹. This will be the only charger you'll want in your bag.

A Universal Solution

Enjoy the flexibility to charge most USB-C® devices¹, whether it's your laptop, tablet, or phone.

Travel-Size

This compact, lightweight charger comfortably fits in your bag without weighing it down. The durable cable and built-in cable management keeps you organized when traveling or commuting.

1. Compatible with most devices that charge using USB-C®. Non-HP listed compatible products tested internally by HP.

Specifications



HP 65W USB-C Laptop Charger

Part number	671R3AA
Dimensions (HxWxD)	3.82 x 2.11 x 0.83 in (97 x 53.5 x 21 mm)
Weight	7.4 oz (210 g)
Cable length	70.9 in (180 cm)
Input	Input efficiency 81.5% min at 115 Vac/ 230Vac @ 5V/3A 86.7% min at 115 Vac/ 230Vac @ 9V/3A 88% min at 115 Vac/ 230Vac @ 12V/5A 89% min at 115 Vac/ 230Vac @ 20V/3.25A 89% min at 115 Vac/ 230Vac @ 15V/4.33A Input frequency range 47 ~ 63 Hz Input AC current 1.6 A at 90 VAC and maximum load
Output	Output power 65W DC output 5V/9V/12V/15V/20V Hold-up time 5ms at 115 Vac input Output current limit 8.0A Maximum Over-Voltage Protection 5V: 7.25V@OVP 9V: 13.05V@OVP 12V: 15.8V@OVP 15V: 21.75V@OVP 20V: 29V@OVP
Connector	USB TYPE C
Operating temperature	32°F to 95°F (0° to 35°C)
Non-operating (storage) temperature	-4°F to 185°F (-20° to 85°C)
Altitude	0 to 16,400 ft (0 to 5000m)
Humidity	20% to 95%
Storage humidity	10% to 95%
EMI and safety certifications	- CE Mark - full compliance with LVD and EMC directives - Worldwide safety standards -IEC60950, EN60950, UL60950, UL62368, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. - MTBF - over 200,000 hours at 25°C ambient condition.
Pallet configuration	Cartons per layer 20 Fully loaded pallet dimension 39.37 x 47.24 x 44.25 in (1000 x 1200 x 1124 mm) Pallet layer 4 Products per pallet 480 Products per layer 120

Note: Pallet information not applicable to #ABB/ABU/ABY/UUZ/ACQ/ABT/ABZ/ACB



Additional information

HP 65W USB-C Laptop Charger

HP product number and UPC	671R3AA#ABA	196548312566
	671R3AA#ABM	196548308538
	671R3AA#AC4	196548308606
	671R3AA#AC8	196548308620
	671R3AA#AKH	196548308651
	671R3AA#ABG	196548308521
	671R3AA#AB2	196548308507
	671R3AA#ABJ	196548429363
	671R3AA#AB1	196548308491
	671R3AA#UUF	196548308682
	671R3AA#AB0	196548308484
	671R3AA#AKL	196548308668
	671R3AA#AR6	196548308675
	671R3AA#ACJ	196548308637
	671R3AA#ABB	196548308514
	671R3AA#ABU	196548308569
	671R3AA#ABY	196548308576
	671R3AA#UUZ	196548308699
	671R3AA#ACQ	196548308644
	671R3AA#ABT	196548308552
	671R3AA#ABZ	196548308590
	671R3AA#ACB	196548424450
	671R3UT#ABA	196548308729
	671R3ET#ABB	196548308705
	671R3ET#ABU	196548308712
	671R3A6#ABB	196548308460
	671R3A6#ABU	196548308477
JAN number	671R3AA#ABJ	4573595775654
Tariff number	8504407007	
Country of origin	China	

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

©Copyright 2022 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum.

