

USB DVI over Cat 5e / Cat 6 KVM Console Extender w/ 1920x1200 Uncompressed Video - 330ft (100m)

StarTech ID: SV565UTPDUV



The SV565UTPDUV USB DVI KVM Extender lets you control a PC from up to 330ft (100m) away over a single Cat 5e or Cat 6 cable connection, with uncompressed 1920x1200 DVI video and access to up to 3 connected USB devices.

A flexible solution for powering large high-definition displays remotely, this DVI USB extender supports uncompressed 1920x1200 video resolution at maximum distance, with 24-bit color depth.

This versatile KVM console extender can be connected to a single system, or cascaded to an existing KVM switch for remote operation of multiple systems, and features 3 USB 2.0 ports on the remote end, allowing you to connect a keyboard, mouse, printer or other peripherals. Since the extender uses Cat 5e (or better) network cable, you have the option to use existing infrastructure wiring, which helps avoid the hassle and expense of running bulky video cables.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### **Applications**

- Operate one or more servers from a remote location within the same building or campus
- Use for remote control of secured, physically inaccessible servers
- Can act as a thin client for power users controlling powerful rack mounted servers as their desktop machines
- Control and monitor a remote server from a harsh environment where the PC would not function properly due to heat/dust/etc. (factory, warehouse, mining, etc.)
- Ideal for controlling a PC in an area where fan or hard drive noise is unacceptable such as a television broadcast studio





#### **Features**

- Uncompressed 1920x1200 HD video extension
- Extend up to 330 ft (100m) over a single Cat5e / Cat6 cable
- OS independent no software or drivers required
- 3 USB 2.0 ports with transfer rates up to 30Mbps
- Supports connection to a single computer or cascading to an existing KVM switch
- Supports most combo keyboard and mouse sets (including Wireless)



## **Technical Specifications**

Warranty 2 Years
Color Black
Enclosure Type Aluminum
Product Height 1.2 in [30 mm]
Product Length 6.9 in [175 mm]
Product Weight 30.3 oz [857 g]
Product Width 4.6 in [118 mm]

Audio No
Daisy-Chain Yes
KVM Ports 1
Multi-Monitor No
PC Interface USB
PC Video Type DVI
Rack-Mountable No

Color Depth 24-bit, 16.7M colors (Truecolor)

IP Control No

Max Transfer Distance 100 m (328 ft)
Maximum Data Transfer Rate 30 Mbps (USB)

Maximum Digital Resolutions Full Uncompressed 1920x1200

Console Interface(s) 1 - DVI-D (25 pin) Female

Console Interface(s) 1 - RJ-45 Female

Console Interface(s) 3 - USB A (4 pin) Female Host Connectors 1 - DVI-D (25 pin) Female

Host Connectors 1 - RJ-45 Female

Host Connectors 1 - USB B (4 pin) Female

OS Compatibility OS independent; No software or drivers required

**Note** Product measurements indicate a single unit only (either Host or Remote)

LED Indicators 1 - Power
LED Indicators 1 - Link
LED Indicators 1 - USB
LED Indicators 1 - Video
Center Tip Polarity Positive
Input Current 0.6 A





# Hard-to-find made easy®

Input Voltage 100 ~ 240 AC

Output Current 3 A
Output Voltage 5 DC
Plug Type C

Power Source 2 AC Adapters Included

Humidity 20~80% RH (Non-Condensing)
Operating Temperature 0°C to 40°C (32°F to 104°F)
Storage Temperature -20°C to 70°C (-4°F to 158°F)

Shipping (Package) Weight 5.5 lb [2.5 kg]

Included in Package 1 - Local Extender Unit
Included in Package 1 - Remote Extender Unit
Included in Package 2 - Mounting Brackets

Included in Package 1 - DVI Cable Included in Package 1 - USB Cable

Included in Package 2 - Universal Power Adapters

Included in Package 6 - Power Cords (2 sets, NA/EU/UK)

Included in Package 1 - Quick Start Guide

# Certifications, Reports and Compatibility







