

2 Port Dual DVI USB KVM Switch with Audio & USB 2.0 Hub

StarTech ID: SV231DD2DUA



The SV231DD2DUA 2-port Dual DVI USB KVM Switch allows two PCs, each with dual DVI video outputs, to share two monitors, one microphone and set of speakers, one keyboard and one mouse as well as two other USB peripherals.

An ideal solution for graphic designers, CAD/CAM designers or educational and financial institutions, the dual view KVM Switch allows you to instantly switch back and forth between dual DVI display PCs at the touch of a button, while maintaining professional level video quality on both monitors. The dual DVI switch also features an integrated USB hub port that allows USB 2.0 peripherals such as thumb drives, external hard drives or web cams to be shared between attached systems - eliminating duplicate peripheral costs.

Please Note: This KVM switch supports DVI-D (digital) signaling only and it is recommended wherever possible to use DVI-D cabling across all PC to KVM and KVM to Console connections to ensure proper function. Please contact technical support if you require assistance identifying the proper cables.

Backed by a StarTech.com 3 year warranty and free lifetime technical support.



Applications

- Dual system control for single user workstations with dual head video cards, increasing user productivity in the office
- Control two dual display multimedia computers with a single set of console peripherals (Keyboard, Mouse, and two Monitors)
- Ideal for financial/banking industries, graphic designers, multi-media applications and industries using CAD/CAM applications, and multiple screens
- Integrated USB 2.0 hub and Mic/Audio ports allow the user to have full multimedia control of two computers and share USB peripherals

Features

- Front panel push-buttons and Hot-key functions for easy switching
- Supports resolutions up to 1920x1200 (DVI-Digital)
- USB 2.0 hub for peripheral sharing (Thumb drives, external hard drives, web cams, etc.)
- Audible tone confirms port switching
- Combined or independent switching of audio ports
- EDID retention eliminates hassle when switching between computers as the KVM "remembers" monitor settings
- Supports all USB-capable operating systems (Windows 98e/SE/ME/2000/XP/Vista/7, Linux, Mac OS, etc.)
- Rugged, all-metal chassis for use in harsh environments
- TMDS compliant to support DDC2B emulation and HDCP for digital contents protection
- Status LED display for easy port status monitoring





Warranty 3 Years

Technical Specifications

Audio Yes Cables No

Included

Daisy-Chain No KVM Ports 2

Multi- Yes

Monitor

PC Interface USB

PC Video DVI

Type

Rack- No

Mountable

DVI Support Yes - Single Link

IP Control No

Maximum 1920 x 1200

Digital

Resolutions

Maximum 1

Number of

Users

Port Push Button and Hotkeys

Selection Support

Console

2 - 3.5 mm Mini-Jack (3 Position) Female

Interface(s)

Console 2 - DVI-I (29 pin) Female

Interface(s)

Console 4 - USB A (4 pin) Female

Interface(s)

Host 2 - USB B (4 pin) Female

Connectors

Host

4 - 3.5 mm Mini-Jack (3 Position) Female

Connectors

Host 4 - DVI-I (29 pin) Female

Connectors



Hard-to-find made easy®

Spec Sheet

OS OS independent; No software or drivers required

Compatibility

Note This KVM switch supports DVI-D (digital) signaling only and it is recommended wherever possible

to use DVI-D cabling across all PC to KVM and KVM to Console connections to ensure proper function. Please contact technical support if you require assistance identifying the proper cables.

Color Black Steel

Enclosure

Type

Product 3.9 in [100 mm]

Depth

2.2 in [57 mm] Product

Height

Product 6.4 in [163 mm]

Length

Product 26.5 oz [750 g]

Weight

Product 6.3 in [160 mm]

Width

LED 1 - Green - Power

Indicators

LED 4 - Green - Host Online, Red - Host Selected

Indicators

Center Tip Positive

Polarity

Input A8.0

Current

Input 110 ~ 240 AC

Voltage

Output 1.5A

Current

12 DC Output

Voltage

Plug Type Μ

AC Adapter Included

Power Source

Humidity 90% RH

Operating 0°C to 40°C (32°F to 104°F)

Temperature

Storage -20°C to 60°C (-4°F to 140°F)

Temperature





Hard-to-find made easy®

Shipping

١,

2.6 lb [1.2 kg]

(Package) Weight

Included in

1 - Two Port Dual DVI KVM

Package

Included in 1 - Rubber Feet

Package

Included in

1 - Universal Power Adapter (NA/EU/UK) or AU in Australia

Package

Included in 1 - Manual

Package

Certifications, Reports and Compatibility





