

## 10 ft Mini DisplayPort™ to DVI Adapter Converter Cable – Mini DP to DVI 1920x1200 - Black

StarTech ID: *MDP2DVIMM10B*



The MDP2DVIMM10B Mini DisplayPort® to DVI Adapter Cable lets you directly connect your Mini DP video source (desktop PC, laptop, Ultrabook, etc.) to a DVI monitor or projector, eliminating the expense of having to upgrade to a Mini DisplayPort-capable monitor.

The adapter cable is 10 feet (3 m) in length, and features male-to-male connectors, allowing you to connect your Mini DisplayPort source directly to a DVI display with no additional cabling required.

Compatible with Intel® Thunderbolt™, when connected directly to a supporting DisplayPort over Thunderbolt I/O port, the adapter supports resolutions up to 1920x1200 (WUXGA).

MDP2DVIMM10B is a passive adapter that requires a dual-mode DisplayPort port (DisplayPort++), meaning that DVI and HDMI signals can also be passed through the port.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Applications

- Connect your existing DVI display device (monitor, projector) to a Mini DisplayPort output device
- Ideal for using your DVI monitor as a secondary display

## Features

- 1x Male Mini DisplayPort connector, 1x Male DVI connector
- Supports resolutions up to 1920x1200 (WUXGA) and HDTV resolutions up to 1080p
- Compatible with Intel® Thunderbolt™ devices that are capable of outputting a DisplayPort signal

## Technical Specifications

Warranty	2 Years
Cable Length	10 ft [3 m]
Color	Black
Product Height	0.6 in [15 mm]
Product Length	120.1 in [3050 mm]
Product Weight	5.4 oz [153 g]
Product Width	1.5 in [38 mm]
Adapter Style	Cable Adapter
Audio	No
Chipset ID	NXP 3361
Converter Type	Passive
Output Signal	DVI-D (DVI Digital)
Maximum Cable Length	10 ft [3 m]
Maximum Digital Resolutions	1920x1200 / 1080p
Wide Screen Supported	Yes
Connector A	1 - Mini-DisplayPort (20 pin) Male
Connector B	1 - DVI-D (25 pin) Male
System and Cable Requirements	DP++ (DisplayPort++) port required from video card or video source for DVI and HDMI® signal pass-through
Humidity	40%-85%RH
Operating Temperature	0°C to 60°C (32°F to 140°F)
Storage Temperature	0°C to 70°C (32°F to 158°F)
Shipping (Package) Weight	5.7 oz [162 g]
Included in Package	1 - Mini DisplayPort® to DVI Adapter

Certifications, Reports and Compatibility

