

USB to RS232 DB9/DB25 Serial Adapter Cable - M/M

StarTech ID: ICUSB232DB25



The ICUSB232DB25 USB to RS232 DB9/DB25 Serial Adapter Cable (M/M) lets you connect 9-pin (DB9) or 25-pin (DB25) RS232 serial devices to your laptop or desktop computer through a USB port, as though the computer offered an onboard serial port. The integrated 3-foot (0.9 meter) cable allows it to be connected directly from the serial device to the computer without requiring additional cables.

A cost-effective solution that bridges the compatibility gap between modern computers and legacy serial peripherals, this high quality USB/RS232 Serial Adapter cable ships with a DB-9 to DB-25 adapter for connection to varied serial equipment.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Ideal for connecting serial devices to laptops or tablet PCs through the USB port
- Connect to and monitor/control industrial sensors
- Connect bar code scanners and other serial devices to a USB port
- Connect a serial modem, digital camera, or PDA with serial sync to your PC's USB port
- Connect to automotive OBD/OBDII sensor adapters that use serial connectivity

Features

- USB powered; No external power adapters needed
- Supports serial transfer speeds up to 250Kbps
- Includes a DB9 to DB25 pin adapter for 25-pin RS232 serial communication
- Supports USB transfer speeds up to 12Mbps
- Plug-and-Play and Hot Swap Support
- Windows certified (WHQL) drivers
- 3ft cable length
- Supports remote wake-up from Modem input signals and USB power management
- Compliant with USB Rev. 2.0 Full-Speed specification
- Electronics Industries Association (EIA) standard RS-232-C compliant
- USB to Straight-Through RS232 Serial Adapter

Technical Specifications

Warranty	2 Years
Bus Type	USB 2.0
Chipset ID	Prolific - PL-2303
Interface	Serial
Port Style	Cable Adapter
Ports	1
Data Bits	4, 5, 6, 7, 8
FIFO	512 Bytes
Flow Control	None, Xon/ Xoff, Hardware
Max Baud Rate	230.4 Kbps
Parity	None, Even, Odd, Mark, Space
Serial Protocol	RS-232
Stop Bits	1, 1.5, 2
Connector Type(s)	1 - USB A (4 pin) Male
External Ports	1 - DB-25 (25 pin; D-Sub) Male
External Ports	1 - DB-9 (9 pin; D-Sub) Male
Microsoft WHQL Certified	Yes
OS Compatibility	Windows® 8 / 8.1 (32/64bit), 7 (32/64), Vista (32/64), XP (32/64), 2000, ME, 98SE, XP Embedded, POS Ready 2009, Embedded System 2009, CE 4.2/5.2, Windows Mobile 5/6, PocketPC 2003 / 2000 Windows Server® 2012, 2008 R2, 2003 Mac OS® 10.x (Tested up to 10.10) Linux 2.4.x - 3.9.x
Cable Length	3 ft [0.9 m]
Color	Gray
Enclosure Type	Plastic
Product	3 ft [0.9 m]

Length	
Product Weight	2.5 oz [70 g]
Humidity	5~85% RH
Operating Temperature	0°C to 70°C (32°F to 158°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Shipping (Package) Weight	3.2 oz [90 g]
Included in Package	1 - 3ft USB to RS232 Cable
Included in Package	1 - DB9 to DB25 Serial Adapter
Included in Package	1 - Driver CD
Included in Package	1 - Manual

Certifications, Reports and Compatibility

