

Spec Sheet

USB 3.0 to Gigabit Ethernet NIC Network Adapter – 10/100/1000 Mbps

StarTech ID: USB31000NDS



The USB31000NDS USB 3.0 to Gigabit Ethernet Network Adapter adds a single RJ45 Ethernet port to a USBenabled computer system, with support for Gigabit network connections at full bandwidth when used with a USB 3.0 host connection, unlike USB 2.0 adapters.

This compact USB 3.0 NIC works with 10/100/1000 Mbps networks and offers backward compatibility with USB 2.0/1.x computer systems (speed limited by USB bus), making it an ideal portable replacement LAN adapter or laptop accessory. Support for features such as Jumbo Frames, VLAN tagging and Wake on LAN (WOL), provides versatile Gigabit network performance for home or business use.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Add Gigabit Ethernet capabilities to a desktop or laptop
- Replace a failed integrated network adapter with an external, USB Ethernet solution to avoid opening the computer case

Features

- Full Gigabit bandwidth support over USB 3.0
- IEEE 802.3, 802.3u and 802.3ab (10BASE-T, 100BASE-TX, and 1000BASE-T) compatible
- USB-Powered
- Crossover Detection & Auto-Correction (Auto MDIX)
- IEEE 802.1Q VLAN Tagging support
- Jumbo Frame support
- Supports Checksum Offload (IPv4, IPv6, TCP, UDP) and Large Send Offload
- Activity and Link LED indicators
- Compact, lightweight design



Technical Specifications

Hard-to-find made easy*

Spec Sheet

Warranty	2 Years
Bus Type	USB 3.0
Chipset ID	ASIX - AX88179
Industry Standards	IEEE802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3az
Interface	RJ45 (Gigabit Ethernet)
Ports	1
Connector Type(s)	1 - RJ-45 Female
Connector Type(s)	1 - USB 3.0 A (9 pin; SuperSpeed) Male
Auto MDIX	Yes
Compatible Networks	10/100/1000 Mbps
Full Duplex Support	Yes
Max Distance	100 m / 330 ft
Maximum Data Transfer Rate	1Gbps (Gigabit Ethernet)
Type and Rate	USB 3.0 - 5 Gbit/s
OS Compatibility	Windows® 8.1 (32/64bit), 8 (32/64), 7 (32/64), Vista(32/64), XP(32/64) Windows® Server 2012, 2008 R2, 2003(32/64) Mac OS® 10.6 - 10.9 Linux Kernel 2.6.14 - 3.5.0
Color	Black
Enclosure Type	Plastic
Product Height	1 in [26 mm]
Product Height Product Length	
•	1 in [26 mm]
Product Length	1 in [26 mm] 2.7 in [68 mm]
Product Length Product Weight	1 in [26 mm] 2.7 in [68 mm] 0.7 oz [21 g]
Product Length Product Weight Product Width	1 in [26 mm] 2.7 in [68 mm] 0.7 oz [21 g] 0.9 in [22.6 mm]
Product Length Product Weight Product Width LED Indicators	1 in [26 mm] 2.7 in [68 mm] 0.7 oz [21 g] 0.9 in [22.6 mm] 1 - Activity (Yellow)
Product Length Product Weight Product Width LED Indicators LED Indicators	1 in [26 mm] 2.7 in [68 mm] 0.7 oz [21 g] 0.9 in [22.6 mm] 1 - Activity (Yellow) 1 - Link (Green)
Product Length Product Weight Product Width LED Indicators LED Indicators Power Adapter Included	1 in [26 mm] 2.7 in [68 mm] 0.7 oz [21 g] 0.9 in [22.6 mm] 1 - Activity (Yellow) 1 - Link (Green) USB-Powered
Product Length Product Weight Product Width LED Indicators LED Indicators Power Adapter Included Humidity	1 in [26 mm] 2.7 in [68 mm] 0.7 oz [21 g] 0.9 in [22.6 mm] 1 - Activity (Yellow) 1 - Link (Green) USB-Powered 10~90% RH
Product Length Product Weight Product Width LED Indicators LED Indicators Power Adapter Included Humidity Operating Temperature Storage Temperature	1 in [26 mm] 2.7 in [68 mm] 0.7 oz [21 g] 0.9 in [22.6 mm] 1 - Activity (Yellow) 1 - Link (Green) USB-Powered 10~90% RH 0°C to 50°C (32°F to 122°F)
Product Length Product Weight Product Width LED Indicators LED Indicators Power Adapter Included Humidity Operating Temperature Storage Temperature	1 in [26 mm] 2.7 in [68 mm] 0.7 oz [21 g] 0.9 in [22.6 mm] 1 - Activity (Yellow) 1 - Link (Green) USB-Powered 10~90% RH 0°C to 50°C (32°F to 122°F) 0°C to 70°C (32°F to 158°F)
Product Length Product Weight Product Width LED Indicators LED Indicators Power Adapter Included Humidity Operating Temperature Storage Temperature System and Cable Requirement	1 in [26 mm] 2.7 in [68 mm] 0.7 oz [21 g] 0.9 in [22.6 mm] 1 - Activity (Yellow) 1 - Link (Green) USB-Powered 10~90% RH 0°C to 50°C (32°F to 122°F) 0°C to 70°C (32°F to 158°F) ts Host computer system with an available USB 3.0/2.0 port
Product Length Product Weight Product Width LED Indicators LED Indicators Power Adapter Included Humidity Operating Temperature Storage Temperature System and Cable Requirement Shipping (Package) Weight	1 in [26 mm] 2.7 in [68 mm] 0.7 oz [21 g] 0.9 in [22.6 mm] 1 - Activity (Yellow) 1 - Link (Green) USB-Powered 10~90% RH 0°C to 50°C (32°F to 122°F) 0°C to 70°C (32°F to 158°F) ts Host computer system with an available USB 3.0/2.0 port 3.5 oz [100 g]



Certifications, Reports and Compatibility















Spec Sheet