



Easy Cleanability and Superior Acoustics

Cleaning and Maintaining your Snowsound Acoustic Panels

SOUNDFIX™ panels are easy to clean and do not accumulate dust, making them ideal for environments concerned about cleanliness or containing the spread of germs. The manufacturing process leaves no airspace or a cavity between the outer fabric and sound-absorbing inner material, and the Trevira® CS outer fabric features a unique weave that prevents dust from penetrating the panel. The result is a cleaner panel that does not degrade in performance over time because of the accumulation of dust or pollen.

Easy to Clean

SOUNDFIX panels can be vacuumed with a clean upholstery brush or wiped down with a cloth when stained. If the panel fabric is stained, a stain remover applied locally is adequate for small stains. A Tide® stick or similar stain removing product can also be used. Where the staining is larger and/or severe, panel fabric can be cleaned with both water-based and solvent-based cleaning systems.

For heightened health and safety against viruses and bacteria, the SOUNDFIX panels can be sanitized using a 75% ethyl alcohol solution sprayed directly onto the surface of the panel to be successfully treated. (This satisfies the Center for Disease Control and Prevention (CDC) recommendation to use a sanitizer with at least 60% alcohol content). Do not fully saturate the material.

- Spray bottles achieve very good cleaning results.
- Brush or suction machines are not recommended (shampoo residues may have a negative effect on the burn behavior of the material).
- Ensure the cover fabric is adequately dried.
- The nap and pile can be restored using steamer.

Stain Key

For stain removal, a Tide stick can also be used on the panels. Stains are best removed while they are still fresh and have not penetrated the interior of the fibers. Dried-in marks must be treated with stain remover.

The following general points apply:

- Never rub the fabric too vigorously or aggressively.
- Rub gently with a clean absorbent cloth from the outside of the center of the stain.
- For small marks, gentle treatment with a damp brush or sponge is sufficient.
- When using a damp sponge or brush the material should only be moistened, never fully wet.
- When using stain removers, the manufacturer's instructions should be noted.
- Avoid applying heat when drying; a hair dryer on a low setting can be used, but maintain a 4-5 inch distance from the surface of the fabric.

For any further questions regarding care and maintenance of SOUNDFIX panels, please feel free to contact our customer service at 855-828-5679 M-Th, 8am - 5pm, and Fri, 8am-12pm (Pacific Time), or email soundfix@atlantic-inc.com