

Key Features

- | Better Conference Calls
- | Wide-Angle Advanced Optic Lens
- | Clear Audio and Communication
- | Software Versatility
- | Expandable Bluetooth® Connectivity



Product Description

The ViewSonic® Tribe VB-CAM-201 is a 4K video conferencing camera perfect for medium to large-sized conference rooms and boardrooms. With 4K Ultra HD resolution and a 120° super wide-angle lens, the Tribe captures everyone in a meeting room with stunning clarity. Voice-tracking technology, combined with 5x digital zoom, ensures that the speaker is always on camera. In addition, an 8W speaker and a four-microphone array with noise and echo cancellation technologies ensure that everyone on your call feels as if they are in the room with you. Plug-and-play connectivity with ViewSonic ViewBoard® interactive displays and commercial displays make setup quick and easy.



Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Sensor:	1/2.5 inch, CMOS, 8.51M pixel
Lens:	5x digital zoom, pan/tilt ±15°
Digital Noise Reduction:	2D, 3D digital noise reduction
White Balance:	Auotmatic, Indoor, Outdoor, One Push, Manual
Field of View (FOV):	120°(DFOV), 110°(HFOV)
Backlight Compensation:	Yes
Resolution:	3840 x 2160
PTZ:	MPT + EPTZ

Connector:

HDMI 2.0 Out(1), USB 2.0 Type A(1), USB 3.0 Type C(1), Ethernet LAN (RJ45)(1)

Video Signal:

Video Support:	4K@30fps, 1080P@60fps, 1080P@30fps, 720P@60fps, 720P@30fps, etc.
Compression:	H.264 / MJPEG /YUY2 /NV12

Audio:

Internal Speakers:	8W (x1)
Sensitivity:	96dB at 0.5m / 1.6 ft
Audio features:	32K sampling rate, high-definition broadband audio, full-duplex voice / Auto Echo cancellation / Auto Noise suppression / Auto Gain control
USB protocol:	Support UAC 2.0

Microphone:

Microphone:	Beamforming microphone
Microphone array:	4 microphones
Distance:	6m / 20 ft

Compatibility:

Minimum Hardware Specs:	CPU (Recommended) 2.4GHz Intel® Core 2™ Duo processor or higher, RAM (Recommnedn) 2GB of Memory or higher, USB 2.0 Type-A required for 1080p video output, USB Type-C required for 4K UHD video output
-------------------------	--

Power:

Voltage:	DC 12V/1.5A Adapter
Consumption (typical):	18W

Specifications:

Bluetooth:	Bluetooth 5.0
------------	---------------

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	20-90%

Dimensions (imperial) (WxHxD):

Packaging (in.):	26.54 x 18.98 x 18.66
Physical (in.):	23.62 x 5.31 x 4.53

Dimensions (metric) (WxHxD):

Packaging (mm):	674 x 482 x 474
Physical (mm):	600 x 135 x 115

Weight (imperial):

Net (lbs):	4.86
Gross (lbs):	28.66

Weight (metric):

Gross (kg):	40.57
-------------	-------

General:

Warranty: One-year limited warranty on parts and labor

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Regulations: FCC, FCC ID, CE, IC ID, LVD

PACKAGE CONTENTS: VB-CAM-201, Documentation, Remote Control, Power Adapter, Bracket, USB Type-C Cable, Bracket Screw x 6, Wall Anchor x 6

UPC: 766907010909

Accessories:

IFP5550-E1, IFP5550-E2, IFP5550-E4, IFP6532, IFP6550-E1, IFP6550-E2, IFP6550-E4, IFP6570, IFP7532, IFP7550-E1, IFP7550-E4, IFP8632, IFP8650-E1, IFP8650-E2, IFP8650-E4, IFP8662, IFP8670, IFP9850-4 , IFP9850-E1, IFP9850-E2, IFP9850-E4, NMP760, VPC25-W33-P1, VPC25-W53-O1, VPC25-W53-O1-1B, VPC25-W53-O2, VPC25-W53-O2-1B, VPC25-W53-P1, VPC25-W53-P2, VPC27-W55-O2, VPC27-W55-O2-1B, VPC27-W55-P2

Awards:

