




HP Prime Gloss Air GR

Intermediate polymeric adhesive vinyl with gray removable adhesive



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



See outstanding image quality and great hiding power

See outstanding image quality and great hiding power

This gloss-finish, intermediate polymeric adhesive vinyl offers outstanding image quality and “pop”. The gray removable adhesive is opaque for maximum coverage. This vinyl installs easily with a low-profile air release liner and provides durable print performance with over 10 years laminated display permanence.¹

REACH compliant²

Offer a vinyl that complies with high health standards. HP Prime Gloss Air GR is REACH compliant²—a regulation of the European Union adopted to improve the protection of human health and the environment from risks that can be posed by chemicals.

Save time with a reliable, total HP solution

Original HP printing materials, Original HP inks, and HP large format printers are designed to work together as a system to provide reliable, consistent, quality results that help save time.

Target customers	Applications	Benefits
Print service providers	Indoor and outdoor advertising	Outstanding image quality on this intermediate polymeric calendared vinyl
	Point-of-sale, retail displays	Gray removable adhesive provides opacity to achieve consistent image quality on multiple surfaces
	Window graphics	Air release liner enables fast, easy, and bubble-free installation
	Exhibit and event graphics	Compatible with Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks

Technical specifications



HP Prime Gloss Air GR

For the latest ICC profiles/paper presets, please visit HPLFMedia.com/hp/paperpresets.

Ink compatibility	Compatible with Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks																
Thickness (base vinyl)	86 microns/3.4 mil per ISO 20534 Test Method																
Base vinyl	Polymeric calendered																
Liner	146 g/m ² , double-sided PE-coated silicone paper with low-profile air release																
Adhesive	Gray, removable pressure-sensitive adhesive; 1 year removable																
Opacity	99% per TAPPI T-425 Test Method																
Finish	Gloss																
Display permanence (Outdoor unprinted)	Over 7 years ³																
Display permanence (Outdoor)	Over 4 years unlaminated, over 10 years laminated with HP 871 and 831 Latex Inks ³																
Display permanence (Indoor home or office)	Over 5 years unlaminated, over 10 years laminated with HP 871 and 831 Latex Inks ⁴																
Display permanence (Commercial in-window)	Over 5 years unlaminated, over 10 years laminated with HP 871 and 831 Latex Inks ⁵																
Water resistance	Water-resistant prints with HP 871 and 831 Latex Inks ⁶																
Minimum application temperature	4 to 35°C (39 to 95°F) on clean, dry surfaces																
Service temperature	-28 to 65°C (-18 to 149°F)																
Operating temperature	15 to 35°C (59 to 95°F)																
Operating humidity	40 to 60% RH																
Lamination	Cold lamination; recommend using HP Matte or Gloss Polymeric Overlaminates																
Shelf life	1 year unopened in original packaging																
Storage temperature	21 to 24°C (69 to 75°F)																
Storage humidity	50% RH																
Environmental	REACH compliant ²																
Country of origin	Product of the United States																
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see HPLFMedia.com/go/mediawarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus .																
Ordering information	<table border="1"> <thead> <tr> <th>Product numbers</th> <th>Roll sizes</th> <th>UPC codes</th> <th>Region</th> </tr> </thead> <tbody> <tr> <td>4WM62A</td> <td>54 in x 150 ft (1372 mm x 45,7 m)</td> <td>848412024432</td> <td>United States, Canada, and Latin America</td> </tr> <tr> <td>4WM64A</td> <td>60 in x 150 ft (1524 mm x 45,7 m)</td> <td>848412024456</td> <td>United States, Canada, and Latin America</td> </tr> <tr> <td>4WM63A</td> <td>54 in x 300 ft (1372 mm x 91,4 m)</td> <td>848412024449</td> <td>United States, Canada, and Latin America</td> </tr> </tbody> </table>	Product numbers	Roll sizes	UPC codes	Region	4WM62A	54 in x 150 ft (1372 mm x 45,7 m)	848412024432	United States, Canada, and Latin America	4WM64A	60 in x 150 ft (1524 mm x 45,7 m)	848412024456	United States, Canada, and Latin America	4WM63A	54 in x 300 ft (1372 mm x 91,4 m)	848412024449	United States, Canada, and Latin America
Product numbers	Roll sizes	UPC codes	Region														
4WM62A	54 in x 150 ft (1372 mm x 45,7 m)	848412024432	United States, Canada, and Latin America														
4WM64A	60 in x 150 ft (1524 mm x 45,7 m)	848412024456	United States, Canada, and Latin America														
4WM63A	54 in x 300 ft (1372 mm x 91,4 m)	848412024449	United States, Canada, and Latin America														

¹ With HP 871 and 831 Latex Inks, over 10 years laminated display permanence for indoor home or office, commercial in-window, and outdoor displays.

² See the HP REACH Declaration published at [HP Printing Products and Consumable Supplies](https://HPLFMedia.com/go/mediawarranties).

³ Outdoor unprinted display permanence rating based on white background color change according to SAE J2527; outdoor display permanence rating according to SAE J2527; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. For more information, see HPLFMedia.com/hp/printpermanence.

⁴ Display permanence rating for interior displays/away from direct sunlight by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see HPLFMedia.com/hp/printpermanence.

⁵ Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant—calculation assumes 6,000 Lux/12 hr day. For more information, see HPLFMedia.com/hp/printpermanence.

⁶ Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see: HPLFMedia.com/hp/printpermanence.

For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2023 HP Development Company, L.P. © 2023 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of HP Development Company, L.P. and is used by Brand Management Group under license from HP Development Company, L.P.

