


X1-4KPRO - DESIGNED FOR XBOX SMART LED 4K PROJECTOR WITH GOOGLE TV

Key Features

- 4K UHD LED smart projector with bright 2500 ANSI lumens and a screen up to 150"
- Xbox native setting with 1440p resolution and a 120Hz refresh rate
- · Ultra-fast 240Hz refresh rate for high-action games and movies
- Built-in Google TV provides easy access to streaming services and smart features for a seamless entertainment experience
- Cinema SuperColor technology with 125% Rec. 709 wide color gamut and HDR/HLG content support produces lifelike colors
- Built-in Dual Harman Kardon Bluetooth speakers deliver exceptional audio performance
- 1.36x digital zoom, auto focus, vertical/horizontal keystone, and 4-corner adjustment for flexible setup
- Supports most media players, PCs, Macs, and mobile devices with inputs such as Wi-

Fi, Dual HDMI and Powered USB A





60 - 150 in. / 1.78 - 3.81 m (diagonal) **DISPLAY**



PANEL



VGA(640 x 480) to 4K(3840 x 2160) **RESOLUTION**



Product **Description**

Unlock the ultimate entertainment experience with the X1-4KPro smart LED projector. This "Designed for Xbox" projector comes with integrated Google TV so you can not only play your favorite games, but also stream your favorite shows and movies in stunning 4K resolution – no external dongle required. With a fast 240Hz refresh rate, it's built to provide ultra-smooth visuals for both high-speed action games and fast-paced movies on a screen up to 150". This home entertainment projector was also designed in partnership with Microsoft for optimized Xbox gameplay: 1440p native Xbox resolution at a 120Hz refresh rate delivers the perfect balance between incredible visuals and accuracy for Xbox gaming. Plus, with next-generation LED technology, you can enjoy pristine image clarity for years to come without performing any maintenance or upkeep. And, with features like vertical lens shift, 1.36x optical zoom, and four-corner adjustment, you can effortlessly build the entertainment setup of your dreams. Level up the way you watch, play and relax with the X1-4KPro projector today.

Specifications

Light Source LED		More Information
Display Resolution 340 x 2160 340 x 31 m (diagonal) 340 x	UPC	766907028065
Display Resolution 3840 x 2160	Light Source	LED
Brightness (Lumens) 2,500 ANS Screen Size 60 - 150 in. / 1.78 - 3.81 m (diagonal) Throw Distance 1,53m-4.98m(100°@2.55m) Throw Ratio 1,15-1.5 Keystone Verlical (+/- 40°) Lens 1,3x optical zoom Light Source Life, Normal (hours) 60,000 Color Depth 1,07 Billion Colors Dynamic Contrast Ratio 16:9 Lens Shift V: +10° Frequency Horizontal 15K-135KHz Frequency Vertical 23-240Hz PC Resolution (max) VGA(640 x 480) to 4K(3840 x 2160) Mac® Resolution (max) 480l, 480p, 576i, 576p, 720p, 1080l, 1080p, 2160p USB 2.0 Type A 1 3.5mm Audio Out 1 Control (R5232) 1 HDMI 2.0 (with HDCP 2.2) 2 Wifi 5Gn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power Key On Screen Display Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality) Control (Information (See user guide for full OSD functionality) Control (Information (See user guide for full OSD functionality) Control (Information (See user guide for full OSD functionality) Control (Information (See user guide for full OSD functionality) Control (Information (See user guide for full OSD functionality) Control (Information (See user guide for full OSD functionality) Control (Information (See user guide for full OSD functionality) Control (Information (See user guide for full OSD functionality) Control (Information (See user guide for full OSD functionality) Control (Information (See user guide for full OSD functionality) Control (Information (See user guide for full OSD functionality) Control (Information (Information (See user guide for full OSD functionality) Control (Information (Information (Information (Information (Information (Info	Display Resolution	4K (3840x2160)
Screen Size 60 · 150 in. / 1.78 · 3.81 m (diagonal) Throw Distance 1.53m-4.98m(100°@2.55m) Throw Ratio 1.15-1.5 Keystone Verlical (+/- 40°) / Honizontal (+/- 40°) Lens 1.3x optical zoom Light Source Life, Normal (hours) 60.000 Color Depth 1.07 Billion Colors Dynamic Contrast Ratio 3.000.000:1 Aspect Ratio 16:9 Lens Shift V: +10° Frequency Vertical 23-240Hz PC Resolution (max) VGA(640 x 480) to 4K(3840 x 2160) Mace Resolution (max) 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p USB 2.0 Type A 1 3.5mm Audio Out 1 Control (R5232) 1 HDMI 2.0 (with HDCP 2.2) 2 Wifi 5Gn Bluetoth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/ 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power Key On Screen	Display Resolution	3840 x 2160
Throw Distance 1.53m.4.98m(100°@2.55m) Throw Ratio 1.15·1.5 Keystone Vertical (+/- 40°) / Horizontal (+/- 40°) Lens 1.3x optical zoom Light Source Life, Normal (hours) 60.000 Color Depth 1.07 Billion Colors Dynamic Contrast Ratio 3.000,000:1 Aspect Ratio 16:9 Lens Shift V: +10° Frequency Horizontal 15K-135KHz Frequency Vertical 23-240Hz PC Resolution (max) VGA(640 x 480) to 4K(3840 x 2160) Mac@ Resolution (max) 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p USB 2.0 Type A 1 3.5mm Audio Out 1 Control (R5232) 1 HDMI 2.0 (with HDCP 2.2) 2 Wiff 5Gn Bluetooth Audio-out 1(BTS.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by < 0.5W Physical Controls Keypad, Power Key On Screen Display	Brightness (Lumens)	2,500 ANSI
Throw Ratio 1.15-1.5 Vertical (+/- 40%) / Horizontal (+/- 40%) Horizontal (+/- 40%)	Screen Size	60 – 150 in. / 1.78 – 3.81 m (diagonal)
Keystone Vertical (+/- 40%) / Horizontal (+/- 40%) Lens 1.3x optical zoom Light Source Life, Normal (hours) 60.000 Color Depth 1.07 Billion Colors Dynamic Contrast Ratio 3.000,000:1 Aspect Ratio 16:9 Lens Shift V: +10% Frequency Horizontal 15K-135KHz Frequency Vertical 23-240Hz PC Resolution (max) VGA(640 x 480) to 4K(3840 x 2160) Mac® Resolution (max) 4801, 480p, 576l, 576p, 720p, 1080l, 1080p, 2160p USB 2.0 Type A 1 3.5mm Audio Out 1 Control (RS232) 1 HDMI 2.0 (with HDCP 2.2) 2 Wiff 5Gn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power Key On Screen Display Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Throw Distance	1.53m-4.98m(100"@2.55m)
Light Source Life, Normal (hours) Color Depth 1.07 Billion Colors Dynamic Contrast Ratio 16:9 Lens Shift V: +10° Frequency Horizontal Frequency Vertical PC Resolution (max) 4801, 4801, 5761, 576p, 720p, 10801, 1080p, 2160p USB 2.0 Type A 3.5mm Audio Out 1 Control (RS232) 1 HDMI 2.0 (with HDCP 2.2) Wiff SGn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage Consumption (typical) Stand-by Physical Controls Keypad, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functions in year Management, Basic, Advanced, System, Information (See user guide for full OSD functions) 1.00 (Voltage Uspical) Controls Consumption (typical) Stand-by Physical Controls Consumption (See user guide for full OSD functionality) Control (RS232) Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Throw Ratio	1.15-1.5
Light Source Life, Normal (hours) 60.000 Color Depth 1.07 Billion Colors Dynamic Contrast Ratio 3.000,000:1 Aspect Ratio 16:9 Lens Shift V: +10° Frequency Horizontal 15K:135KHz PC Resolution (max) VGA(640 x 480) to 4K(3840 x 2160) Mac® Resolution (max) 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p U5B 2.0 Type A 1 3.5mm Audio Out 1 Control (RS232) 1 HDMI 2.0 (with HDCP 2.2) 2 Wifi 5Gn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power Key On Screen Display Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Keystone	Vertical (+/- 40º) / Horizontal (+/- 40º)
Color Depth 1.07 Billion Colors Dynamic Contrast Ratio 3,000,000:1 Aspect Ratio 16:9 Lens Shift V: +10° Frequency Horizontal 15K-135KHz Frequency Vertical 23-240Hz PC Resolution (max) VGA(640 x 480) to 4K(3840 x 2160) Mac® Resolution (max) 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p USB 2.0 Type A 1 3.5mm Audio Out 1 Control (RS232) 1 HDMI 2.0 (with HDCP 2.2) 2 Wifi 5Gn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power Key On Screen Display Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Lens	1.3x optical zoom
Dynamic Contrast Ratio 3,000,000:1 Aspect Ratio 16:9 Lens Shift V: +10° Frequency Horizontal 15K-135KHz Frequency Vertical 23-240Hz PC Resolution (max) VGA(640 x 480) to 4K(3840 x 2160) Mac® Resolution (max) 4800, 4800, 576i, 576p, 720p, 1080i, 1080p, 2160p USB 2.0 Type A 1 3.5mm Audio Out 1 Control (RS232) 1 HDMI 2.0 (with HDCP 2.2) 2 Wifi 5Gn Bluetooth Audio-out 1(8T5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power key On Screen Display Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD runctionality)	Light Source Life, Normal (hours)	60,000
Aspect Ratio 16:9 Lens Shift V: +10° Frequency Horizontal 15K-135KHz Frequency Vertical 23-240Hz PC Resolution (max) VGA(640 x 480) to 4K(3840 x 2160) Mac® Resolution (max) 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p USB 2.0 Type A 1 3.5mm Audio Out 1 Control (RS232) 1 HDMI 2.0 (with HDCP 2.2) 2 Wifi 5Gn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power key On Screen Display Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Color Depth	1.07 Billion Colors
Lens Shift V: +10° Frequency Horizontal 15K-135KHz Frequency Vertical 23-240Hz PC Resolution (max) VGA(640 x 480) to 4K(3840 x 2160) Mac® Resolution (max) 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p USB 2.0 Type A 1 3.5mm Audio Out 1 Control (RS232) 1 HDMI 2.0 (with HDCP 2.2) 2 Wifi 5Gn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power key Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Dynamic Contrast Ratio	3,000,000:1
Frequency Vertical 23-240Hz PC Resolution (max) VGA(640 x 480) to 4K(3840 x 2160) Mac® Resolution (max) 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p USB 2.0 Type A 1 3.5mm Audio Out 1 Control (RS232) 1 HDMI 2.0 (with HDCP 2.2) 2 Wifi 5Gn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power key On Screen Display Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Aspect Ratio	16:9
Frequency Vertical 23-240Hz PC Resolution (max) VGA(640 x 480) to 4K(3840 x 2160) Mac® Resolution (max) 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p USB 2.0 Type A 1 3.5mm Audio Out 1 Control (RS232) 1 HDMI 2.0 (with HDCP 2.2) 2 Wifi 5Gn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power key On Screen Display Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Lens Shift	V: +10°
PC Resolution (max) VGA(640 x 480) to 4K(3840 x 2160) Mac® Resolution (max) 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p USB 2.0 Type A 1 3.5mm Audio Out 1 Control (RS232) 1 HDMI 2.0 (with HDCP 2.2) 2 Wifi 5Gn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W	Frequency Horizontal	15K-135KHz
Mac® Resolution (max)480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160pUSB 2.0 Type A13.5mm Audio Out1Control (RS232)1HDMI 2.0 (with HDCP 2.2)2Wifi5GnBluetooth Audio-out1(BT5.0)Internal Speakers6W (x2)Voltage100-240V+/- 10%, 50/60Hz ACConsumption (typical)236WStand-by<0.5W	Frequency Vertical	23-240Hz
USB 2.0 Type A 3.5mm Audio Out 1 Control (RS232) 1 HDMI 2.0 (with HDCP 2.2) Wifi 5Gn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	PC Resolution (max)	VGA(640 x 480) to 4K(3840 x 2160)
3.5mm Audio Out Control (RS232) 1 HDMI 2.0 (with HDCP 2.2) Wifi 5Gn Bluetooth Audio-out I(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) Stand-by Physical Controls Keypad, Power key On Screen Display Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Mac® Resolution (max)	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p
Control (RS232) HDMI 2.0 (with HDCP 2.2) Wifi 5Gn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) Stand-by Physical Controls Keypad, Power key Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	USB 2.0 Type A	1
Wifi 5Gn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power key Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	3.5mm Audio Out	1
Wifi 5Gn Bluetooth Audio-out 1(BT5.0) Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power key On Screen Display Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Control (RS232)	1
Internal Speakers 6W (x2) Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power key Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	HDMI 2.0 (with HDCP 2.2)	2
Internal Speakers Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) Stand-by <0.5W Physical Controls Keypad, Power key Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Wifi	5Gn
Voltage 100-240V+/- 10%, 50/60Hz AC Consumption (typical) 236W Stand-by <0.5W Physical Controls Keypad, Power key Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Bluetooth Audio-out	1(BT5.0)
Consumption (typical) Stand-by <0.5W Physical Controls Keypad, Power key Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality) 	Internal Speakers	6W (x2)
Stand-by <0.5W Physical Controls Keypad, Power key On Screen Display Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Voltage	100-240V+/- 10%, 50/60Hz AC
Physical Controls Keypad, Power key Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Consumption (typical)	236W
On Screen Display Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)	Stand-by	<0.5W
functionality)	Physical Controls	Keypad, Power key
Temperature 32-104º F (0 - 40º C)	On Screen Display	
	Temperature	32-104º F (0 - 40º C)

Kensington Lock Slot	1
Net (lbs)	8.1
Gross (lbs)	12.3
Net (kg)	3.7
Gross (kg)	5.6
Packaging (in.)	19.3x14.8x12.3
Physical (in.)	14.0x9.6x4.8
Packaging (mm)	490x376x313mm
Physical (mm)	355x244x121mm
Regulations	cTUVus
Package Contents	Projector, power cable, remote control, Quick Start Guide,
Warranty	Three-year limited warranty on parts and labor
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907028065







Contact Sales ViewSonic.com

888.881.8781 email: salesinfo@viewsonic.com