

## Key Features

Streamlined Desktop Display Solution | Enhanced Productivity with

Dual Monitor Setup | Reduce Clutter with Single-Cable Solution |

Reduce Clutter with Single-Cable Solution | A More Comfortable

Workspace



## Product Description

Designed to boost productivity and maximize output, the ViewSonic® VG2456 is a 24” docking monitor that transforms your desktop into a streamlined and efficient workspace. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the latest USB 3.2 Type-C connectivity makes dual-monitor setup a breeze. That’s not all, the integrated USB hub also provides single-cable simplicity for connecting and charging your peripherals and accessories. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need. In addition, the included vDisplay software gives you quick and easy OSD control, as well as customized screen templates for easy multi-tasking. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for quick deployment and a lower total cost of ownership.




01. Menu Controls
02. VESA Compatible Wall Mount  
100 x 100 mm
03. Internal Speakers



04. AC In
05. HDMI 1.4
06. Display Port In
07. USB Type A (x2)




08. Kensington® Lock Slot
09. LAN (RJ45)
10. USB Type B
11. Display Port Out
12. USB 3.2 Type C



24”  
DISPLAY



IPS  
PANEL



1920 x 1080  
RESOLUTION

### Contact Sales

- call: 888.881.8781
- email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)
- visit: [viewsonic.com](http://viewsonic.com)

**Display:**

|                              |                                |
|------------------------------|--------------------------------|
| Display Size (in.):          | 24                             |
| Viewable Area (in.):         | 23.8                           |
| Panel Type:                  | IPS                            |
| Resolution:                  | 1920 x 1080                    |
| Resolution Type:             | HD (1920x1080)                 |
| Static Contrast Ratio:       | 1,000:1                        |
| Dynamic Contrast Ratio:      | 50,000,000:1                   |
| Light Source:                | WLED                           |
| Brightness:                  | 250 cd/m2                      |
| Colors:                      | 16.7M                          |
| Color Space Support:         | 6 bit                          |
| Aspect Ratio:                | 16:9                           |
| Response Time (Typical GTG): | 15ms                           |
| Response Time (GTG w/OD):    | 5ms                            |
| Viewing Angles:              | 178° horizontal, 178° vertical |
| Backlight Life (Hours):      | 30,000                         |
| Panel Surface:               | Anti-glare, Hard coating (3H)  |

**Compatibility:**

|                        |           |
|------------------------|-----------|
| PC Resolution (max):   | 1920x1080 |
| Mac® Resolution (max): | 1920x1080 |

**Connector:**

USB 3.2 Gen 1 Type A(2), USB 3.2 Gen 1 Type B(1), USB 3.2 Gen 1 Type C(1), HDMI 1.4 In(1), Display Port(1), Display Port Out(1)

**Audio:**

|                    |         |
|--------------------|---------|
| Internal Speakers: | 2W (x2) |
|--------------------|---------|

**Controls:**

|                    |                     |
|--------------------|---------------------|
| Physical Controls: | 1,2,3,4,5,6 (Power) |
|--------------------|---------------------|

On Screen Display: Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

**Operating Conditions:**

|                            |                       |
|----------------------------|-----------------------|
| Temperature:               | 32-104° F (0 - 40° C) |
| Humidity (non-condensing): | 20-90%                |

**Mount:**

|                  |              |
|------------------|--------------|
| VESA Compatible: | 100 x 100 mm |
|------------------|--------------|

**Video Signal:**

|                       |             |
|-----------------------|-------------|
| Frequency Horizontal: | 15 ~ 82 KHz |
| Frequency Vertical:   | 24 ~ 75 Hz  |

**Video Input:**

|               |   |
|---------------|---|
| Digital Sync: | TMDS for HDMI (v1.4), PCI-E for DisplayPort (v1.2), Micro-Packet for USB Type C |
|---------------|---|

**Ergonomics:**

|                      |                 |
|----------------------|-----------------|
| Height Adjust:       | 130 mm / 5.1 in |
| Swivel:              | 120°            |
| Pivot (Right/Left):  | 90° / 90°       |
| Tilt (Forward/Back): | 40° / 5°        |

**Weight (imperial):**

|                          |      |
|--------------------------|------|
| Net (lbs):               | 14.1 |
| Net Without Stand (lbs): | 8.8  |
| Gross (lbs):             | 20.7 |

**Weight (metric):**

|                         |     |
|-------------------------|-----|
| Net (kg):               | 6.4 |
| Net Without Stand (kg): | 4.0 |
| Gross (kg):             | 9.4 |

**Dimensions (imperial) (WxHxD):**

|                               |                   |
|-------------------------------|-------------------|
| Packaging (in.):              | 23.4 x 8.3 x 15.6 |
| Physical (in.):               | 21.2 x 16.0 x 8.0 |
| Physical Without Stand (in.): | 21.2 x 12.6 x 2.0 |

**Dimensions (metric) (WxHxD):**

|                              |                       |
|------------------------------|-----------------------|
| Packaging (mm):              | 595.0 x 210.0 x 396.0 |
| Physical (mm):               | 539.0 x 406.2 x 202.0 |
| Physical Without Stand (mm): | 539.0 x 320.0 x 52.0  |

**General:**

Regulations: cTUVus, FCC-B, ICES003, Energy Star, EPEAT, MX-CoC, Mexico Energy

PACKAGE CONTENTS: VG2456 Display, Power Cable, DP to DP Cable, USB Type C Cable, USB 3.2 Uplink Cable, Quick Start Guide

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907006155

**Accessories:**

CB-00008948, CB-00009950, CB-00010684, CB-00010958, LCD-CMK-001, LCD-WMK-001