




VG2758-2K - 27" 1440P IPS ERGONOMIC DOCKING MONITOR | 100W USB-C, RJ45, DAISY CHAIN

Key Features


- Lower TCO (total cost of ownership) via a built-in USB-C docking station with 100W power delivery
- Connect multiple monitors together using a USB-C daisy chain
- Plug in your favorite peripherals using a future-proof five-port USB hub
- An ergonomic design lets users work for longer with less strain



27"
DISPLAY



IPS
PANEL



2560 x 1440p
RESOLUTION



Product Description

Add next-generation productivity, clarity and connectivity to your setup with the 27" VG2758-2K USB-C docking monitor. This stunning 2K monitor streamlines your workspace by eliminating the need for a separate docking station or extra cables. This empowers users to enjoy a lower overall total cost of ownership (TCO) compared to more traditional configurations. The VG2758-2K monitor's built-in docking station includes 100W USB-C connectivity, an RJ45 Ethernet port, USB-C daisy-chaining and a five-port USB hub. With advanced daisy-chain technology, this next-generation docking monitor lets users create a streamlined multi-monitor setup via a single USB-C daisy chain cable. Enjoy razor sharp resolution and fast refresh rates with no additional cables required. The VG2758-2K monitor's future-proof USB hub features three USB-A ports and two USB-C ports (with 15W power delivery). For easier access, users can plug their devices into the 1x USB-C port and 2x USB-A ports located on the front bezel of the monitor. Plus, with an advanced ergonomic design, the VG2758-2K lets you work for longer with less strain.

Specifications

	More Information
UPC	766907027952
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	QHD (2560x1440)
Static Contrast Ratio	1,500:1
Light Source	LED
Brightness	350 cd/m2
Colors	16.7M
Color Space Support	8 bit true
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	100Hz
PC Resolution (max)	2560 x 1440p
Mac® Resolution (max)	2560 x 1440p
USB Type A	3
USB Type C (Upstream)	1 (DP Alt mode; 100W)
USB Type C (Downstream)	2 (15W)
USB Type C (Out)	1 (DP Alt mode)
3.5mm Audio Out	1
Ethernet LAN (RJ45)	1
HDMI 1.4 In	1
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	138
Eco Mode (optimized)	143
Consumption (typical)	149
Consumption (max)	242
Voltage	100-240 VAC, 50-60Hz
Stand-by	0.5

Power Supply	Internal
Cable Organization	Yes
Kensington Lock Slot	1
Physical Controls	Joystick key: Up, Right, Down, Left, Center; Power
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	30 ~ 151 KHz
Frequency Vertical	50 ~ 100 Hz
Height Adjust	150 mm / 5.9 in
Swivel	90º
Pivot (Right/Left)	90º / 90º
Tilt (Forward/Back)	5º / 30º
Regulations	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC
Net (lbs)	16.4
Net Without Stand (lbs)	11
Gross (lbs)	22.4
Net (kg)	7.4
Net Without Stand (kg)	5
Gross (kg)	10.2
Packaging (in.)	27.6W x 16.7H x 6.5D
Physical (in.)	24.12 W x 15.84 ~ 20.69H x 8.6D
Physical Without Stand (in.)	24.12 W x 14.16H x 1.76D
Packaging (mm)	702W x 425H x 166D
Physical (mm)	612.6W x 402.32~525.64H x 218.47D
Physical Without Stand (mm)	612.6 W x 359.77H x 44.75D
Package Contents	LCD Display, Power Cable, DisplayPort Cable, USB Type-C Cable (with USB Type A adaptor), Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907027952



INSTALLING THE QUICK DEPLOY STAND
FOR VG58 SERIES DOCKING MONITORS



VIEWSONIC VG58 SERIES
DOCKING MONITORS



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com