

Xerox® B410 Printer



Work doesn't slow down,
and your printer shouldn't either.

PRINT SPEED (UP TO:)	
One-sided Speed¹	Black-and-White: Up to 50/47 ppm Letter/A4
Two-sided Speed¹	Black-and-White: Up to 25/24 ppm Letter/A4
Monthly Duty Cycle² (Up To:) Pages Per Month	175,000
Recommended Average Monthly Print Volume (Up To:) Pages Per Month	20,000
Processor/Memory/Storage Clock Speed/Cores Memory/Storage	1 GHz Dual Core Processor 1GB RAM 8GB eMMC/ Optional: 500+GB HDD
Connectivity Device Connectivity	Hi-Speed USB 2.0 (Type A), Hi-Speed USB (Type B) Gigabit Ethernet/ Optional: Wireless Network Adapter (802.11 b/g/n/ac)
Imaging Technology	Laser
PRINT	
Print Resolution (Up To:)	1200 x 1200 dpi, 2400 Image Quality
First-Print-Out Time (As Fast As:)	As fast as 5.4 seconds black-and-white
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL 5 Emulation, PDF v1.7 Emulation, Direct Image
Print Features	One Touch UI, Print Quality, Normal, Secure, Saved and Sample Set Job Types, Duplex, Orientation, Collation, Print Job ID in Margins, Draft Mode, N-up, Booklet Layout, Watermark, Tray and Toner Status, Rotate Image 180 Degrees, Saved Settings, Earth Smart Settings
MOBILE AND CLOUD READY	
Mobile Printing	Apple AirPrint, Mopria Print Service, Chromebook, Wi-Fi Direct ³
Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox Workplace Cloud and Suite is the complete print management platform for security, cost control and mobility delivering workflow productivity to office and hybrid workers. Available as an on-premises version (Workplace Suite) or a Cloud-based (Workplace Cloud), it provides the ultimate flexibility in freeing up IT teams to focus on core business priorities. (Select models may require additional optional equipment.)
Cloud Connectivity	Yes (via Xerox Print and Scan Experience)

Xerox B410 Printer

PRINT DETAILS	
First-Print-Out Time – B&W (As Fast As:)	5.2 seconds
Resolution (Up To:)	1200 x 1200 dpi, 2400 Image Quality
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL 5 Emulation, PDF v1.7 Emulation, Direct Image
Unprintable Page Margin	Print: 4.2 mm from each edge
Print from USB	Yes. Documents; PDF, HTML, XPS, Microsoft file formats (.doc, .docx, .xls, .xlsx, .ppt, .pptx) Images: .dcx, .gif, .JPEG (.jpg), .bmp, .pcx, .TIFF (.tif), .png
Print Driver Types/Operating Systems	Windows® 11, Windows® 10, Windows Server 2022, Windows Server 2019, Windows Server 2016, Windows Server 2012 R2, Windows Server 2012, macOS 13.x, macOS 12.x, macOS 11.x. Microsoft Universal Print. For the latest information about supported Operating Systems, please visit our Drivers & Downloads page and specify your device at support.xerox.com .
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, MS Web Services WSD-Print, 802.1x, SNMP, ThinPrint, Universal Print, Bonjour
Font Capability	PCL5/6 94 scalable fonts, 2 bitmapped PS emulation 163 scalable fonts
DEVICE MANAGEMENT	
Device Management	Xerox Easy Assist, Remote Operator Panel, Embedded Web Server
Xerox® CentreWare® Web Software	Yes
SECURITY	
Security Protocols/Features	Digitally Signed Firmware Updates, Trusted Platform Module (TPM), TLS 1.3, FIPS 140-2 Certificate Management, Secure Password Reset, TCP Connection Filtering, Port Filtering, Access Controls, Confidential Print, Non-Volatile Memory Wipe, Protected USB Ports, IPsec, Image Overwrite ⁴
WI-FI SECURITY (REQUIRES WIRELESS NETWORK ADAPTER)	
Authentication and Encryption Methods	Infrastructure (BSS) Mode, WEP Encryption (64 & 128 bit keys), WPA2/WPA Personal AES PSK, WPA2-Personal, WPA3 Support, 802.1x; EAP-MD5, EAP-MSCHAPv2, EAP-TLS, EAP-TTLS (CHAP/MSCHAP/MSCHAPv2/PAP), LEAP, PEAP
PAPER HANDLING	
MAIN TRAY	
Standard/Optional	Standard
Capacity (Up To:)	550 sheets of 20 lb bond/75 gsm
Minimum Media Size (in)	4.1 x 5.8 in
Minimum Media Size (mm)	105 x 148 mm
Maximum Media Size (in)	Legal (8.5 x 14 in)
Maximum Media Size (mm)	216 x 360 mm
Minimum Media Weight (gsm)	60 gsm
Minimum Media Weight – Duplex (gsm)	60 gsm
Maximum Media Weight (gsm)	120 gsm
Maximum Media Weight – Duplex (gsm)	120 gsm
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Recycled, Bond, Labels, Pre-Printed, Colored Paper, Rough Cotton, Custom
BYPASS TRAY	
Standard/Optional	Standard
Capacity (Up To:)	100 sheets of 20 lb bond/75 gsm
Minimum Media Size (in)	3 x 5.8 in
Minimum Media Size (mm)	76 x 148 mm
Maximum Media Size (in)	Legal (8.5 x 14 in)
Maximum Media Size (mm)	216 x 360 mm
Minimum Media Weight (gsm)	60 gsm
Minimum Media Weight – Duplex (gsm)	60 gsm
Maximum Media Weight (gsm)	216 gsm
Maximum Media Weight – Duplex (gsm)	120 gsm
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Cardstock, Recycled, Bond, Labels, Glossy, Vinyl, Pre-Printed, Envelope, Colored Paper, Rough Cotton, Custom

Xerox B410 Printer

PAPER HANDLING (CONTINUED)	
OPTIONAL 550-SHEET TRAY (ADD UP TO 3 ADDITIONAL TRAYS)	
Capacity (Up To:)	550 sheets of 20 lb bond/75 gsm
Minimum Media Size (in)	4.1 x 5.8 in
Minimum Media Size (mm)	105 x 148 mm
Maximum Media Size (in)	Legal (8.5 x 14 in)
Maximum Media Size (mm)	216 x 360 mm
Minimum Media Weight (gsm)	60 gsm
Minimum Media Weight – Duplex (gsm)	60 gsm
Maximum Media Weight (gsm)	120 gsm
Maximum Media Weight – Duplex (gsm)	120 gsm
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Recycled, Bond, Labels, Pre-Printed, Colored Paper, Rough Cotton, Custom
STANDARD/MAXIMUM INPUT CAPACITY	
Standard Input Capacity	650
Maximum Input Capacity	2300
OUTPUT CAPACITY	
Output Capacity	250

Xerox B410 Printer

DEVICE SPECIFICATIONS	
ELECTRICAL REQUIREMENTS	
North America	100 to 127 volts (V) at 50 to 60 hz or 57 to 63 hertz (HZ) nominal 90 to 140 volts, extreme
Europe	220 to 240 volts (V) at 50 to 60 hz or 57 to 63 hertz (HZ) nominal (not available in all countries) 198 to 264 volts, extreme
POWER CONSUMPTION	
Operation/Running – 110V/220V	Simplex 669W; Duplex 417W
Standby Mode – 110V/220V	7.7W
Auto Off/Sleep Mode – 110V/220V	1.0W
Power Off Mode – 110V/220V	0.1W
Default Time to Sleep Mode	15 minutes (Adjustable 1-60 minutes)
Time to First Print from Sleep Mode	6.9 seconds
Time to Ready from Off	98 seconds
OPERATING ENVIRONMENT	
Required Temperature Range – Fahrenheit (operating)	50 to 90° F
Required Temperature Range – Celsius (operating)	10 to 32° C
Required Relative Humidity	8% to 80% RH
Required Temperature Range – Fahrenheit (storage)	-40 to 104° F
Required Temperature Range – Celsius (storage)	-40 to 40° C
SOUND POWER LEVELS	
Sound Pressure Levels	Operating simplex/56 dB(A) Operating duplex/55 dB(A) Quiet mode simplex/52 dB(A) Quiet mode duplex/51 dB(A) Idle 14 dB(A)
Sound Power Levels	Operating simplex/7.1 B(A) Operating duplex/6.9 B(A) Quiet mode simplex/6.6 B(A) Quiet mode duplex/6.6 B(A) Idle 3.1 B(A)

Xerox B410 Printer

DIMENSIONS AND WEIGHTS	
Printer (Packaged)	Width: 16.9 in/430 mm Depth: 18.5 in/470 mm Height: 16.6 in/422 mm Weight: 38 lb/17.2 kg
Printer (Unpackaged)	Width: 15.7 in/399 mm Depth: 14.7 in/373 mm Height: 12.1 in/308 mm Weight: 33.4 lb/15.2 kg
550-Sheet Tray (Packaged)	Width: 16.9 in/428mm Depth: 18.4 in/468 mm Height: 7.6 in/193 mm Weight: 12.2 kg/5.5 kg
550-Sheet Tray (Unpackaged)	Width: 15.3 in/389 mm Depth: 14.7 in/373 mm Height: 4.3 in/108 mm Weight: 10.4 lb/4.7 kg
Printer Stand (Packaged)	Width: 20.7 in/525 mm Depth: 22.2 in/565 mm Height: 9.2 in/235 mm Weight: 37.7 lb/17.1 kg
Printer Stand (Unpackaged)	Width: 18.2 in/463 mm Depth: 20 in/510 mm Height: 17.3 in/440 mm Weight: 32.7 lb/14.8 kg
INSTALLATION CONSIDERATIONS	
Clear area around the device is necessary for access and ventilation. The below table shows the area needed on each side for correct installation.	
Top	3.9 in/100 mm
Rear	3.9 in/100 mm
Left	2.6 in/65 mm
Right	4.3 in/110 mm
Front	12 in /305 mm
SYSTEM CERTIFICATION/REGULATORY COMPLIANCE	
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertifications
WHAT'S IN THE BOX	
All items contained in the box	B410 Printer Power Cord Installation Guide Product Safety Sheet Quick Use Guide Software and Documentation CD Pre-installed Starter Capacity Print Cartridges: Black cartridge: 6,000 print capacity ⁵

Xerox B410 Printer

SUPPLIES AND ACCESSORIES	NORTH AMERICA AND EUROPE*	ALL OTHER REGIONS
Genuine Xerox Black Standard Capacity Toner Cartridge, Xerox B410 Printer (6,000 Pages) ⁵	006R04725	006R04728
Genuine Xerox Black High Capacity Toner Cartridge, Xerox B410 Printer (14,000 Pages) ⁵	006R04726	006R04729
Genuine Xerox Black Extra High Capacity Toner Cartridge, Xerox B410 Printer (25,000 Pages)	006R04727	006R04730
Genuine Xerox Black Imaging Kit, Xerox B410 Printer (75,000 Pages) ⁶	013R00702	013R00702
OPTIONAL ACCESSORIES		
550-Sheet Tray	097N02469	
Wireless Network Adapter	097N02470	
500+GB Hard Disk	097N02467	
Xerox Adjustable Stand ⁷	497N07994	
Xerox Printer Stand	097S05244	

* North America (NA): U.S., Canada
 Europe (XE): U.K., France, Germany, Spain, Italy, Netherlands, Belgium, Norway, Sweden, Finland, Denmark, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland Andorra, Azores, Corsica, Greenland, Iceland, Lichtenstein, Luxembourg, Madeira, San Marino

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Requires Wireless Network Adapter

⁴ Requires 500+GB Hard Disk

⁵ Average standard pages. Declared yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

⁶ Approximate pages. Declared yield will vary depending on job run length and media size/orientation and print mode. For more information, visit office.xerox.com/latest/SUPGL-01.PDF

⁷ Availability varies by geography. Contact your Xerox sales representative for more information.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. Visit xerox.com/About-Xerox/Recycling.

For more information, visit us at xerox.com/office.