



Work doesn't slow down, and your printer shouldn't either.

PRINT SPEED (UP TO:)			
One-sided Speed ¹	Black-and-white: Up to 50/47 ppm Letter/A4		
Two-sided Speed ¹	Black-and-white: Up to 25/24 ppm Letter/A4		
Monthly Duty Cycle ² (Up To:) Pages Per Month	175,000		
Recommended Average Monthly Print Volume (Up To:) Pages Per Month	20,000		
Processor/Memory/Storage Clock Speed/Cores Memory/Storage	1 GHz Dual Core Processor 1GB RAM 8GB eMMC/ Optional : 500+GB HDD		
Connectivity Device Connectivity	Hi-Speed USB 2.0 (Type A), Hi-Speed USB (Type B) Gigabit Ethernet/ Optional: Wireless Network Adapter (802.11 b/g/n/ac)		
Imaging Technology	Laser		
PRINT			
Print Resolution (Up To:)	1200 x 1200 dpi, 2400 Image Quality		
First-print-out Time (As Fast As:)	As fast as 5.4 seconds black-and-white		
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL® 5 Emulation, PDF v1.7 Emulation, Direct Image		
Print Features	One Touch UI, Print Quality, Normal, Secure, Saved and Sample Set Job Types, Duplex, Orientation, Collation, Print Job ID in Margins, Draft Mode, N-up, Booklet Layout, Watermark, Tray and Toner Status, Rotate Image 180 Degrees, Saved Settings, Earth Smart Settings		
MOBILE AND CLOUD READY			
Mobile Printing	Apple® AirPrint®, Mopria® Print Service, Chromebook, Wi-Fi Direct®3		
Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox Workplace Cloud and Suite is the complete print management platform for security, cost control, and mobility, delivering workflow productivity to office and hybrid workers. Available as an on-premises version (Workplace Suite) or a cloud-based (Workplace Cloud), it provides the ultimate flexibility in freeing up IT teams to focus on core business priorities. (Select models may require additional optional equipment.)		
Cloud Connectivity	Yes (via Xerox® Print and Scan Experience App)		

PRINT DETAILS			
First-print-out Time – B&W			
(As Fast As:)	5.4 seconds		
Resolution (Up To:)	1200 x 1200 dpi, 2400 Image Quality		
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL® 5 Emulation, PDF v1.7 Emulation, Direct Image		
Unprintable Page Margin	Print: 4.2 mm from each edge		
Print from USB	Yes. Documents; PDF, HTML, XPS, Microsoft File Formats (.doc, .docx, .xls, .xlsx, .ppt, .pptx) Images: .dcx, .gif, .JPEG (.jpg), .bmp, .pcx, .TIFF (.tif), .png)		
Print Driver Types/Operating Systems	Windows® 11, Windows® 10, Windows Server 2022, Windows Server 2019, Windows Server 2016, Windows Server 2012 R2, Windows Server 2012. macOS 13.x, macOS 12.x, macOS 11.x. Microsoft Universal Print. For the latest information about supported operating systems, please visit our Drivers & Downloads page and specify your device at support.xerox.com.		
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, MS Web Services WSD-Print, 802.1x, SNMP, ThinPrint, Universal Print, Bonjour		
Font Capability	PCL5/6 94 Scalable Fonts, 2 Bitmapped PS Emulation 163 Scalable Fonts		
DEVICE MANAGEMENT			
Device Management	Xerox® Easy Assist App, Remote Operator Panel, Xerox® Embedded Web Server		
Xerox® CentreWare® Web Software	Yes		
SECURITY			
Security Protocols/Features	Digitally Signed Firmware Updates, Trusted Platform Module (TPM), TLS 1.3, FIPS 140-2 Certificate Management, Secure Password Reset, TCP Connection Filtering, Port Filtering, Access Controls, Confidential Print, Non-volatile Memory Wipe, Protected USB Ports, IPSec, Image Overwrite ⁴		
WI-FI SECURITY (REQUIRES	WIRELESS NETWORK ADAPTER)		
Authentication and Encryption Methods	Infrastructure (BSS) Mode, WEP Encryption (64 and 128 bit keys), WPA2/WPA Personal AES PSK, WPA2-Personal, WPA3 Support, 802.1x; EAP-MD5, EAP-MSCHAPv2, EAP-TLS, EAP-TLS (CHAP/MSCHAP/MSCHAPv2/PAP), LEAP, PEAP		
PAPER HANDLING			
MAIN TRAY			
Standard/Optional	Standard		
Capacity (Up To:)	550 sheets of 20 lb bond/75 gsm		
Minimum Media Size (in)	4.1 x 5.8 in		
Minimum Media Size (mm)	105 x 148 mm		
Maximum Media Size (in)	Legal (8.5 x 14 in)		
Maximum Media Size (mm)	216 x 360 mm		
Minimum Media Weight (gsm)	60 gsm		
Minimum Media Weight – Duplex (gsm)	60 gsm		
Maximum Media Weight (gsm)	120 gsm		
Maximum Media Weight – Duplex (gsm)	120 gsm		
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Recycled, Bond, Labels, Pre-printed, Colored Paper, Rough Cotton, Custom		
BYPASS TRAY			
Standard/Optional	Standard		
Capacity (Up To:)	100 sheets of 20 lb bond/75 gsm		
Minimum Media Size (in)	3 x 5.8 in		
Minimum Media Size (mm)	76 x 148 mm		
Maximum Media Size (in)	Legal (8.5 x 14 in)		
Maximum Media Size (mm)	216 x 360 mm		
Minimum Media Weight (gsm)	60 gsm		
Minimum Mediα Weight – Duplex (gsm)	60 gsm		
Maximum Media Weight (gsm)	216 gsm		
Maximum Media Weight – Duplex (gsm)	120 gsm		
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Cardstock, Recycled, Bond, Labels, Glossy, Vinyl, Pre-printed, Envelope, Colored Paper, Rough Cotton, Custom		

PAPER HANDLING (CONTINUED)				
OPTIONAL 550-SHEET TRAY (ADD UP TO 3 ADDITIONAL TRAYS)				
Capacity (Up To:)	550 sheets of 20 lb bond/75 gsm			
Minimum Media Size (in)	4.1 x 5.8 in			
Minimum Mediα Size (mm)	148 x 210 mm			
Maximum Media Size (in)	Legal (8.5 x 14 in)			
Maximum Media Size (mm)	216 x 360 mm			
Minimum Media Weight (gsm)	60 gsm			
Minimum Media Weight – Duplex (gsm)	60 gsm			
Maximum Media Weight (gsm)	120 gsm			
Maximum Media Weight – Duplex (gsm)	120 gsm			
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Recycled, Bond, Labels, Pre-printed, Colored Paper, Rough Cotton, Custom			
STANDARD/MAXIMUM INPUT CAPACITY				
Standard Input Capacity	650			
Maximum Input Capacity	2300			
OUTPUT CAPACITY				
Output Capacity	250			

DEVICE SPECIFICATIONS					
ELECTRICAL REQUIREMENTS					
North America	100 to 127 volts (V) at 50 to 60 hz or 57 to 63 hertz (HZ) nominal 90 to 140 volts, extreme				
Europe	220 to 240 volts (V) at 50 to 60 hz or 57 to 63 hertz (HZ) nominal (Not available in all countries) 198 to 264 volts, extreme				
POWER CONSUMPTION	POWER CONSUMPTION				
Operation/Running – 110V/220V	Simplex 669W; Duplex 417W				
Standby Mode – 110V/220V	7.7W				
Auto Off/Sleep Mode – 110V/220V	1.0W				
Power Off Mode – 110V/220V	0.1W				
Default Time to Sleep Mode	15 minutes (Adjustable 1-60 minutes)				
Time to First Print From Sleep Mode	6.9 seconds				
Time to Ready From Off	98 seconds				
OPERATING ENVIRONMENT					
Required Temperature Range – Fahrenheit (Operating)	50 to 90° F				
Required Temperature Range – Celsius (Operating)	10 to 32° C				
Required Relative Humidity	8% to 80% RH				
Required Temperature Range – Fahrenheit (Storage)	-40 to 104° F				
Required Temperature Range – Celsius (Storage)	-40 to 40° C				
SOUND POWER LEVELS					
Sound Pressure Levels	Operating simplex/56 dB(A) Operating duplex/55 dB(A) Quiet mode simplex/52 dB(A) Quiet mode duplex/51 dB(A) Idle 14 dB(A)				
Sound Power Levels	Operating simplex/7.1 B(A) Operating duplex/6.9 B(A) Quiet mode simplex/6.6 B(A) Quiet mode duplex/6.6 B(A) Idle 3.1 B(A)				

DIMENSIONS AND WEIGHTS	DIMENSIONS AND WEIGHTS				
Printer (Packaged)	Width: 16.9 in/430 mm Depth: 18.5 in/470 mm Height: 16.6 in/422 mm Weight: 38 lb/17.2 kg				
Printer (Unpackaged)	Width: 15.7 in/399 mm Depth: 14.7 in/373 mm Height: 12.1 in/308 mm Weight: 33.4 lb/15.2 kg				
550-sheet Tray (Packaged)	Width: 16.9 in/428 mm Depth: 18.4 in/468 mm Height: 7.6 in/193 mm Weight: 12.2 kg/5.5 kg				
550-sheet Tray (Unpackaged)	Width: 15.3 in/389 mm Depth: 14.7 in/373 mm Height: 4.3 in/108 mm Weight: 10.4 lb/4.7 kg				
Printer Stand (Packaged)	Width: 20.7 in/525 mm Depth: 22.2 in/565 mm Height: 9.2 in/235 mm Weight: 37.7 lb/17.1 kg				
Printer Stand (Unpackaged)	Width: 18.2 in/463 mm Depth: 20 in/510 mm Height: 17.3 in/440 mm Weight: 32.7 lb/14.8 kg				
Adjustable Stand (Packaged)	Width: 27.2 in/690 mm Depth: 26.3 in/670 mm Height: 9.1 in/232 mm Weight: 62.6 lb/28.4 Kg				
Adjustable Stand (Unpackaged)	Width: 24.6 in/626 mm Depth: 23.5 in/597 mm Height: 20.5 in/521 mm Weight: 50.9 lb/23.1 Kg				
REMOTE SERVICES					
Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time				
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® Devices based on actual usage, eliminating the need to manually manage supplies inventory				
INSTALLATION CONSIDERAT	TONS				
A clear area around the device is nec	essary for access and ventilation. The table below shows the area needed on each side for correct installation.				
Тор	3.9 in/100 mm				
Rear	3.9 in/100 mm				
Left	2.6 in/65 mm				
Right	4.3 in/110 mm				
Front	12 in /305 mm				
SYSTEM CERTIFICATION/RE	GULATORY COMPLIANCE				
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertifications				
WHAT'S IN THE BOX					
All Items Contained in the Box	B410 Printer Power Cord Installation Guide Product Safety Sheet Quick Use Guide Software and Documentation CD Pre-installed Starter Capacity Print Cartridges: Black cartridge: 6,000 print capacity ⁵				

SUPPLIES AND ACCESSORIES	NORTH AMERICA AND EUROPE*	ALL OTHER REGIONS		
Genuine Xerox Black Standard Capacity Toner Cartridge, Xerox® B410 Printer (6,000 Pages) ⁵	006R04725	006R04728		
Genuine Xerox Black High Capacity Toner Cartridge, Xerox B410 Printer (14,000 Pages) ⁵	006R04726	006R04729		
Genuine Xerox Black Extra High Capacity Toner Cartridge, Xerox B410 Printer (25,000 Pages)	006R04727	006R04730		
Genuine Xerox Black Imaging Kit, Xerox B410 Printer (75,000 Pages) ⁶	013R00702	013R00702		
OPTIONAL ACCESSORIES				
550-sheet Tray	097N02469			
Wireless Network Adapter	097N02470			
500+GB Hard Disk	097N02467			
Printer Stand	097S05244			
Adjustable Stand	497N07994			

^{*} North America (NA): U.S., Canada

Europe (XE): U.K., France, Germany, Spain, Italy, Netherlands, Belgium, Norway, Sweden, Finland, Denmark, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland, Andorra, Azores, Corsica, Greenland, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland, Andorra, Azores, Corsica, Greenland, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland, Andorra, Azores, Corsica, Greenland, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland, Andorra, Azores, Corsica, Greenland, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland, Andorra, Azores, Corsica, Greenland, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland, Andorra, Azores, Corsica, Greenland, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland, Andorra, Azores, Corsica, Greenland, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland, Andorra, Azores, Corsica, Greenland, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland, Andorra, Azores, Corsica, Greenland, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland, Andorra, Azores, Corsica, Greenland, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland, Andorra, Azores, Corsica, Greenland, Iceland, Andorra, Azores, Corsica, Greenland, Iceland, Andorra, Azores, Corsica, Greenland, Iceland, Andorra, Azores, Corsica, Greenland, Andorra, Corsica, Greenland, Andorra, Corsica, Greenland, Andorra, Corsica, Greenlan Lichtenstein, Luxembourg, Madeira, San Marino

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. Visit xerox.com/About-Xerox/Recycling.

For more information, visit us at xerox.com/office.



Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Requires Wireless Network Adapter
⁴ Requires 500+GB Hard Disk
⁵ Average standard pages. Declared yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage, and print mode.

⁶ Approximate pages. Declared yield will vary depending on job run length, media size/orientation, and print mode. For more information, visit office.xerox.com/latest/SUPGL-01.PDF