


VX2776-4K-MH DU - 27" 4K UHD THIN-BEZEL IPS MONITOR WITH USB-C, HDMI, AND DISPLAYPORT

Key Features


- 27 Inch 4K UHD (3840x2160p) IPS monitor with thin bezels and 60Hz refresh rate
- USB-C connectivity for fast data, audio and video transfer and 65W charging over one cable
- HDR10 content support for deep contrast, rich color and vibrant details
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- The VX2776-4K-MH DU supports laptops, PCs, and Macs with USB C, HDMI and DisplayPort inputs



27
DISPLAY



IPS
PANEL



3840 X 2160
RESOLUTION



FRAMELESS DESIGN
For a more immersive viewing experience

Product Description

Whether you're working hard on a presentation or watching a movie, the ViewSonic® VX2776-4K-mhdu is designed to take your setup to the next level. Featuring a SuperClear® IPS panel and a sleek frameless design, this monitor provides a near-seamless viewing experience that's ideal for multi-monitor configurations. Stunning 4K Ultra HD resolution delivers four times more pixels than Full HD monitors, so you can have the clarity and precision you need for work and play. USB-C 3.2 connectivity lets you send video, audio, data and 65W of charging power over a single cable, while HDMI and DisplayPort inputs keep you connected to your favorite devices. HDR10 content support helps this monitor display vivid colors at a brightness that substantially exceeds standard monitors.

Specifications

Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	3840 x 2160
Display Resolution	4K (3840x2160)
Static Contrast Ratio	1,300:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	10 bit (8 bit + A-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	4ms
Response Time (MPRT)	1ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	3840 X 2160
Mac® Resolution (max)	3840 X 2160
USB Type C	1
3.5mm Audio Out	1
HDMI 2.0 In	1
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	33
Eco Mode (optimized)	39
Consumption (typical)	46
Consumption (max)	125
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5
Power Supply	External
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)

Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI 2.0: 30 ~ 140 KHz DisplayPort: 30 ~ 140 KHz USB Type C: 30 ~ 140 KHz
Frequency Vertical	HDMI 2.0: 40 ~ 60 Hz DisplayPort: 40 ~ 60 Hz USB Type C: 40 ~ 60 Hz
Tilt (Forward/Back)	5° / 22°
Net (lbs)	8.6
Net Without Stand (lbs)	7.8
Gross (lbs)	13.2
Net (kg)	3.9
Net Without Stand (kg)	3.5
Gross (kg)	6
Packaging (in.)	27.4 " (W) x 18.2 " (H) x 5.2 " (D)
Physical (in.)	24.2 " (W) x 17.2 " (H) x 8.2 " (D)
Physical Without Stand (in.)	24.2 " (W) x 14.1 " (H) x 1.8 " (D)
Packaging (mm)	697 mm (W) x 462 mm (H) x 132 mm (D)
Physical (mm)	615 mm (W) x 437 mm (H) x 209 mm (D)
Physical Without Stand (mm)	615 mm (W) x 358 mm (H) x 46 mm (D)
Regulations	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, NRCan, NOM, Mexico Energy
PACKAGE CONTENTS	LCD Display, Power Cable, USB-C Cable, HDMI Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907019322



Contact Sales

[ViewSonic.com](https://viewsonic.com)

888.881.8781

email:

salesinfo@viewsonic.com