


Key Features

Stunning 4K Ultra HD Resolution | HDR Content Support | Responsive
Gameplay | Bright Images in Any Environment | Huge Screen Size for
Less Cost



Product Description


For an incredible entertainment experience from the comfort of home, the ViewSonic® PX701-4K projector delivers stunning Ultra HD resolution at an affordable price. While true 4K resolution and HDR support make this projector ideal for movie watching, users will enjoy its low 5ms input lag and 240Hz refresh rate for casual gaming. With 3200 lumens and room-filling sound, this projector provides bright visuals and immersive audio in nearly any room or environment. An automatic horizontal and vertical keystone feature, along with four-corner adjustment, delivers flexible setup of image sizes up to 300 inches.



3840 x 2160
RESOLUTION



3,200 ANSI
LUMENS



1.5-1.65
THROW RATIO

Contact Sales

- call: 888.881.8781
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Type:	DLP Lamp
Resolution Type:	4K (3840x2160)
Resolution:	3840 x 2160
Brightness (Lumens):	3,200 ANSI
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Throw Distance:	1m~10.96m (100"@3.32m)
Throw Ratio:	1.5-1.65
Keystone:	Vertical ($\pm 40^\circ$) / Horizontal ($\pm 40^\circ$)
Lens:	1.1x optical zoom
Light Source (watt):	203
Light Source Life, Normal (hours):	6000
Light Source Life, Dynamic Eco-Mode (hours):	20000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	12,000:1
Aspect Ratio:	16:9

Video Signal:

Frequency Horizontal:	15K-129KHz
Frequency Vertical:	23-240Hz

Compatibility:

PC Resolution (max):	3840 x 2160
PC Resolution (min):	640 x 480
Mac® Resolution (max):	3840 x 2160
Mac® Resolution (min):	640 x 480

Connector:

USB 2.0 Type A(1), 3.5mm Audio Out(1), RS232 Out(1), HDMI 2.0 In(2)

Audio:

Internal Speakers:	10W (x1)
--------------------	----------

Power:

Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	290W
Stand-by:	<0.5W

Controls:

Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	0-90%

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Weight (imperial):

Net (lbs):	6.2
Gross (lbs):	8.8

Weight (metric):

Net (kg):	2.8
Gross (kg):	4

Dimensions (imperial) (WxHxD):

Packaging (in.):	16.3 x 6.6 x 11.7
Physical (in.):	12.3 x 4.3 x 8.7

Dimensions (metric) (WxHxD):

Packaging (mm):	415.0 x168.0 x 297.0
Physical (mm):	312.0 x 108.0 x 222.0

General:

Regulations: FCC, cTUVus, ROHS

PACKAGE CONTENTS: PX701-4K, power cable, remote control, Quick Start Guide

Warranty: Three-year limited warranty on parts, labor and backlight

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907007893

Accessories:

HB10B, PJ-CASE-008, PJ-SCW-1001W, PJ-WMK-006, PJ-WMK-007, PM-FCP, VCB10, VSR100