



## 27" 1080P VIDEO CONFERENCING MONITOR WITH WINDOWS HELLO CERTIFIED IR 5MP WEBCAM, USB-C, HDMI, DP - VG2741V

### Key Features

---

- Enjoy better meetings with a 5MP camera, microphone and built-in speakers
- A Windows Hello-certified IR camera delivers a more secure sign on experience
- Find your perfect camera angle without compromising your ergonomic setup with  $\pm 5^\circ$  of tilt adjustment
- Connect your favorite devices using DisplayPort, HDMI, and USB-C\* inputs or the built-in USB hub
- Work and meet for longer with less strain thanks to ViewSonic's blue light technology



27  
DISPLAY



IPS  
PANEL



1920 x 1080  
RESOLUTION



### Product Description

---

Enjoy streamlined collaboration and video conferencing with the ViewSonic® VG2741V monitor. This 27" FHD monitor features a built-in 5MP integrated camera that supports secure, password-free sign-in with Windows Hello, while a 5-degree adjustable angle and privacy shutter ensure optimal positioning and peace of mind. Plus, with additional features including built-in camera, a microphone and powerful speakers, users can enjoy a fully immersive meeting experience where everyone looks and sounds their best. Get more clarity from vivid visuals with SuperClear® IPS technology and stay comfortable with a fully ergonomic stand. Whether you're working from home or at the office, the VG2741V makes it easy to stay connected with HDMI, DisplayPort, and USB-C\* inputs - along with a handy USB hub that includes both USB-A and USB-C ports.

\*USB-C port supports video, audio, and data only.

# Specifications

|                             | More Information                             |
|-----------------------------|----------------------------------------------|
| UPC                         | 766907032260                                 |
| Screen Size                 | 27                                           |
| Viewable Area (in.)         | 27                                           |
| Panel Type                  | IPS                                          |
| Display Resolution          | 1920 x 1080                                  |
| Display Resolution          | Full HD (1920x1080)                          |
| Static Contrast Ratio       | 1,500:1                                      |
| Dynamic Contrast Ratio      | 50,000,000:1                                 |
| Light Source                | LED                                          |
| Brightness                  | 250 cd/m2                                    |
| Colors                      | 16.7M                                        |
| Color Space Support         | 6 bit + FRC                                  |
| Aspect Ratio                | 16:9                                         |
| Response Time (Typical GTG) | 4ms                                          |
| Viewing Angles              | 178º horizontal, 178º vertical               |
| Backlight Life (Hours)      | 30,000                                       |
| Panel Surface               | Anti-Glare type, Hard-coating (3H), Haze 25% |
| Refresh Rate                | 120Hz                                        |
| PC Resolution (max)         | 1920 x 1080                                  |
| Mac® Resolution (max)       | 1920 x 1080                                  |
| USB Type A                  | 2                                            |
| USB Type C                  | 2                                            |
| 3.5mm Audio Out             | 1                                            |
| HDMI 1.4 In                 | 1                                            |
| DisplayPort                 | 1                                            |
| Internal Speakers           | 2W (x2)                                      |
| Eco Mode (Conserve)         | 16                                           |
| Eco Mode (optimized)        | 20                                           |
| Consumption (typical)       | 24                                           |
| Consumption (max)           | 72                                           |
| Voltage                     | AC 100-240V (universal), 50-60Hz             |
| Stand-by                    | 0.5                                          |
| Power Supply                | Internal                                     |

|                                     |                                                                                                                                        |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>Cable Organization</b>           | Yes                                                                                                                                    |
| <b>Kensington Lock Slot</b>         | 1                                                                                                                                      |
| <b>Webcam</b>                       | 5MP                                                                                                                                    |
| <b>Physical Controls</b>            | Key 1 (volume down), Key 2, Key 3, Key 4, Key 5, Key 6 (power)                                                                         |
| <b>On Screen Display</b>            | Input Select, Audio/MIC Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu                                                |
| <b>Temperature</b>                  | 32-104º F (0 - 40º C)                                                                                                                  |
| <b>Humidity (non-condensing)</b>    | 20-90%                                                                                                                                 |
| <b>VESA Compatible</b>              | 100 x 100 mm                                                                                                                           |
| <b>Frequency Horizontal</b>         | 30 ~ 135 KHz                                                                                                                           |
| <b>Frequency Vertical</b>           | 48 ~ 120 Hz                                                                                                                            |
| <b>Height Adjust</b>                | 150 mm / 5.9 in                                                                                                                        |
| <b>Swivel</b>                       | 90º                                                                                                                                    |
| <b>Pivot (Right/Left)</b>           | 90º / 90º                                                                                                                              |
| <b>Tilt (Forward/Back)</b>          | 5º / 20º                                                                                                                               |
| <b>Regulations</b>                  | cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy                                                                    |
| <b>Net (lbs)</b>                    | 11.7                                                                                                                                   |
| <b>Net Without Stand (lbs)</b>      | 8.2                                                                                                                                    |
| <b>Gross (lbs)</b>                  | 17.9                                                                                                                                   |
| <b>Net (kg)</b>                     | 5.3                                                                                                                                    |
| <b>Net Without Stand (kg)</b>       | 3.7                                                                                                                                    |
| <b>Gross (kg)</b>                   | 8.1                                                                                                                                    |
| <b>Packaging (in.)</b>              | 27.6 x 20.7 x 4.9                                                                                                                      |
| <b>Physical (in.)</b>               | 24.1 x 15.74 ~ 21.65 x 8.11                                                                                                            |
| <b>Physical Without Stand (in.)</b> | 24.1 x 15.25 x 2.33                                                                                                                    |
| <b>Packaging (mm)</b>               | 700 x 525 x 125                                                                                                                        |
| <b>Physical (mm)</b>                | 611.8 x 399.9 ~ 549.9 x 206.1                                                                                                          |
| <b>Physical Without Stand (mm)</b>  | 611.8 x 387.3 x 59.2                                                                                                                   |
| <b>Package Contents</b>             | VG2741V x1, 3-pin Plug x1, HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male; with Type-A adapter) x1, Quick Start Guide x1 |
| <b>Recycle/Disposal</b>             | Please dispose of in accordance with local, state or federal laws.                                                                     |
| <b>Warranty</b>                     | Three-year limited warranty on parts, labor and backlight                                                                              |

UPC: 766907032260



## Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email:

[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)