


## LS901-4K - 5,500 ANSI LUMENS 4K HDR LASER PROJECTOR

### Key Features

---


- Entertainment on a Bigger Screen than your TV
- True 4K Ultra HD Resolution
- Powerful Brightness, Stunning Detail
- Ultra-wide 21:9 Cinematic Views
- Easy Setup in Any Space



30 - 300 in. / 0.76 - 7.62 m  
**DISPLAY**



**PANEL**



3840 x 2160  
**RESOLUTION**



### Product Description

---

Bring the movie theater home with the ViewSonic® LS901-4K laser projector. Experience stunning 4K detail and vibrant colors that make your favorite films and shows come alive, even in big rooms. Enjoy a truly cinematic experience with HDR/HLG support and a widescreen 21:9 aspect ratio. Set it up anywhere thanks to flexible installation options like optical zoom, vertical lens shift, and 360° projection – you'll get a perfect picture every time. Plus, the long-lasting laser light source means you can enjoy brilliant entertainment for years.

### Specifications

---

More Information

UPC

766907027624

|                                                    |                                                                                                                    |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>Light Source</b>                                | DLP Laser                                                                                                          |
| <b>Display Resolution</b>                          | 4K (3840x2160)                                                                                                     |
| <b>Display Resolution</b>                          | 3840 x 2160                                                                                                        |
| <b>Brightness (Lumens)</b>                         | 5,500 ANSI                                                                                                         |
| <b>Screen Size</b>                                 | 30 - 300 in. / 0.76 - 7.62 m                                                                                       |
| <b>Throw Distance</b>                              | 1m-10.96m (100"@"3.32m)                                                                                            |
| <b>Throw Ratio</b>                                 | 1.2-2.04                                                                                                           |
| <b>Keystone</b>                                    | Vertical (± 30º) / Horizontal (± 30º)                                                                              |
| <b>Light Source (watt)</b>                         | Laser                                                                                                              |
| <b>Light Source Life, Normal (hours)</b>           | 20000                                                                                                              |
| <b>Light Source Life, Dynamic Eco-Mode (hours)</b> | 30000                                                                                                              |
| <b>Color Depth</b>                                 | 1.07 Billion Colors                                                                                                |
| <b>Dynamic Contrast Ratio</b>                      | 3,000,000:1                                                                                                        |
| <b>Aspect Ratio</b>                                | 16:9                                                                                                               |
| <b>Lens Shift</b>                                  | V: 0%, -21%                                                                                                        |
| <b>Frequency Horizontal</b>                        | 15K-255KHz                                                                                                         |
| <b>Frequency Vertical</b>                          | 23-240Hz                                                                                                           |
| <b>PC Resolution (max)</b>                         | 3840 x 2160                                                                                                        |
| <b>PC Resolution (min)</b>                         | 640 x 480                                                                                                          |
| <b>Mac® Resolution (max)</b>                       | 3840 x 2160                                                                                                        |
| <b>Mac® Resolution (min)</b>                       | 640 x 480                                                                                                          |
| <b>USB 2.0 Type A</b>                              | 1                                                                                                                  |
| <b>Ethernet LAN (RJ45)</b>                         | 1                                                                                                                  |
| <b>3.5mm Audio Out</b>                             | 1                                                                                                                  |
| <b>Control (RS-232)</b>                            | 1                                                                                                                  |
| <b>HDMI 2.0 (with HDCP 2.2)</b>                    | 2                                                                                                                  |
| <b>Internal Speakers</b>                           | 15W (x2)                                                                                                           |
| <b>Voltage</b>                                     | 100-240V+/- 10%, 50/60Hz AC                                                                                        |
| <b>Consumption (typical)</b>                       | 245W                                                                                                               |
| <b>Stand-by</b>                                    | <0.5W                                                                                                              |
| <b>Physical Controls</b>                           | Keypad, Power key                                                                                                  |
| <b>On Screen Display</b>                           | Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality) |
| <b>Temperature</b>                                 | 32-104º F (0 - 40º C)                                                                                              |
| <b>Kensington Lock Slot</b>                        | 1                                                                                                                  |
| <b>Net (lbs)</b>                                   | 10.69                                                                                                              |

|                         |                                                                                                                                                             |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Gross (lbs)</b>      | 15.0                                                                                                                                                        |
| <b>Net (kg)</b>         | 4.85                                                                                                                                                        |
| <b>Gross (kg)</b>       | 6.8                                                                                                                                                         |
| <b>Packaging (in.)</b>  | 19.5 x 15.2 x 7.7                                                                                                                                           |
| <b>Physical (in.)</b>   | 13.3 x 11.0 x 5.2                                                                                                                                           |
| <b>Packaging (mm)</b>   | 496.0 x 387.0 x 195.0                                                                                                                                       |
| <b>Physical (mm)</b>    | 337.0 x 280.0 x 132.0                                                                                                                                       |
| <b>Regulations</b>      | cTUVus                                                                                                                                                      |
| <b>Package Contents</b> | LS901-4K, power cable, remote control, Quick Start Guide                                                                                                    |
| <b>Warranty</b>         | Three-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration). |
| <b>Recycle/Disposal</b> | Please dispose of in accordance with local, state or federal laws.                                                                                          |

UPC: 766907027624



**Contact Sales**  
[ViewSonic.com](https://www.viewsonic.com)

888.881.8781   
email:  
[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)