PRO MP161 E2U

Business & Productivity Monitor

Collaborate with

#DAMUR

Upcycle Carton Design

Tripod not included.

Portable Design
Bring it anywhere you want without any strain or pressure.

1/4" Tripod Mount Support
Lock the portable monitor with the tripod with the 1/4" tripod socket to make it more flexible to stand by you.

Lengthened Ergo Fold-out Kickstand 0˚ ~ 180˚
Promotes a more upright screen position, ensuring better ergonomics.

L-shaped Cable
L-shaped Cables prevent cable bending, ensuring convenience and uninterrupted use.

Type C Display
Built-in an USB Type-C connection allows you to effortlessly connect to and charge your devices

Ultra Slim
Ultra slim profile offers a minimalistic look that looks great in any space and desk.

Post-Consumer Recycled Material (PCR)
Using post-consumer recycled material in monitor bodies to minimize environmental impact and promote sustainability.

Anti-Flicker Technology & Less Blue Light
With MSI Anti-Flicker technology & Less Blue Light, a stable output current for the monitor & effectively reduce blue light is provided to protect your eyes

Eye-Q Check
Help user to have a self-check eyes & remind to take a rest while using the monitor for a long time.

Built-in Speakers
Built-in speakers allow you to listen clearly without connecting external speakers

SPECIFICATIONS

Type / Size	15.6"
Active Display Area (mm)	344.16(H) x 193.59(V)
Curvature	Flat
Panel Type	IPS
Resolution	1920 x 1080 (FHD)
Pixel Pitch	0.17925(H) x 0.17925(V)
Aspect Ratio	16:9
Brightness (nits)	250
Contrast Ratio	800:1
Refresh Rate	60Hz
Response Time	4ms (GTG)
View Angles	170˚(H) / 170˚(V)
sRGB	53% (CIE 1976)
Surface Treatment	Anti-glare
Display Colors	16.7M
Color Bit	8 bits (6 bits + FRC)
Video Interface	1x Mini-HDMI™ 2.0b (FHD@60Hz) 2x Type-C (DP 1.2a signal with Alt mode & 15W Power Delivery / Power Input)
Speaker	2x 1.5W
Power Type	External USB Power (Type C interface)
Adjustment (Tilt)	0˚ ~ 180˚ (stand 13mm lengthened)
Kensington Lock	N/A
Tripod Socket	1/4" Standard Tripod Socket
VESA Mounting	N/A
Product Dimension with Stand (W x D x H)	362.26 x 18.8 x 233.84 mm (14.26 x 0.74 x 9.21 inch)
Product Dimension without Stand (W x D x H)	362.26 x 10.8 x 233.84 mm (14.26 x 0.43 x 9.21 inch)
Weight (NW / GW)	0.8 kg (1.76 lbs) / 1.4 kg (3.09 lbs)
Dimension (W x D x H) With Carton	425 x 290 x 55 mm (16.73 x 11.42 x 2.17 inch)
Accessory	1x L-shaped right angle Mini-HDMI to HDMI cable, 1x L-shaped right angle Type-C to Type-C cable (1M), 1x Protection Bag, 1x Quick Guide
Note	HDMI: 1920 x 1080 (Up to 60Hz) Type-C: 1920 x 1080 (Up to 60Hz) Adaptive-Sync support

Accessory :
L-Shaped Type-C & Mini HDMI to HDMI cables

1. Power Button & OSD Controller
2. 1x Type-C (DP Alt & 15W Power Delivery / Power Input)
3. 1x Type-C (DP Alt & 15W Power Delivery / Power Input)
4. 1x Mini-HDMI™ 2.0b (FHD@60Hz)