CyberPower

XC625 STANDBY UPS SYSTEM



Offers significant energy savings, battery backup and surge protection.

The CyberPower XC625 uninterruptible power supply (UPS) system provides battery backup and surge protection for lightning-induced surges and other power events that can damage electronic equipment. This unit delivers battery backup to power connected electronics during a utility power failure and enough runtime to perform a graceful shutdown to protect against the loss of data and damage to valuable electronics during longer outages.

Including a sleek design, this UPS is perfect for all your home office and entertainment needs, including computers, gaming consoles, and broadband routers.

With a $100,000 lifetime connected equipment guarantee and a three-year warranty, you can trust CyberPower's commitment to the quality of the XC625.

TYPICAL APPLICATIONS

- Desktop Computers
- Personal Electronics

FEATURES

- 625 VA / 375 W
- 8 Standard Outlets
- Standby Topology
- Full-time Surge Protection and Battery Backup
- Three-Year Warranty

SPECIFICATIONS

GENERAL	
UPS Topology	Standby
Energy Saving	Yes
ENERGY STAR® Qualified	Yes
INPUT	
Nominal Input Voltage	120 VAC
Frequency Range	47 – 63 Hz
Circuit Breaker	15 A
Plug Type	NEMA 5-15P
Cord Length	5 ft

OUTPUT	
VA	625 VA
Watts	375 W
On Battery Voltage	120 VAC ± 5%
On Battery Frequency	50/60 Hz ± 1%
On Battery Waveform	Simulated Sine Wave
Outlet Type	NEMA 5-15R
Outlets – Total	8
Outlets - Battery & Surge Protected	4
Outlets - Surge-Only Protected	4
Outlets - Widely Spaced	4
Overload Protection	Internal Circuitry Limiting Circuit Breaker

XC625 STANDBY UPS SYSTEM



SPECIFICATIONS CONT.

BATTERY	
Runtime at Half Load (min)	9
Runtime at Full Load (min)	2
Battery Type	Sealed Lead-Acid
Battery Quantity	1
Typical Recharge Time	8 Hours
SURGE PROTECTION & FILTERING	
Surge Suppression	890 J
EMI/RFI Filtration	Yes
MANAGEMENT & COMMUNICATIONS	
HID Compliant USB Port	Yes
LED Indicators	Power On
Audible Alarms	On Battery, Low Battery, Overload, Fault
Software	PowerPanel® Personal
PHYSICAL	
Keyhole Mounting Slots	Yes, 2 x 2-direction slots
Dimensions (WxHxD) (in.)	9.8 × 5.8 × 3.2
Weight (lbs.)	5.0

ENVIRONMENTAL	
Operating Humidity	0 – 95% (non-condensing)
Operating Temperature	32°F to 104°F (0°C to 40°C)
CERTIFICATIONS	
Safety	UL1778, cUL, FCC DOC Class B, CEC
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	Three-Year Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	$100,000

©2018 Cyber Power Systems (USA), Inc. CyberPower is a registered trademark and brand of Cyber Power Systems (USA), Inc. All rights reserved. All other trademarks are the property of their respective owners. CyberPower reserves the right to change, without notice, marketing programs, product offerings and specifications. **www.cyberpowersystems.com**