


VX3218-PC-MHD - 32" OMNI CURVED 1080P 1MS 165HZ GAMING MONITOR WITH ADAPTIVE SYNC

Key Features

- 32 Inch Full HD (1920x1080p) 1500R curved gaming monitor with thin bezels
- 165Hz refresh rate and 1ms MPRT response time (with DisplayPort) for ultimate gaming experience
- · Adaptive Sync technology enables fluid and tear-free gameplay
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- An arsenal of pre-set customizable visual modes keeps you ready for any FPS, RTS, or MOBA games
- The VX3218-PC-MHD supports laptops, PCs and Macs with HDMI and DisplayPort inputs







PANEL



1920x1080 RESOLUTION



Product **Description**

With an immersive 1500R curved screen and Full HD 1080p resolution, the ViewSonic® VX3218-PC-MHD monitor provides an incredible viewing experience for work or play. With features including a high 165Hz* refresh rate, 1ms (MPRT) response time and adaptive sync technology, this monitor virtually eliminates screen tearing and stuttering for a fluid gaming experience. The VX3218-PC-MHD also comes equipped with ViewSonic exclusive ViewMode™ presets, which offer optimized screen performance for different home entertainment applications such as watching movies, editing files, or playing video games. Two HDMI (v1.4) inputs, and one DisplayPort (v1.2) input offers flexible connectivity for both general use and entertainment. *165Hz refresh rate with DisplayPort

Specifications

Screen Size	32
Viewable Area (in.)	31.5
Panel Type	MVA
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	4,000:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	300 cd/m2
Colors	16.7M
Color Space Support	6 bit+FRC
Aspect Ratio	16:9
Response Time (Typical GTG)	6ms
Response Time (MPRT)	1ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Curvature	1500R
Refresh Rate	165Hz
PC Resolution (max)	1920×1080
Mac® Resolution (max)	1920×1080
3.5mm Audio Out	1
HDMI 1.4 In	2
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	23W
Eco Mode (optimized)	29W
Consumption (typical)	35W
Consumption (max)	41W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	External
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI (v1.4): 30 \sim 160 KHz, DisplayPort (v1.2): 30 \sim 193 KHz
Frequency Vertical	HDMI (v1.4): 48 ~ 144 Hz, DisplayPort (v1.2): 48 ~ 165 Hz
Tilt (Forward/Back)	5º / 20º
Net (lbs)	10.8
Net Without Stand (lbs)	9.3
Gross (lbs)	16.1
Net (kg)	4.9
Net Without Stand (kg)	4.2
Gross (kg)	7.3
Packaging (in.)	38.2 x 20.6 x 6.7
Physical (in.)	27.9 x 20.2 x 9.0
Physical Without Stand (in.)	27.9 x 16.5 x 3.7
Packaging (mm)	970.0 x 523.0 x 170.0
Physical (mm)	709.0 x 513.0 x 228.0
Physical Without Stand (mm)	709.0 x 419.0 x 93.0
Regulations	cTUVus, FCC-B, ICES003, CEC, NOM, Mexico Energy
PACKAGE CONTENTS	VX3218-PC-MHD, Power Cable, DisplayPort Cable, AC/DC Adapter, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907010190







Contact Sales ViewSonic.com 888.881.8781 email: salesinfo@viewsonic.com