





VIEWSONIC 34" UWQHD ERGONOMIC 21:9 CURVED DOCKING MONITOR WITH 100W USB-C AND RJ45 ETHERNET

Key Features


- **BUILT-IN DOCKING STATION:** Simplify your setup with USB-C single-cable connectivity, an RJ45 Ethernet port, USB hub, and more
- **IMMERSIVE CURVED SCREEN:** Experience greater immersion and less visual discomfort with a 1500R curved screen
- **ULTRA WIDE QHD CLARITY:** Enjoy stunning detail and extra screen space with 4K resolution and a 21:9 aspect ratio
- **STREAMLINED CONTROL:** Manage settings and split-screen functions easily with an On-Screen Display (OSD) menu and vDisplayManager
- **ERGONOMIC COMFORT:** Work for longer in greater comfort with a flexible, ergonomic design
- **LOWER TCO:** From installation to disposal, this monitor is designed to cut down on the total cost of ownership



34
DISPLAY



VA
PANEL



3440 X 1440
RESOLUTION



Product Description

Streamline your setup and see the bigger picture with the ViewSonic® VG3456CA USB-C docking monitor. Save hundreds with a built-in docking station that includes USB-C connectivity with 100W power delivery, an RJ45 Ethernet port, and an integrated USB hub that makes it easy to connect the latest laptops and systems. This 34" curved ultrawide monitor offers expansive screen space with a UWQHD 3440x1440 resolution. Its 21:9 aspect ratio provides additional workspace, allowing you to display more content simultaneously - without the bezel gap that can be typically found in dual-monitor setups. The immersive 1500R curvature enhances viewing comfort and reduces eye strain by mimicking the natural curvature of the human eye. Elevate your productivity and unlock more screen space with the VG3456CA USB-C monitor today.

Specifications

	More Information
UPC	766907033670
Screen Size	34
Viewable Area (in.)	34
Panel Type	VA
Display Resolution	3440 x 1440
Display Resolution	UWQHD (3440x1440)
Static Contrast Ratio	3,000:1
Dynamic Contrast Ratio	80M:1
Light Source	LED
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	10 bit (8 bit + FRC)
Aspect Ratio	21:9
Response Time (Typical GTG)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Curvature	1500R
Refresh Rate	100Hz
PC Resolution (max)	3440 X 1440
Mac® Resolution (max)	3440 X 1440
USB Type A	4
USB Type C	100W x 1, 15W x 1
Ethernet LAN (RJ45)	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	5W (x2)
Eco Mode (Conserve)	33W
Eco Mode (optimized)	38W
Consumption (typical)	43W
Consumption (max)	210W
Voltage	100-240 VAC, 50-60Hz
Stand-by	0.3

Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	30 ~ 150 KHz
Frequency Vertical	48 ~ 100 Hz
Height Adjust	110 mm / 4.3 in
Swivel	120°
Tilt (Forward/Back)	5° / 40°
Regulations	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, NOM, Mexico Energy
Net (lbs)	20.7
Net Without Stand (lbs)	15.4
Gross (lbs)	33.7
Net (kg)	9.4
Net Without Stand (kg)	7
Gross (kg)	15.3
Packaging (in.)	39 " (W) x 19.5 " (H) x 9.4 " (D)
Physical (in.)	31.81 " (W) x 16.7~21.01 " (H) x 9.3 " (D)
Physical Without Stand (in.)	31.81 " (W) x 15.41 " (H) x 4.53 " (D)
Packaging (mm)	990 mm (W) x 495 mm (H) x 238 mm (D)
Physical (mm)	808 mm (W) x 424.1~533.7 mm (H) x 236.2 mm (D)
Physical Without Stand (mm)	808 mm (W) x 391.3 mm (H) x 115 mm (D)
Package Contents	LCD Display, Power Cable, HDMI Cable, USB Type C Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907033670



Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email: salesinfo@viewsonic.com