

PRODUCT SELECTION GUIDE

Network Operations / MSPs Security Operations & MSSPs



Product / Feature	LinkSprinter	Test Accessory	LinkRunner AT 1500	LinkRunner AT 3000	LinkRunner AT 4000	LinkRunner 10G	EtherScope nXG	AirCheck G3	AirMagnet Survey PRO	CyberScope ¹	
Ethernet Copper	10/100/1000 Mbps		10/100/1000 Mbps (detects Multi-Gig and 10 Gbps)			10/100 Mbps & 1/2.5/5/10 Gbps				10/100 Mbps & 1/2.5/5/10 Gbps	
Ethernet Fiber				1 Gbps		1/10 Gbps				1/10 Gbps	
PoE Test (up to 90W at PSE, 71.3W at PD)	Voltage only		•	•	•	•	•			•	
Wiremap, Toner, & Cable Test Open/Short/Length	Cable Test Only		•	•	•	•	•			•	
Default Gateway, DNS, IP	1 IP Target		Unlimited Targets								Unlimited Targets
Wi-Fi Test/Heatmaps (up to Wi-Fi 7 & 2.4, 5, 6 GHz band)							•	•	•	•	
Wi-Fi Connection & Roaming Test							•	•	•	•	
Discover SSID, AP, & Clients							•	•	SSIDs & APs Only	•	
AirWISE® Intelligence							•	•	•	•	
AP & Client Locate							•	•	AP Locate Only	•	
RF Traffic Statistics							•	•		•	
AirMapper™ Site Survey ²							•	•	•	•	
Bluetooth/BLE Site Survey							•	•		•	
Wi-Fi Spectrum Analysis ³							Optional NXT-2000			Optional NXT-2000	
Network Topology Mapping ²					•	•	•	•		•	
Network Discovery					•	•	•	•		•	
Packet Capture					•	•	•	•		•	
LANBERT™ Media Qualification ⁴				Up to 1 Gbps		Up to 10 Gbps				Up to 10 Gbps	
iPerf Performance Test		•			•	•	•	•	•	•	
Line Rate Performance Test				Reflector Only		10 Gbps				10 Gbps	
Remote View/Control ²			•	•	•	•	•	•	Windows Apps	•	
Integration of Nmap into AutoTest & Network Discovery										•	
Standalone Nmap App / Custom Script Support										•	
Automated Discovery Monitoring										•	
Option to Disable Functionality*			•	•	•	•	•	•		•	

¹ The full function CE version includes wired Ethernet and wireless (Wi-Fi and BT/BLE) capabilities. Wired only (XRF) and wireless only (AIR) versions are also available - specific capabilities depend on the version. Refer to the CyberScope online [Model Comparison](#) for details.

² Depending on each product's capabilities, Link-Live gated features can include AirMapper enhanced site survey visualizations, advanced Network Topology Mapping filters, and Remote View/Control; these features are available to customers with AllyCare support or a Link-Live Enabled Features subscription.

³ NXT-2000 is not supported by AirCheck G3 or CyberScope Air testers manufactured before August 2024. Contact Customer Service at www.netally.com/contact-us for more information and available options.

⁴ LANBERT and Performance tests require the use of two units (or a loopback), a controller and remote.

*Allows disabling of specific product capabilities for use in secure environments.

Toll-Free (North America) 1-844-878-2559
International +1-719-755-0770

