

LS832WU - 5000 ANSI LUMENS WUXGA ULTRA SHORT THROW LASER INSTALLATION PROJECTOR

Key Features


- High brightness 5000 Lumens WUXGA laser projector with 0.25 ultra short throw and advanced visual features
- Long-lasting laser phosphor light source allows the lamp to shine bright for up to 30,000 hours
- 0.25 ultra short throw ratio, HV keystone, 4 corner adjustments and 360 degree projection
- Schedule, and manage the projector remotely with Crestron, AMX, Extron, PJ Link, ATEN, and ViewSonic's vController
- Supports most media players, PCs, Macs, and mobile devices with inputs such as HDMI, USB and Ethernet LAN



87 - 120 in. / 2.21 - 3.05 m
DISPLAY



PANEL



3840 x 2160
RESOLUTION



Product Description

The ViewSonic® ultra-short throw LS832WU projector is the ultimate digital signage solution for public and commercial spaces such as auditoriums, museums, storefronts, shopping malls and airports. Featuring laser phosphor technology, the LS832WU projector delivers 5,000 ANSI lumens of brightness to ensure crisp images even in spaces with ambient lighting. Enjoy a maintenance-free projection experience without having to deal with complicated lamp replacements. An ultra-short throw ratio enables this projector to create 100" images from just 11" away. Enjoy screen sizes up to 170" at a lower cost-per-inch compared to commercial displays. The LS832WU laser projector comes loaded with features like H/V keystone, automated four corner adjustment and flexible installation options. Enjoy comprehensive LAN control for centralized management and compatibility with Crestron, AMX, Extron and PJ Link AV control systems.

Specifications

	More Information
UPC	766907021912
Light Source	DLP Laser
Display Resolution	WUXGA (1920x1200)
Display Resolution	1920 x 1200
Brightness (Lumens)	5,000 ANSI
Screen Size	87 - 120 in. / 2.21 - 3.05 m
Throw Distance	0.17-0.66m (100"@0.28m)
Throw Ratio	0.253
Keystone	Vertical (+/- 10º) / Horizontal (+/- 10º)
Lens	Fixed Zoom
Light Source (watt)	Laser
Light Source Life, Normal (hours)	20000
Light Source Life, Dynamic Eco-Mode (hours)	30000
Color Depth	1.07 Billion Colors
Dynamic Contrast Ratio	3,000,000:1
Aspect Ratio	16:10
Input Lag	37ms
Frequency Horizontal	15K- 91KHz
Frequency Vertical	24- 85Hz
PC Resolution (max)	3840 x 2160
PC Resolution (min)	640 x 480
Mac® Resolution (max)	3840 x 2160
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
USB 2.0 Type B	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
3.5mm Audio In	1
3.5mm Mic In	1
Control (RS232)	1
HDMI 2.0 (with HDCP 2.2)	2
VGA In	1
VGA Out	1

Internal Speakers	10W (x1)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	328W
Stand-by	<0.5W
Physical Controls	Keypad, Power key
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104° F (0 - 40° C)
Kensington Lock Slot	1
Net (lbs)	12.8
Gross (lbs)	17.9
Net (kg)	5.8
Gross (kg)	8.1
Packaging (in.)	20.4 x 16.5 x 12.3
Physical (in.)	15.0 x 12.5 x 5.2
Packaging (mm)	518.0 x 420.0 x 313.0
Physical (mm)	382.0 x 318.0 x 132.0
Regulations	cTUVus
Package Contents	LS832WU projector, power cable, remote control, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907021912



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com